



CUTTING OIL

Cooling lubricants for metalworking

KEY FEATURES


- Reinforced mineral cutting oil for drills and tappers
- Compatible with all metals, ferrous or non-ferrous
- Adheres strongly to the tool
- Chips are effectively removed from the cutting zone
- Very good oxidation resistance
- Heat-resistant and pressure-resistant
- Reduces the wear of cutting tools as well as production costs (material and labor) by reducing the coefficient of friction
- Ensures high-quality machining of the workpieces
- Silicone-free

AREAS OF APPLICATION

- Threading
- Grinding (drilling)
- Milling
- Punching by machining or forming

HOW TO USE

- Das Aerosol vor Gebrauch 1 Minute kräftig schütteln
- 2 Anwendungsmöglichkeiten dank des Cobra²-Doppelsprühkopfes :
 - Präzise Anwendung mit hochgeklapptem Kapillarröhrchen
 - Flächige Sprühen mit dem Diffusor (aus ca. 15 cm Abstand zur Oberfläche)
- Vor dem Lackieren entfetten Sie die Teile mit dem INDUSTRIAL CLEANER, Art.-Nr.: 805155



PHYSICOCHEMICAL PROPERTIES

- | | |
|---------------------|-------------------------|
| • Physical state: | Liquid |
| • Colour: | Yellow-brown |
| • Odor: | Characteristic |
| • Flash Point: | Below 0°C |
| • Water Solubility: | Insoluble |
| • Soluble in: | Most organic solvents |
| • Density: | 0.838 g/cm ³ |

PACK SIZE

Aerosol 650/500 ml x 12

Part number: **805421**

EAN code: 3429978054216

STORAGE

Container is pressurized: Can explode if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not puncture or burn – even after use. Protect from sunlight. Do not expose to temperature above 50°C / 122°F.