

Eaton 012336

Catalog Number: 012336

Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure. Connection terminal, 160A, 1p, round/round

General specifications



Product Name	Catalog Number
Eaton xEffect K-Type Terminal Enclosures Switch- & Controlgear Enclosure	012336
	EAN
	4015080123361
Product Length/Depth	Product Height
100 mm	115 mm
Product Width	Product Weight
37 mm	0.563 kg
Compliances	
RoHS conform	

Product specifications

Used with

Accessory panel building
General switchboard accessory

Special features

Conversion kits for strip terminal in cable connection available separately
Terminal covers available separately
Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN, protective earth (ground) symbol
Relationship of rated operational current -terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021
Outer terminal for round or sectoral conductor, other side for Cu strip

Type

Accessory panel building
General switchboard accessory

Features

Contact safe

Accessory/spare part type

Terminals, 160 – 1000 A
Terminations

Connection type

Clamp
Screwing

Number of poles

Single-pole

Rated operation current (Ie)

160 A

Resources

Catalogs

[eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf](#)

Declarations of conformity

[DA-DC-03_K95_K150_K240_K2x240_K3x185](#)

[eaton-xeffect-k-type-terminals-declaration-of-conformity-en-us.pdf](#)

Drawings

[eaton-control-panels-xeffect-k-type-terminal-3d-drawing.eps](#)

[eaton-control-panels-terminals-xeffect-k-type-terminal-3d-drawing.eps](#)

Installation instructions

[IL015110ZU](#)

mCAD model

[eaton-K95_1N_BR-drawing.dwg](#)

[eaton-K95_1N_BR-3d-model.stp](#)

System overview

[eaton-control-panels-terminals-xeffect-k-type-terminal-explosion-drawing-002.eps](#)

Mounting method

Screw

Suitable for

Fine strand conductors
Useful for stranded conductors

Nominal current

160 A

Number of connections (Less Than 6 mm squared)

0

Number of connections (Less Than AWG 6)

0

Number of connections (Greater Than 25 mm squared)

2

Number of connections (Greater Than 250 kcmil)

0

Number of connections (10 mm squared)

0

Number of connections (16 mm squared)

0

Number of connections (25 mm squared)

0

Number of connections (250 kcmil)

0

Number of connections (AWG 2)

0

Number of connections (AWG 4)

0

Number of connections (AWG 4/0)

0

Number of connections (AWG 6)

0

Number of connections (total)

2

Rated insulation voltage (Ui)

1000 VAC

Number of outputs

1

Terminal capacity (aluminum cable)

35 mm² - 70 mm² (1x)

Terminal capacity (copper/aluminum cable)

16 mm² - 95 mm² (1x)

Conductor cross section, input - max

95 mm²

Conductor cross section, output - min

10 mm²

Conductor cross section, input - min

10 mm²

Conductor cross section, input AWG - min

3 mm²

Conductor cross section, input AWG - max

8 mm²

Conductor cross section, output - max

95 mm²

Conductor cross section, output AWG - max

8 mm²

Conductor cross section, output AWG - min

3 mm²

Number of inputs

1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia