



EN ISO 20345:2011



RITMO

TIMBA
91294-11L
S3 SRC
Size: 35-48

Weight: 540 gr.

Fit: 11

Working Environment:

 Finishing-off building, Logistics
 and Light Industry, Components
 and Automotive, Multipurpose


FEATURES

UPPER

 Mesh H.T. no ladder
 Drummed Suede Leather Hydro
 1,6-1,8 mm
 Mesh H.T. no ladder
 3D Air circulation 320 gr.

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE
PU / PU ESD-PLUS SRC

 Double density PU sole, Outer- and
 in-between sole with ESD
 compound. For use in contact with
 sensitive electronic equipment.
 Light and comfortable, very
 versatile, highly non-slip SRC
 Antislip standard.

TECHNOLOGIES

Removable Insole

 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"

Protection elements
ZERO(k)
 ANTIPERFORATION

alu-sxt2.0
 aluminium

 A new aluminium multi-thicknesses
 toecap, which delivers a highly
 performing protection where needed.
 Resistant to impact of over 200J. Non
 Metallic anti-perforation insert.
 Resistant to over 1100 N with zero
 perforation.

Lateral stability
dynamic H C control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.

Torsional stability
STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.

Electrical features

 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


SRC (SRA+SRB)


 SOLE 91
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.54
	HEEL (CONTACT ANGLE °) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.29
	HEEL (CONTACT ANGLE °) ≥ 0.13	

EN ISO 20344:2011