

2000 Ts PLUS - Model 156

Superior breathable microporous laminate technology, Type 4/5/6 protection

Sealed seams provide additional protection in low hazard liquid spray applications..

DESIGN

MICROGARD® 2000 is designed to allow water vapor (perspiration) to escape from the suit yet will withstand saturation of liquid chemicals and filter 100% of particulates down to 0.01 microns in size*.

With serged and taped seams, MICROGARD® 2000 Ts PLUS provides an exceptional overall barrier to low hazard liquid spray and fine particulates.

* KAKEN Particle penetration test

SERGED AND TAPED SEAMS

Internal stitching which is overtaped to offer increased strength and an effective barrier to liquids and particulates.

SUIT FEATURES

- Hood
- Elasticated wrists, waist and ankles
- · 2-way front zipper with resealable storm flap
- Finger loops
- Chin Strap
- · Attached socks with boot overflaps

COLOURS

White

SIZES

S-5XL





Industries

- Life Sciences
- Automotive
- Metal fabrication
- Food Processing
- Defense
- Agriculture
- Automotive Aftermarket
- Chemical
- Emergency Medical Services
- Machinery and Equipment

- Oil and gas
- Utilities
- Nuclear


Applications

- Product inspection
- Loading and hauling
- Fibre Glass/Resin Applications/Ceramic Fibres
- Body painting including surface inspection
- Cleaning of plant and machines
- Maintaining lab furniture and equipment


KEY FEATURES & BENEFITS

- Proven protective barrier to low concentration liquid chemicals, liquid & particulate biological hazards
- Comfortable to wear featuring moisture vapor permeable fabric ("breathable") to help reduce the risk of heat stress
- Optimized body fit, improving wearer comfort and safety
- Anti-static, tested according to EN 1149-5
- Ultra Low Linting, reduced risk of contamination in critical areas
- Silicone free, critical in spray painting applications
- Tunnelled elasticated hood, wrists and ankles Helps to minimize the risk of linting and cross contamination

Material Diagram



Seam Diagram



Performance Standards





















Product Information

Product Information	
Available Sizes	S, M, L, XL, 2XL, 3XL
Color	White
Country Of Origin	China
Models Available	103, 111, 122
Packaging Overview	Individually Packed
Product Material	Microporous polyethylene Laminate non-woven
Product Reference	2000 Ts PLUS - Model 156
Standards Overview	CE CATEGORY III (Type 4-B, Type 5-B, Type 6-B, EN 1073-2, EN 14126, DIN 32781, EN 1149-5)
Seam Type	Stitched and Taped
Shelf Life	5 years



Suit components & accessories

Suit Components and Accessories

Design Features

Coverall, 3-piece hood, elasticated hood, waist, wrists, ankles and overflaps. 2-way front zipper with resealable storm flap, finger loops and intergrated socks with boot overflaps.

For additional in formation visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00

Asia Pacific Region Ansell Global Trading Center T: +603 8310 6688 North America Region Ansell Healthcare Products LLC T: +1 800 800 0444

Latin America & Caribbean Region

Australia Ansell Limited T: +61 1800 337 041

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Ansell, $^{\textcircled{6}}$ and $^{\textcircled{m}}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\textcircled{6}}$ 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

