



SHELL	A±0.38	B±0.12	C±0.10	D±0.25	G±0.25	PART NUMBER
09	30.81	24.99	16.96	16.79	5.90	D09P13A*PV00**
15	39.14	33.32	25.18	25.12	5.90	D15P13A*PV00**
25	53.03	47.04	39.12	38.84	5.70	D25P13A*PV00**
37	69.32	63.50	55.68	55.30	5.70	D37P13A*PV00**

LF FOR LEAD FREE

Plating: 4 --> flash AU
Plating: 6 --> 0.76µ AU

Technical characteristics:
Shell: steel tin/Zinc Cr3 plated
Insulators: self-extinguishing thermoplastic, UL Class 94V0
Contacts size 20: brass, gold on mating end, bright tin on termination end over nickel on entire contact
Cycles :500 For plating 6
Cycles :200 for plating 4

Screwlock: brass, tin/Zinc Cr3 plated

Electrical characteristics:
max. current rating: 5A
Test voltage: 1000V
Rated voltage: 300V
Contact resistance: <15mΩ
Shell resistance: <5mΩ
Insulation resistance: >5000MΩ

Climatic characteristics:
Operating temperature range: -55°C +125°C

Dimensions:
In accordance with MIL-C-24308

FOR ROHS DETAILS REFER DWG. NO: C01-8646-0000

European Views

rev	ecn no	dr	date
B	105-0124	JS	2005/07/27
C	106-0074	SK	2006/06/08
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
TOLERANCES UNLESS OTHERWISE SPECIFIED				
Dr	JOHN SLEEBA	1996/09/10	ANGULAR	0.X ±0.1
Eng	GEORGE VJ	1996/09/10	LINEAR	0.XX ±0.1
Chr	GEORGE VJ	2005/07/27	0.XX* ±1*	0.XXX ±0.1
Appr	KVSD	2005/07/27	Product family	D-SUB
title PIN CONNECT.SUB right angled spill with screwlock, metal bracket				Rev. C
catalog no DELTA-D				spec no C01-8646-0484
CUSTOMER				sheet 1 of 1



Copyright FCI.