



Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Number of Positions: 19

Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Centerline (Pitch): 5.08 mm [.2 in ]

Number of Rows: 1

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Wire Protection                   | With                  |
| Terminal Block Connector Type     | Header                |
| Connector System                  | Wire-to-Board         |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

|                        |                |
|------------------------|----------------|
| Stacking Configuration | Side Stackable |
| Number of Positions    | 19             |
| Number of Rows         | 1              |
| Wire Entry Angle       | 35°            |
| Wire Entry Location    | Side           |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 300 VAC |
|-------------------|---------|

Body Features

|                       |       |
|-----------------------|-------|
| Primary Product Color | Black |
|-----------------------|-------|



|                                      |                            |
|--------------------------------------|----------------------------|
| Product Orientation                  | Vertical                   |
| Contact Features                     |                            |
| Contact Mating Area Plating Material | Tin (Sn)                   |
| Contact Base Material                | Brass                      |
| Contact Current Rating (Max)         | 17.5 A                     |
| Termination Features                 |                            |
| Termination Post & Tail Length       | 3.8 mm[.15 in]             |
| Termination Method to PCB            | Through Hole - Solder      |
| Mechanical Attachment                |                            |
| Screw Plating Material               | Nickel                     |
| Screw Material                       | Brass                      |
| Thread Size                          | M3                         |
| Connector Mounting Type              | Board Mount                |
| Housing Features                     |                            |
| Housing Material                     | PA 66                      |
| Centerline (Pitch)                   | 5.08 mm[.2 in]             |
| Dimensions                           |                            |
| Wire Size                            | 30 – 12 AWG                |
| Usage Conditions                     |                            |
| Operating Temperature Range          | -40 – 110 °C[-40 – 230 °F] |
| Operation/Application                |                            |
| Circuit Application                  | Power & Signal             |

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

|                                               |                                                                                                                     |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions                                                                                           |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions                                                                                           |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold                                                                                |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2025 (247)<br>Candidate List Declared Against: JAN 2025 (247)<br>SVHC > Threshold: |



Pb (2% in 4960776)

**Article Safe Usage Statements:**  
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

|                           |                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------|
| Halogen Content           | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Wave solder capable to 265°C                                                        |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-796949-9  
19POS TERMI-BLOK PCB MOUNT



TE Part # 282847-9  
TERMI-BLOK PCB MOUNT 35 9P.5

Customers Also Bought



TE Part #3-2134249-3  
D3900S 7.5MM PITCH REC ASSY 3P BLACK Z



TE Part #CAT-D9934-A75H  
DYNAMIC 3400F HDR ASSY



TE Part #2837892-2  
OCEAN-2.0-APPLICATOR-S-046F053F-SSA




TE Part #3-5175475-5  
CHAMP 050 B/B REC V W/LEG 40P





TE Part #3-5175475-7

[CHAMP 050 B/B REC V W/LEG 60P](#)



TE Part #2-2013519-0

[DYNAMIC D3900 H-HDR ASSY 10P Y TYPE-A](#)




TE Part #1-2229803-2

[D3950 HDR 7/11POS 1ROW Y KEY](#)



TE Part #5917629-5

[AMP FH REC V 120P H-9 SIF](#)



TE Part #3-5179275-8

[CHAMP 050-I PLUG H ASSY 68P](#)

Documents

Product Drawings

[19POS 5.08MM TERMI-BLOK TOP WI](#)

English

CAD Files

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1546074-9\\_O.2d\\_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1546074-9\\_O.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-1546074-9\\_O.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1-1773458-1\\_EURO\\_STYLE\\_TERMINAL\\_BLOCKS\\_QRG](#)

English

Product Specifications

[Application Specification](#)

English