

ATV600 Control Unit, modular drive, 380...480V, for liquid cooled

APM6L0CTLN4

EAN Code: 3606481012760

Main

Range of product	Altivar Process Modular	
Product or component type	Control module	
IP degree of protection	IP00 conforming to IEC 61800-5-1	

Complementary

[Us] rated supply voltage	380480 V 24 V
Width	230 mm
Height	510 mm
Depth	131 mm
Net weight	6.5 kg

Environment

Insulation resistance	> 1 MOhm 500 V DC for 1 minute to earth	
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6	
Pollution degree	2 conforming to IEC 61800-5-1	
Vibration resistance	1.5 mm peak to peak (f= 213 Hz) conforming to IEC 60068-2-6 0.5 gn (f= 13200 Hz) conforming to IEC 60068-2-6	
Shock resistance	4 gn for 11 ms conforming to IEC 60068-2-27	
Relative humidity	595 % without condensation conforming to IEC 60068-2-3	
Ambient air temperature for operation	-1050 °C	
Ambient air temperature for storage	-4070 °C	
Operating altitude	<= 4800 m with current derating above 1000m	
Environmental characteristic	Chemical pollution resistance class 3C3 conforming to IEC 60721-3-3 Dust pollution resistance class 3S3 conforming to IEC 60721-3-3	
Standards	IEC 61800-3 IEC 61800-5-1 IEC 61000-3-12 IEC 60721-3 IEC 61508 IEC 13849-1 UL 618000-5-1	
Product certifications	TÜV cULus	

Rates duty January 2016

Marking CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.0 cm
Package 1 Width	34.0 cm
Package 1 Length	65.0 cm
Package 1 Weight	9.776 kg
Unit Type of Package 2	P06
Number of Units in Package 2	3
Package 2 Height	75.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	37.5 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2439
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5b418692-6578-4a36-aac4-0bf9526de237
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins