



LEAK DETECTOR

Rapid detection of gas leaks

KEY FEATURES

- Immediately visible leakage detection
- Foaming or blistering on gas leakage
- Material-neutral
- Non-flammable
- Over 99% biodegradable
- Leaves no residue
- Contains corrosion inhibitors
- Formulated with antifreeze down to -20 °C
- Do not use under pressurized oxygen
- Aerosol can be used in all positions

AREAS OF APPLICATION

- Suitable for leaks of :
Compressed air, CO₂, nitrogen, butane, propane, gas cylinders, air conditioning and refrigerant gases
- Leak detection on : pipelines, fittings, connections, valves, safety valves

HOW TO USE

- Do not use in case of leaks with pressurized oxygen
- Shake aerosol well
- Spray on the pipes to be checked to make possible leaks visible
- A thin layer is enough
- Depending on the size of the gas leak, smaller or larger bubbles form immediately



PHYSICOCHEMICAL PROPERTIES

- | | |
|-------------------|-------------------------|
| • Physical state: | Liquid |
| • Color: | White |
| • Boiling point: | > 100 °C |
| • Smell: | Barely noticeable |
| • Solubility: | Very soluble in water |
| • Density: | 1.024 g/cm ³ |

PACK SIZE

Aerosol 650/400 ml x 12

Part number: **805501**

EAN-Code 13: 3429978055015

STORAGE

Container is pressurized: Can explode if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not puncture or burn – even after use. Protect from sunlight. Do not expose to temperature above 50°C / 122°F.