


**FAG****32310-B**

Tapered roller bearing

Tapered roller bearings 323, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

Technical information



Your current product variant

Tolerance class	PN	Normal (ISO 492:2014)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	B	Increased contact angle
Quality level	Standard	
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	110 mm	Outside diameter
B	40 mm	Width, inner ring
C	33 mm	Width, outer ring
T	42.25 mm	Width, total
C _r	165,000 N	Basic dynamic load rating, radial
C _{0r}	223,000 N	Basic static load rating, radial
C _{ur}	28,000 N	Fatigue load limit, radial
n _G	6,500 1/min	Limiting speed
n _{gr}	4,800 1/min	Thermal speed rating
m	1.95 kg	Weight



Mounting dimensions

d _a max	60 mm	Maximum diameter of shaft shoulder
d _b min	60 mm	Minimum diameter of shaft shoulder
D _a min	83 mm	Minimum diameter of housing shoulder
D _a max	100 mm	Maximum diameter of housing shoulder
D _b min	103 mm	Minimum diameter of housing shoulder
C _a min	5 mm	Minimum axial space
C _b min	9 mm	Minimum axial space
r _a max	2.5 mm	Maximum fillet radius of shaft
r _b max	2 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	2.5 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	2 mm	Minimum chamfer dimension of outer ring back face
a	33 mm	Distance between the apexes of the pressure cones
d ₁	82.3 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors





e	0.55	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1.1	Dynamic axial load factor
Y ₀	0.6	Static axial load factor

Additional information

T5FD050	Comparative designation to ISO 10317 and ISO 355
---------	--



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed