



 PRODUCT-DETAILS

OT2000E03W4

OT2000E03W4 SWITCH-DISCONNECTOR



General Information

| | |
|-----------------------|---|
| Extended Product Type | OT2000E03W4 |
| Product ID | 1SCA105517R1001 |
| EAN | 6417019395050 |
| Catalog Description | OT2000E03W4 SWITCH-DISCONNECTOR |
| Long Description | 3-pole, front operated, base mounted switch-diconductor, handle and shaft are not included, wide phase distance, terminal bolt kit included |

ABB EcoSolutions

| | |
|---|-----------------|
| End Of Life Disassembling Instructions | 1SCC301121M0201 |
| Environmental Information | 1SCC301268D0201 |
| Environmental Product Declaration - EPD | 1SCC301304D0201 |

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| RoHS Declaration | 1SCC011020D0201 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 1SCC011025D0201 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals | 1SCC301078M0205 |
| Mechanical Drawings | OT2500E03W4.igs |
| Environmental Product Declaration - EPD | 1SCC301304D0201 |

Environmental

| | |
|---------------------------|-----------------|
| Degree of Protection | Front IP00 |
| Environmental Information | 1SCC301268D0201 |
| Pollution Degree | 3 |

Ordering

| | |
|--------------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |
| Country or Territory of Origin | Finland |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 500.5 mm |
| Product Net Height | 376.5 mm |
| Product Net Depth / Length | 145.5 mm |
| Product Net Weight | 25.5 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 407 mm |
| Package Level 1 Depth / Length | 619 mm |
| Package Level 1 Height | 190 mm |
| Package Level 1 Gross Weight | 27.4 kg |
| Package Level 1 EAN | 6417019395050 |

Technical

| | |
|---|--|
| Conventional Free-air Thermal Current (I_{th}) | $\Theta = 40\text{ }^{\circ}\text{C}$ 2000 A |
| Degree of Protection | Front IP00 |
| Distance Between Phases | Phase distance 140 mm |
| Handle Type | Handle and shaft not included |
| Mechanical Durability | 6000 |
| Mounting Type | Base mounting |
| Number of Poles | 3P |
| Operating Mode | Front |
| Pollution Degree | 3 |
| Position of Line Terminals | Top In - Bottom Out Bottom In - Top Out |
| Power Loss | at Rated Operating Conditions per Pole 55 W |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 1000 V |
| Rated Operational Current AC-21B (I_e) | (380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A |
| Rated Operational Current AC-22B (I_e) | (380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A |
| Rated Operational Voltage | Main Circuit 1000 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V) 176 kA |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 55 kA |
| Special Functions | Wide phase distance 140 |
| Standards | IEC 60947-3 |
| Switches Operating Mechanism | Mechanism at the End of the Switch 03 (Left Side) |
| Terminal Type | Lug terminals |
| Tightening Torque | acc. IEC 60947-1 50 ... 75 N·m |

Technical UL/CSA

| | |
|-------------------|--------------------------------|
| Tightening Torque | acc. IEC 60947-1 50 ... 75 N·m |
|-------------------|--------------------------------|

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| A2L Certificate – IEC | 1SCC301338D0201 |
| Declaration of Conformity - CE | 1SCC301176D2702 |
| DNV GL Certificate | 1SCC301184D0203 |

External Classifications and Standards

| | |
|----------------------------|---|
| Object Classification Code | Q |
|----------------------------|---|

| | |
|---------------|---|
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| ETIM 10 | EC000216 - Switch disconnecter (AC) |
| eClass | V11.1 : 27371403 |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

