

## Winpak Lane Inc. 998 S SIERRA WAY

Standard T&B Catalog Number:

TY242M

**UPC Number:** 78621083071

**Status:** Active

**Description:** 

Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 208mm (8.19 Inches), Width of 3.6mm (0.142 Inches), Thickness of 1.04mm (0.041 Inches), Tensile Strength Rating of 180 Newtons (40 Pounds), Bulk Pack

Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.  Because there are no notches, Ty-Rap ties provide an infinite number of locking positions while fastening the tie at the precise bundle diameter needed.  The No-Slip Tail provides easy grip during tensioning. Ty-Rap ties feature a unique friction surface designed to reduce slippage during installation.  Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.  General  Material Nylon 6.6  Color Natural  Dimension Information  Nominal Length (inches) 8  Length (inches) 8.19  Width (inches) .140  Max. Wire Bundle Diameter (inches) 2  Specifications  Temperature Rating -40°F to 185°F  Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000  Package in Units 10000	Features	,
an infinite number of locking positions while fastening the tie at the precise bundle diameter needed.  The No-Slip Tail provides easy grip during tensioning. Ty-Rap ties feature a unique friction surface designed to reduce slippage during installation.  Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.  General  Material  Nylon 6.6  Color  Natural  Dimension Information  Nominal Length (inches)  8  Length (inches)  8.19  Wicth (inches)  1.40  Max. Wire Bundle Diameter (inches)  2  Specifications  Temperature Rating  -40°F to 185°F  Flammability Rating  UL 94 V-2  Tooling  Application Tools  ERG50, WT1-TB  Packaging  T&B Order Multiple  1000  T&B Inner Pack  1000		uneven surfaces and easier to pull through bulk- heads. Non-magnetic stainless steel locking device insures both maximum strength and the right tight-
ing. Ty-Rap ties feature a unique friction surface designed to reduce slippage during installation.  Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.  General  Material Nylon 6.6  Color Natural  Dimension Information  Nominal Length (inches) 8 Length (inches) 8.19  Width (inches) .140  Max. Wire Bundle Diameter (inches) 2  Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000		an infinite number of locking positions while fasten-
tion points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.  General  Material Nylon 6.6 Color Natural  Dimension Information  Nominal Length (inches) 8 Length (inches) 8.19 Width (inches) 1.140 Max. Wire Bundle Diameter (inches) 2 Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000		ing. Ty-Rap ties feature a unique friction surface de-
Material Nylon 6.6  Color Natural  Dimension Information  Nominal Length (inches) 8 Length (inches) 8.19 Width (inches) .140 Max. Wire Bundle Diameter (inches) 2 Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000		tion points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, pre-
Color Natural  Dimension Information  Nominal Length (inches) 8 Length (inches) 8.19 Width (inches) .140 Max. Wire Bundle Diameter (inches) 2 Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000 T&B Inner Pack 1000	General	
Nominal Length (inches) 8 Length (inches) 8.19 Width (inches) .140 Max. Wire Bundle Diameter (inches) 2 Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000 T&B Inner Pack 1000		
Length (inches) 8.19 Width (inches) .140 Max. Wire Bundle Diameter (inches) 2 Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000 T&B Inner Pack 1000	Dimension Information	
Max. Wire Bundle Diameter (inches)  Specifications  Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000	Length (inches)	8.19
Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000		
Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2  Tooling  Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000		2
Application Tools ERG50, WT1-TB  Packaging  T&B Order Multiple 1000  T&B Inner Pack 1000	Temperature Rating	
Packaging           T&B Order Multiple         1000           T&B Inner Pack         1000	, ,	
T&B Order Multiple 1000 T&B Inner Pack 1000		ERG50, WT1-TB
T&B Inner Pack 1000	rackaying	
	T&B Order Multiple	1000
Package in Units 10000	T&B Inner Pack	1000
	Package in Units	10000



Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	1.88 lbs. per 1000
Application Support	
Material Selection Guide	Available on Website
Available Colors	Available on Website
Certifications	
RoHS Compliance	Yes
Certifications	



File Nbr: E49405

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com