

Solo Smoke Detector Tester

SAFETY DATA SHEET

SDS0066UK

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 453/2010

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	
Product Name	Solo Smoke Detector Tester.
Trade Name	Solo A3 –XXX (XXX denotes customer variant).
CAS No.	Mixture.
EINECS No.	Mixture.
REACH Registration No.	None assigned.
1.2 Relevant identified uses of the substance or mixture and uses advised against	
Identified use(s)	Smoke simulation.
Uses advised against	None known.
1.3 Details of the supplier of the Safety Data Sheet	
Company Identification	Detectortesters (No Climb Products Ltd) Edison House 163 Dixons Hill Road Welham Green Hertfordshire. AL9 7JE. United Kingdom
Telephone	+44 (0) 1707 282760
Fax	+44 (0) 1707 282777
E-mail	SDS@detectortesters.com
1.4 Emergency telephone number	
Emergency Phone No.	+44 (0) 1707 282760

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
Directive 67/548/EEC & Directive 1999/45/EC	Not classified as dangerous for supply/use.
2.2 Label elements	
Hazard Symbol	According to Directive 67/548/EEC & Directive 1999/45/EC None.
Risk Phrases	None.
Safety Phrases	S2: Keep out of the reach of children. S17: Keep away from combustible material. S16: Keep away from sources of ignition - No smoking.
Additional Information	14.5 % by mass of the contents are flammable. Do not spray on a naked flame or any incandescent material. Do not pierce or burn, even after use. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C.
2.3 Other hazards	High concentrations: May cause drowsiness and dizziness.
2.4 Additional Information	None.

Solo Smoke Detector Tester

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.1 Mixtures

EC Classification No. 67/548/EEC

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
1,1,1,2-tetrafluoroethane	50 - 100	811-97-2	212-377-0	None assigned	None
Propan-2-ol	10 - 25	67-63-0	200-661-7	01-2119457558-25	F; R11, Xi; R36, R67

3.2 Additional Information

For full text of R/S phrases see section 16.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.

Skin Contact

Wash with plenty of soap and water.

Eye Contact

Flush eyes with water for at least 15 minutes while holding eyelids open. If eye irritation persists: Get medical advice/attention.

Ingestion

Unlikely route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

None anticipated.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

5. SECTION 5: FIRE-FIGHTING MEASURES

Pressurised container: May burst if heated.

5.1 Extinguishing Media

Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Unsuitable Extinguishing Media

None known.

5.2 Special hazards arising from the substance or mixture

Heating may cause pressure rise with risk of bursting.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

Solo Smoke Detector Tester

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

- | | |
|--|--|
| 6.1 Personal precautions, protective equipment and emergency procedures | Ensure adequate ventilation. Avoid inhalation of high concentrations of vapours. Wear suitable gloves and eye/face protection. |
| 6.2 Environmental precautions | Do not release large quantities into the surface water or into drains. |
| 6.3 Methods and material for containment and cleaning up | Collect mechanically and dispose of according to Section 13. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty. |
| 6.4 Reference to other sections | See Also Section: 8, 13. |

7. SECTION 7: HANDLING AND STORAGE

- | | |
|---|---|
| 7.1 Precautions for safe handling | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Provide adequate ventilation. Avoid inhalation of high concentrations of vapours. Avoid prolonged skin contact. Wear suitable gloves if prolonged skin contact is likely. See Section: 8. Do not eat, drink or smoke during work. Wash hands thoroughly after handling. |
| 7.2 Conditions for safe storage, including any incompatibilities | |
| Storage Temperature | Ambient. |
| Storage Life | Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. |
| Incompatible materials | Stable under normal conditions. |
| 7.3 Specific end use(s) | None anticipated.
Smoke simulation. |

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
1,1,1,2-tetrafluoroethane	811-97-2	1000	4240	-	-	WEL
Propan-2-ol	67-63-0	400	999	500	1250	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

- | | |
|-------------------------------------|------------------|
| 8.1.2 Biological limit value | Not established. |
|-------------------------------------|------------------|

Solo Smoke Detector Tester

8.1.3 PNECs and DNELs

Propan-2-ol

DNEL	Oral	Inhalation	Dermal
Industry - Long Term – Local effects	-	-	-
Industry - Long Term - Systemic effects	-	500 mg/m ³	888 mg/kg bw/day
Consumer - Long Term - Local effects	-	-	-
Consumer - Long Term - Systemic effects	26 mg/kg bw/day	89 mg/m ³	319 mg/kg bw/day

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation.

8.2.2 Personal protection equipment

Eye/face protection

Not normally required.



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely.
Gloves: Nitrile rubber, NBR.



Respiratory protection

No personal respiratory protective equipment normally required. Handling of larger amounts: In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type A (EN14387 or EN405) may be appropriate.
Not applicable.



Thermal hazards

8.2.3 Environmental Exposure Controls

Do not release large quantities into the surface water or into drains.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Characteristic.
Odour Threshold	Not determined.
pH	Not determined.
Melting Point/Freezing Point	Not determined.
Initial boiling point and boiling range	-26 °C
Flash Point	13 °C
Evaporation rate	Not applicable.
Flammability (solid, gas)	Non-flammable; tested to 2008/47/EC Annex 1.9.1(iii).
Upper/lower flammability or explosive limits	Explosive Limit Ranges: 2.0 – 12.0 Vol-%
Vapour pressure	5.2 bar @ 20 °C
Density	1.132 g/cm ³ @ 20 °C
Vapour density	Not determined.
Relative density	Not determined.
Solubility(ies)	Immiscible with water.
Partition coefficient: n-octanol/water	Not determined.
Ignition temperature	425 °C
Auto-ignition temperature	Product is not selfigniting.
Decomposition Temperature	Not determined.
Kinematic Viscosity	Not determined.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

Solo Smoke Detector Tester

9.2 Other information

Organic solvents - Content 14.8%

10. SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	Stable under normal conditions.
10.4	Conditions to avoid	Heat and direct sunlight.
10.5	Incompatible materials	None anticipated.
10.6	Hazardous Decomposition Product(s)	None known.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.1 Mixtures

Acute toxicity	Low acute toxicity.
Irritation	Not classified.
Corrosivity	Not classified.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	None anticipated.
Carcinogenicity	No evidence of carcinogenicity.
Mutagenicity	There is no evidence of mutagenic potential.
Toxicity for reproduction	None anticipated.
Aspiration hazard	None anticipated.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION



12.1	Toxicity	Low toxicity to aquatic organisms.
12.2	Persistence and degradability	The product is readily biodegradable. Unlikely to persist.
12.3	Bioaccumulative potential	The product has no potential for bioaccumulation.
12.4	Mobility in soil	Immiscible with water. The product is predicted to have low mobility in soil.
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility. Do NOT landfill.
13.2	Additional Information	Disposal should be in accordance with local, state or national legislation.

Solo Smoke Detector Tester

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number		
ADR, IMDG, IATA	UN 1950	
14.2 UN Proper Shipping Name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, Non-flammable	
14.3 Transport hazard class(es)		
ADR		
Class / Classification	2 5A Gases	
Label	2.2	
IMDG, IATA		
Class / Division	2.2	
Label	2.2	
14.4 Packing Group		
ADR, IMDG, IATA	None.	
14.5 Environmental hazards		
Marine Pollutant	No.	
14.6 Special precautions for user	Warning: Gases.	
Kemler Code	-	
IMDG EMS	F-D, S-U	
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.	
14.8 Additional Information		
ADR		
Limited Quantity (LQ)	1 L	
ADR Transport Category	3	
Tunnel Restriction Code	Not applicable in Limited Quantities.	
IMDG		
Limited Quantity (LQ)	1L	
IATA		
Limited Quantity (LQ)	1L	 
UN Model Regulation	UN 1950, AEROSOLS, 2.2	

Solo Smoke Detector Tester

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the substance or mixture

15.1.1 EU regulations

Authorisations and/or restrictions on use

Candidate List of Substances of Very High Concern for Authorisation All chemicals are not listed.

REACH: ANNEX XVII Restrictions on the manufacture, placing on the market and use of All chemicals are not listed.

certain dangerous substances, mixtures and articles

REACH: ANNEX XIV List of substances subject to authorisation All chemicals are not listed.

Community Rolling Action Plan (CoRAP); Draft 29/02/2012 All chemicals are not listed.

15.1.2 National regulations

None known.

Wassergefährdungsklasse (Germany)

1,1,1,2-tetrafluoroethane

WGK class 1

Propan-2-ol

WGK class 1

Technical Instructions (air)

Class	Share in %
NK	10 - <25

VOC-CH

14.48%

VOC-EU

167.3g/l

Danish MAL Code

2-1

15.2 Chemical Safety Assessment

Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
WGK	Wassergefährdungsklasse (Germany)
VOC	Volatile Organic Compounds
MAL Code	Måleteknisk Arbejdshygienisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	International Maritime Code for Dangerous Goods
IATA	International Air Transport Association
F	Highly flammable
Xi	Irritant

Risk Phrases

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

Solo Smoke Detector Tester

Disclaimers

The information is based on the best knowledge of No Climb Products Ltd. and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for purposes other than it is intended.

Annex to the extended Safety Data Sheet (eSDS)

No information available.