

PRODUCT-DETAILS

TY272MX

CBL TIE 120LB 9IN UV BLK NYLON

General Information	
Extended Product Type	TY272MX
Product ID	7TAG009330R0007
EAN	5414363063087
Catalog Description	CBL TIE 120LB 9IN UV BLK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 224mm (8.8 Inches), Width of 6.9mm (0.27 Inch), Thickness of 1.5mm (0.06 Inches), Tensile Strength Rating of 534 Newtons (120 Pounds), Bulk Pack

Ordering EAN UPC

541436306308	7
786210850726	5

υım	ensions	

Product Net Width	0.275 in
	6.99 mm
Product Net Depth /	8.75 in
Length	222.3 mm

Container Information

Package Level 1 Units	500 piece
Package Level 2 Units	5000 piece
Package Level 2 Width	13.6 in 345 mm
Package Level 2 Height	9.5 in 241 mm
Package Level 2 Depth / Length	21.4 in 544 mm

Technical UL/CSA

Flammability According	V-2
to UL94	

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.236 to 1.97 in 6 to 50 mm
Color	Black
Effective Date	19750325
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	120 lb 530 N
Thickness	0.07 in 1.78 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000487
Declaration of Conformity - CE	9AKK107492A9841
Instructions and Manuals	TY272MX
REACH Declaration	9AKK107992A3994
RoHS Information	9AKK107991A8361

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

TY272MX 3

_					
Ca	te	a	റ	m	es

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$