

PRODUCT-DETAILS

ZLS905E68-3LLALB

ZLS905E68-3LLALB Starter pack



General Information

Extended Product Type	ZLS905E68-3LLALB
Product ID	2CCA183210R0001
EAN	7612271417147
Catalog Description	ZLS905E68-3LLALB Starter pack
Long Description	Starter pack Touch proof with 68 Modules L1,L2,L3 LA,LB Pluggable socket system SMISSLINE TP is completely fingersafe (IP2XB) together with the socket end piece

Technical

Standards	IEC/EN 61439-6
Product Name	Starter pack
Rated Operational Voltage	690 V AC 1000 V DC
Rated Current (I _n)	125 A
Options Provided	3LLALB
Model Number	Flat

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	2CCY451206D0201

Dimensions

Product Net Width	111 mm
Product Net Height	1266 mm
Product Net Depth / Length	34 mm
Product Net Weight	2071 g

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	132 mm
Package Level 1 Height	67 mm
Package Level 1 Depth / Length	1269 mm
Package Level 1 Gross Weight	2392 g
Package Level 1 EAN	7612271417147

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389030
E-Number (Switzerland)	809994840
Country of Origin	Switzerland (CH)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107991A9646
Environmental Information	2CCY451206D0201
Instructions and Manuals	9AKK107680A2315
RoHS Information	9AKK107991A9646

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
Instructions and Manuals	9AKK107680A2315
Dimension Diagram	9AKK107492A6192

Classifications

ETIM 6	EC001522 - Busbar
ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar
EPLAN Catalog Tree	Electrical engineering / Protection devices / General
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389030
Object Classification Code	W

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A

