

Fuse holder terminal blocks for 5 x 20 mm and 5 x 25 mm fuses

Compression clamp

DIN 1 - DIN 3




End stop	th. 9,1 mm	BADL	V0	0199 408.02
End stop	th. 9,1 mm	BAM		0103 002.26
<i>Other end stops : See Accessories section</i>				
Rail	35 x 7,5 x 1	PR30	prepunched	0173 220.05
Rail	35 x 15 x 2,3	PR4		0168 500.12
Rail	35 x 15 x 1,5	PR5	prepunched	0101 598.26
Rail	32 x 15	PR1Z2		0163 050.04
<i>Other rails : See Accessories section</i>				

Notes

The use of some accessories may decrease the block's voltage rating. For more information, consult us.


Accessories



1 End section	black	FEM13U	V0	th. 1,5 mm	0199 635.24
2 Test plug		FC2		DIA. 2 mm	0007 865.26
3 Test socket		FC4		DIA. 4 mm	0167 860.01
4 Standard jumper bar		AL2		DIA. 2 mm	0163 043.21
5 Screw for BJ		AL3		DIA. 3 mm	0163 261.00
6 Washer for BJ		AL4		DIA. 4 mm	0163 262.01
7 Fuse 5 x 20	250 V	BJS131		10 poles	0175 991.11
		VJS11			0163 394.26
		RDJ11			0168 783.01
		FU520		0,5 A	0008 288.15
				1 A	0008 290.13
				2 A	0008 291.00
				3,15 A	0008 289.16
				5 A	0008 292.01
		FU525		1,6 A	0167 546.22
				2 A	0167 547.23
				2,5 A	0167 548.04
				4 A	0167 549.05
				6,3 A	0167 550.02
8 Blown fuse indicator		LEN	Neon	110 - 230 VAC	0167 075.25
			Neon	480 VAC	0103 909.00
				Leakage current with neon indicator	
				< 0,5 mA (110 & 480 VAC)	
				< 0,7 mA (230 VAC)	
9 Comb-type jumper bar	70 A	PC 13		10 poles	0173 510.20
R See section on markers marking method					

MU 10/13.SF1


Spacing 13 mm (.512")



13 mm block for blown fuse indicator (to be ordered separately).

MU 10/14,5.SF1

Spacing 14,5 mm (.571")



14,5 mm block for blown fuse indicator (to be ordered separately).

Color	Type	Part numbers	Color	Type	Part numbers
Black V0	MU 10/13.SF1	0199 012.17	Black V0	MU 10/14,5.SF1	0199 011.16

Characteristics

Wire size	Wire size		
	NFC DIN	UL	CSA
Compression Solid wire	0,5-16 mm ²	22-10 AWG	6 AWG max.
clamp Stranded wire	0,5-10 mm ²	22-10 AWG	6 AWG max.

Voltage			
Rated	750 V Gr.C (1)	600 V (1)	600 V (1)
Pulse			
Pollution degree			
Current			
Rated	16 A	16 A	16 A

Wire size			
Rated / Gauge	10 mm ²	10 AWG	6 AWG
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
12 mm	5,5 mm	1,2-1,4 Nm	IP 20
.47"	.22"	10.6-12.3 lb.in	NEMA 1

Characteristics

Wire size	Wire size		
	NFC DIN	UL	CSA
Compression Solid wire	0,5-16 mm ²	22-10 AWG	6 AWG max.
clamp Stranded wire	0,5-10 mm ²	22-10 AWG	6 AWG max.

Voltage			
Rated	750 V Gr.C (1)	600 V (1)	600 V (1)
Pulse			
Pollution degree			
Current			
Rated	16 A	16 A	16 A

Wire size			
Rated / Gauge	10 mm ²	10 AWG	6 AWG
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
12 mm	5,5 mm	1,2-1,4 Nm	IP 20
.47"	.22"	10.6-12.3 lb.in	NEMA 1

Type	Part numbers	Type	Part numbers
FC2	DIA. 2 mm	FC2	closed block delivered with plate
FC4	DIA. 4 mm	FC4	DIA. 2 mm
AL2	DIA. 2 mm	AL2	DIA. 4 mm
AL3	DIA. 3 mm	AL3	DIA. 2 mm
AL4	DIA. 4 mm	AL3	DIA. 3 mm
AL4	DIA. 4 mm	AL4	DIA. 4 mm
FU520	0,5 A	FU520	0,5 A
	1 A		1 A
	2 A		2 A
	3,15 A		3,15 A
	5 A		5 A
FU525	1,6 A	FU525	1,6 A
	2 A		2 A
	2,5 A		2,5 A
	4 A		4 A
	6,3 A		6,3 A
LEN	Neon 110 - 230 VAC	LEN	Neon 110 - 230 VAC
	Neon 480 VAC		Neon 480 VAC
	Leakage current with neon indicator		Leakage current with neon indicator
	< 0,5 mA (110 & 480 VAC)		< 0,5 mA (110 & 480 VAC)
	< 0,7 mA (230 VAC)		< 0,7 mA (230 VAC)
PC 13	10 poles	PC 13	10 poles

Note : (1) Insulation voltage of terminal block - operating voltage : In accordance with fuse rating.