### AMP | SMA

TE Internal #: 1052508-1

TE Internal Description: 2052 1131 00

View on TE.com >



#### Connectors > RF Connectors > Coax Connectors



RF Interface: SMA

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 8.99 mm [ .354 in ]

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Threaded

## **Features**

## **Product Type Features**

Connector Product Type	Connector Assembly
RF Interface	SMA
RF Connector Style	Jack
Connector & Contact Terminates To	Printed Circuit Board, Wire & Cable

## **Configuration Features**

PCB Mount Orientation	Edge
Number of Positions	1
Number of Coaxial Contacts	1

#### **Electrical Characteristics**

Impedance	50 Ω	

## **Body Features**

Body Material	Stainless Steel
Body Material Finish	Plated
Body Plating Material	Gold

#### **Contact Features**

RF Connector Contact Configuration	Captivated Contacts
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper

#### **Termination Features**



Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Panel Mount Feature Type	Flange
Panel Attachment Style	Front Mount
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Ероху
Dimensions	
Product Length	9.53 mm[.375 in]
RF Connector Mated Outer Diameter (Approximate)	8.99 mm[.354 in]
Operation/Application	
Operating Frequency	18 GHz
Packaging Features	
Packaging Method	Carton
Other	
Number of Panel Mounting Holes	4
Dielectric Material	PTFE

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (.6% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Pin-in-Paste capable to 260°C



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Also in the Series | SMA



Battery Holders(1)




Connector Adapters & Connector Savers(8)



Connector Caps & Covers(3)



Connector Strain Relief(1)



# Customers Also Bought















## Documents

Product Drawings 2052 1131 00

English