Product data sheet Characteristics

LX9FF200

TeSys F - specific contactor coil - TeSys F - 208 V 40...400 Hz low consumption

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 71.00 USD



Range of product	TeSys F	
Range	TeSys	
Product or component type	Specific contactor coil	— eds
Device short name	LX9FF	
Range compatibility	TeSys F LC1F contactor	—orodu
Product compatibility	LC1F115 LC1F150	of these
Control circuit type	AC 40400 Hz low consumption	Pility —
[Uc] control circuit voltage	208 V AC 40400 Hz	— e
Average resistance	45 Ohm inrush at 68 °F (20 °C) 1788 Ohm holding at 68 °F (20 °C)	
Inductance of closed circuit	5.95 H	— in sni
Operating time	130 ms opening 35 ms closing	eterminin
Mechanical durability	10 Mcycles	for d
Operating rate	<= 2400 cyc/h at <= 55 °C	— pesn
		— a

Complementary

Complementary		
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.350.55 Uc at 131 °F (55 °C) drop-out 0.851.1 Uc at 131 °F (55 °C) operational	
Inrush power in VA	690855 VA at 68 °F (20 °C) 40400 Hz	
Hold-in power consumption in VA	6.68.1 VA at 68 °F (20 °C) 40400 Hz	7
Heat dissipation	5.97.2 W	-

Environment

Ambient air temperature for operation	> 23131 °F (> -555 °C)
Product weight	0.95 lb(US) (0.43 kg)

Ordering and shipping details

22341 - CONTACTOR,D,K,&F ACCESS
l12
1
1.080000000000001
N
CZ

Contractual warranty

Warranty period	18 months
-----------------	-----------