Product data sheet Characteristics

XVC1M5K

Complete pre wired monolithic tower light, Harmony XVC, plastic, red orange green blue clear, 100mm, base mounting, steady or flashing, 100...240V AC

N	12	٩I	r

Range of product	Harmony XVC1
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	5 illuminated units
Sound signalling	Without
Mounting diameter	100 mm
Component name	XVC
Light source	LED steady or flashing red LED steady or flashing orange LED steady or flashing green LED steady or flashing blue LED steady or flashing clear
[Us] rated supply voltage	100240 V
Supply circuit type	AC

Complementary

Material	Polycarbonate: illuminated unit	
	ABS (acrylonitrile butadiene-styrene): base unit	
	PBT + ABS (UL94-V0): top cover	
Product mounting	On base	
Cable cross section	0.33 Mm²	
	0.83 mm ²	
AWG gauge	AWG 18	
	AWG 22	
Cable length	500 mm	
Marking	CE	
[Uimp] rated impulse withstand voltage	4 kV	
Current consumption	270 mA	
Flashing frequency	0.73 Hz	
Net weight	1.8 kg	
Height	528 mm	

Environment

Standards	IEC 60947-1 IEC 60947-5-1	
Product certifications	UL	
Protective treatment	TC	
Ambient air temperature for storage	-3570 °C	
Ambient air temperature for operation	-3050 °C	
Electrical shock protection class	Class I conforming to IEC 61140	
IP degree of protection	IP54 conforming to IEC 60529	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins