

KX Tower Pincers

- | Extremely slim shape and outwardly positioned cutting edges for binding deep mounted steel rods and for problem areas
- | KX Solinger tower pincers
- | Suitable for work in places which are difficult to reach
- | Fast, reliable and cost-effective drilling and cutting of the wire in a single operation
- | For fixing reinforcement steel with binding wire from a roll
- | Cutting edges inductively hardened
- | Power transmission with optimum leverage for easy and effortless work
- | Tremendous cutting performance, up to 45 % power saving compared with conventional nippers
- | Elliptical formed joint to guarantee optimum handling
- | Handles coated with plastic
- | Made of tool steel, forged, oil-hardened

SKU: 115-12-300-KX4-SB

Safety Notes



Use tools for indicated purposes only.
Before using the cutting tools please wear body protection such as safety mask, safety glasses and hand protection.
Beware of wire ends flying off!

General Information

Tower Pincers


As well as the standard steel fixer's pincers which stand out as a result of their hardened and tempered construction, we also have the exclusive KX model. This in-house development enables extremely high forces to be applied and, as a result of its design, is also for work in confined spaces.



Low-effort construction work

It takes many hours of hard manual work to erect the steel framework for a building. Tools that are both tough and strain-reducing are an essential feature of construction work. Bolt-cutters, steel fixer's pincers and end cutting nippers made by NWS provide easy handling and save tremendously on the effort required when cutting through reinforcing matting or twisting reinforcing wire. This makes work easier and quicker – which benefits construction progress at the same time.

Downloads

	115-12-260-KX3.jpg		detail_115-12-260-KX3_1804061537.jpg		detail_115-11-230-KX2_0603011519.jpg
	detail_115-11-230-KX2_0603011522.jpg		detail_115-11-230-KX2_0603011520.jpg		VP-1435.jpg

Technical Data

115-12-300-KX4-SB		
	Length - mm	300
	Length - in	11 3/4
	Cutting edge shape	
	Soft wire (220 N/mm ²) copper, aluminium, plastic - cutting capacity - Ø mm	4,5
	Medium hard wire (750 N / mm ²) nail, wire nail - cutting capacity - Ø mm	4
	Hard wire (1800 N / mm ²) wire rope fiber, steel rope - cutting capacity - Ø mm	2,8
	Cutting edge hardness - HRC	57 - 59
	DIN standards - National, European and worldwide	DIN ISO 9242
	Weight - g	490
	Length including self-service packaging - mm	375
	Width including self-service packaging - mm	65
	Height including self-service packaging - mm	28
	Weight self-service packaging - g	505
	Packing unit	6
	Barcode	40 03758 61513 3