

Datasheet

200MHz/100MHz/70MHz

Digital Storage Oscilloscope

Stock No. : Model :

123-3553 **IDS-2204E**

123-3552 **IDS-2104E**

124-0233 **IDS-2074E**

124-1956 **IDS-2202E**

124-1955 **IDS-2102E**

123-3551 **IDS-2072E**



VPO
Visual Persistence Oscilloscope

FEATURES

- 200/100/70MHz Bandwidth
- Sample Rate : Max. 1GSa/s (4ch Model) Per Channel 1GSa/s (2ch Model)
- Standard 10M Maximum Memory Depth and VPO Waveform Display Technology
- Waveform Update Rate of 120,000 wfm/s
- 8 " 800 x 480 TFT LCD Display
- Max. 1M pts of FFT to Get Higher Resolution in Frequency Domain
- Digital Filter Function
- Segmented Memory and Waveform Search Functions
- I²C/SPI/UART/CAN/LIN Serial Bus Trigger and Decoding Function
- Datalog Function for Waveform Observation in Long Period of Time
- Network Storage Function

The IDS-2000E Series features bandwidth selections of 200MHz, 100MHz, and 70MHz. 4 channel models of the series provides 1GSa/s max. real-time sampling rate ; 2 channel models of the series provides 1GSa/s per channel real-time sampling rate .All series is equipped with waveform update rate of 120,000 wfm/s. The 8-inch 800 x 480 16 : 9 TFT LCD display and the minimum 1mV/div vertical range allow the IDS-2000E Series to clearly display complex and random waveforms.

With respect to the memory depth, the standard IDS-2000E Series digital oscilloscope provides 10M long memory for users to completely retrieve and analyze waveforms. Users, base upon the application requirements, can select 1K, 10K, 100K, 1M or 10M memory depth. Short memory depth allows users to observe fast-changing waveforms and, on the other hand, long memory depth aims for continuously changing waveforms. The IDS-2000E Series is equipped with waveform search and segmented memory functions to expand the flexible applications of 10M long memory. With the waveform search function, users can rapidly search waveforms according the required trigger conditions. The segmented memory can be divided the maximum into 29,000 sections for users to bypass any unimportant waveforms so as to swiftly search all required waveforms. Memory depth provides users with the optimized applications. The waveform update rate of 120,000 wfm/s, twice as fast as that of the same category oscilloscopes, allows users to easily observe random signals so as to completely measure and test signals.

With respect to test and measurement items, the IDS-2000E Series provides 36 items and the statistics function, which allows users to analyze the maximum, the minimum, mean value, and standard deviation of the test and measurement item. Users, via the data log function, can set time and interval for waveform observation to achieve the long record objective. The IDS-2000E Series also provides 1M max. FFT display. High resolution FFT display, high waveform update rate, Window Zoom and Peak Search allow users to obtain more accurate and efficient test and measurement results while conducting tests in the frequency domain.

In addition to waveform search and segmented memory functions, the IDS-2000E Series also provides bus decoding function and digital filter function. With bus decoding function, users can not only analyze I²C, SPI, and UART bus but also CAN, LIN bus, which are often used for automobile communications. Digital filter allows users to independently set high pass or low pass digital filter frequency for each channel. By so doing, the observation for the signals of the specific frequency bandwidth becomes easier, and magnetic noise can be filtered out from the magnetic component while conducting power supply test applications.

The IDS-2000E Series features automatic zero key for horizontal, vertical and trigger level. Users can rapidly zero all data by simply pressing the zero key. The communications interface provides USB Host port, Device port, Ethernet communications interface. Data storage and remote control requirements can be achieved by the communications interface.

APPLICATIONS

- **Educational Training and Laboratory**
- **QA Tests**
- **Serial Bus Design and Debugging**
- **Maintenance Services**

SPECIFICATIONS

		IDS-2072E	IDS-2074E	IDS-2102E	IDS-2104E	IDS-2202E	IDS-2204E
VERTICAL SENSITIVITY	Channels	2Ch+EXT	4Ch	2Ch+EXT	4Ch	2Ch+EXT	4Ch
	Bandwidth	DC~70MHz(-3dB)		DC~100MHz(-3dB)		DC~200MHz(-3dB)	
	Rise Time	5ns		3.5ns		1.75ns	
	Bandwidth Limit	20MHz		20MHz		20M/100MHz	
	Vertical Resolution Input Coupling Input Impedance DC Gain Accuracy Polarity Maximum Input Voltage Offset Position Range Waveform Signal Process	8 bits : 1mV ~ 10V/div AC, DC, GND 1MΩ // 16pF approx. ±(3% when 2mV/div or greater is selected ; ±(5%) when 1mV/div is selected Normal & Invert 300Vrms , CAT I (300Vrms CAT II with GTP-070A-4/150A-4/300A-4, 10 : 1 probe) 1mV/div ~ 20mV/div : ±0.5V ; 50mV/div ~ 200mV/div : ±5V ; 500mV/div ~ 2V/div : ±25V ; 5V/div~10V/div : ±250V + , - , × , ÷ , FFT , FFTrms , Uesr Defined Expression FFT : 1Mpts ; FFT : Spectral magnitude. Set FFT Vertical Scale to Linear RMS or dBV RMS ; FFT Window Displays : Rectangular, Hamming , Hanning, Blackman-Harris					
TRIGGER	Source Trigger Mode Trigger Type Trigger Holdoff Range Coupling Sensitivity	Ch1 ,CH2, CH3, CH4, Line, EXT* ; *dual channel models only. Auto (Supports Roll Mode for 100 ms/div and slower), Normal, Single Sequence Edge, Pulse Width(Glitch), Video, Pulse Runt, Rise & Fall(Slope), Alternate, Time out, Event-Delay(1~65,535 events), Time-Delay(Duration;4ns~10s), Bus 4ns ~ 10s AC, DC, LF rej. , Hf rej. , Noise rej. 1div					
EXT TRIGGER	Range Sensitivity Input Impedance	±15V DC ~ 100MHz Approx. 100mV 100MHz ~ 200MHz Approx. 150mV 1MΩ ±3%, ~16pF					
HORIZONTAL	Time Base Range Pre-trigger Post-trigger Time Base Accuracy Real Time Sample Rate Record Length Acquisition Mode Peak Detection Average	1ns/div ~ 100s/div (1-2-5 increments); ROLL : 100ms/div ~ 100s/div 10 div maximum 2,000,000 div maximum ±50 ppm over any≥ 1 ms time interval Max. : 1GSa/s (4ch model); Per channel 1GSa/s (2ch model) Max. : 10Mpts Normal, Average, Peak Detect, Single 2ns (typical) Selectable from 2 to 256					
X-Y MODE	X-Axis Input Y-Axis Input Phase Shift	Channel 1 ; Channel 3* (* : four channel models only) Channel 2 ; Channel 4* (* : four channel models only) ±3° at 100kHz					
CURSORS AND MEASUREMENT	Cursors Automatic Measurement Control Panel Function Auto Counter Autoset Save Setup Save Waveform	Amplitude, Time, Gating Available; Unit : Seconds(S), Hz(1/S), Phase (Degrees), Ratio(%) 36 sets: Pk-Pk, Max, Min, Amplitude, High, Low, Mean, Cycle Mean, RMS, Cycle RMS, Area, Cycle Area, ROVShoot, FOVShoot, RPRESshoot, FPRESshoot, Frequency, Period, RiseTime, FallTime, +Width, -Width, Duty Cycle, +Pulses, -Pulses, +Edges, -Edges, FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF, Phase Cursors measurement 6 digits, range from 2Hz minimum to the rated bandwidth Single-button, automatic setup of all channels for vertical, horizontal and trigger systems, with undo Autoset 20set 24set					
DISPLAY SYSTEM	TFT LCD Type Display Resolution Interpolation Waveform Display Waveform Update Rate Display mode Display Graticule	8" TFT LCD WVGA color display 800 horizontal x 480 vertical pixels (WVGA) Sin(x)/x Dots, Vectors, Variable persistence(16ms~10s), Infinite persistence 120,000 waveforms per second, maximum YT ; XY 8 x 10 divisions					
INTERFACE	USB Port Ethernet Port (LAN) Go/NoGo BNC Kensington Style Lock	USB 2.0 Full-speed host port x 1, USB High-speed 2.0 device port x 1 RJ-45 connector, 10/100Mbps with HP Auto-MDIX 5V Max/10mA TTL open collector output Rear-panel security slot connects to standard Kensington-style lock					
POWER SOURCE MISCELLANEOUS	Line Voltage Range Multi-Language Menu On-Line Help Time clock Operation Environment	AC 100V ~ 240V, 48Hz ~ 63Hz, auto selection Available Available Time and date, provide the date/time for saved data Temperature: 0°C to 50°C. Relative Humidity: ≤80%, 40°C or below; ≤45%, 41°C ~ 50°C					
DIMENSIONS & WEIGHT	384(W) X 208(H) X 127.3(D)mm, Approx. 2.8 kg						

Note : Three-year warranty, excluding probes & LCD display panel.

Specifications subject to change without notice.

ORDERING INFORMATION

IDS-2204E	200MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2202E	200MHz, 2-Channel, Digital Storage Oscilloscope
IDS-2104E	100MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2102E	100MHz, 2-Channel, Digital Storage Oscilloscope
IDS-2074E	70MHz, 4-Channel, Digital Storage Oscilloscope
IDS-2072E	70MHz, 2-Channel, Digital Storage Oscilloscope

ACCESSORIES

Quick start guide, Power cord x 1
GTP-070B-4 : 70MHz(10:1/1:1) Switchable passive probe for IDS-2072E/2074E(one per channel)
GTP-150B-4 : 150MHz(10:1/1:1) Switchable passive probe for IDS-2102E/2104E(one per channel)
GTP-300B-4 : 300MHz(10:1/1:1) Switchable passive probe for IDS-2202E/2204E(one per channel)

OPTIONAL ACCESSORIES

CDB-03	Oscilloscope Education & Training Kit	GCP-020	Current Probe, DC ~ 100kHz, 10A, Current Probe
GCP-005	Current Probe, 40Hz ~ 1kHz, 5A, Current Probe	GCP-100	Current Probe, 40Hz ~ 10kHz, 20A, Current Probe
GRA-420	Rack Adapter Panel	GCP-1030	Current Probe, DC ~ 100MHz, 30Arms, Current probe
CAK-003	50Ω Impedance Adapter	GCP-206P	Current Probe - Power Supply, 2 Channel Power Supply for GCP-530/1030
GSC-008	Soft Carrying Case	GCP-245P	Current Probe - Power Supply, 4 Channel Power Supply for GCP-530/1030
GTL-232	RS-232C Cable, 9-pin, F-F Type, null modem, 2000mm	GCP-530	Current Probe, DC ~ 50MHz, 30Arms, Current Probe
GTL-246	USB Cable, USB 2.0, A-B Type, 1200mm	GDP-025	Differential Probe, 25M High Voltage Differential Probe
GTL-248	USB Cable, Double Shielded, 2000mm	GDP-050	Differential Probe, 50M High Voltage Differential Probe
GTL-251	USB-GPIB Adapter, GPIB-USB-HS, USB 2.0, Hi-Speed	GDP-100	Differential Probe, 100M High Voltage Differential Probe
	USB compliance, 2000mm	GTP-033A	Oscilloscope Probe, 35MHz 1:1 Passive Probe, BNC(P/M)

FREE DOWNLOAD

PC Software	OpenWave software	Driver	USB driver ; LabView driver
-------------	-------------------	--------	-----------------------------