

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	AC 250 V , DC 350 V			
	CURRENT	5 A	APPLICABLE CABLE	φ8.5	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	CONTACT SHALL BE MEASURED AT DC 1 A	5 mΩ MAX.	X	X	
INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	X	
VOLTAGE PROOF	1000 V AC. FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X	
MECHANICAL CHARACTERISTICS					
CONTACT INSERTION AND WITHDRAWAL FORCES	φ0.97±0.003 BY STEEL GAUGE.	INSERTION AND WITHDRAWAL FORCES : 0.2 N MIN.	X	—	
CONNECTOR INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION AND WITHDRAWAL FORCES LOCKING DEVICE WITH UNLOCK : 16.7 N MAX. LOCKING DEVICE WITH LOCK : — N MAX.	X	—	
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.	CONTACT RESISTANCE: 5 mΩ MAX.	X	—	
VIBRATION	FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, — m/s ² AT 2h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	X	—	
SHOCK	490 m/s ² DURATIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	X	—	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 10 MΩ MIN (AT HIGH HUMIDITY). ② INSULATION RESISTANCE: 100 MΩ MIN (AT DRY). ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40 → R/T ⁽¹⁾ → +100 → R/T °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES.	① INSULATION RESISTANCE: 1000 MΩ MIN.. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X	—	
DRY HEAT	EXPOSED AT + 100 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
COLD	EXPOSED AT - 40 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
0					
REMARK		APPROVED	EJ. KUNII	16.03.03	
(1) R/T : ROOM TEMPERATURE		CHECKED	EJ. KUNII	16.03.03	
		DESIGNED	TY. TAKAHASHI	16.03.03	
Unless otherwise specified, refer to IEC 60512(JIS C 5402).		DRAWN	TY. TAKAHASHI	16.03.03	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-025489-00-00		
HRS	SPECIFICATION SHEET	PART NO.	JR13JK-5S		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL114-0542-4-00	△	1/1