Product data sheet Characteristics

KBB40ABT44W **CENTER FEED UNIT 40A**





Main

Range of product	Canalis	
Product or component type	Feed unit	_
BAR MATERIAL	Aluminium	_
Product compatibility	KBB	_
[le] rated operational current	25 A	
	40 A	•
Mounting location	Central	
Colour	White (RAL 9003)	

Complementary

Main		
Range of product	Canalis	
Product or component type	Feed unit	
BAR MATERIAL	Aluminium	
Product compatibility	KBB	
[le] rated operational current	25 A 40 A	
Mounting location	Central	
Colour	White (RAL 9003)	
Complementary		
Protection type	Without protection	
[Ue] rated operational voltage	230400 V	
Connections - terminals	Terminal block - Pg 21 - screw clamp connector for 610 mm²	
Control type	Without	
Number of circuits	2	
Provided equipment	End cover	
Mounting mode	By clips	
Mounting support	Busbar	
Standards	IEC 60439-2 IEC 61439-6	
Width	244 mm	
Depth	103.5 mm	
Height	75.5 mm	
Net weight	500 g	
Environment		
LIMIOIIIICIIL	IP55 conforming to IEC 60529	

Environment

ZIVII OTITION		
IP degree of protection	IP55 conforming to IEC 60529	

Packing Units

Unit Type of Package 1	PCE	
Unit Type of Package 2	P06	

Offer Sustainability

Sustainable offer status	Green Premium product	
Sustainable offer status	Green Ferman product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection an never end up in rubbish bins	
Halogen content performance	Halogen free product	

Contractual warranty

Contractical Warranty		
Warranty	18 months	