

Pin busbar, 16 mm² connection: 6x 2-phase according to UL 489, 480Y/277V for LS 5SJ4...-HG




Figure similar

Model	
product brand name	SETRON
product designation	Pin busbar
General technical data	
compatibility	for 6 MCBs 2P
phase number	2
Main circuit	
operational current rated value	80 A
Suitability	
suitability for interaction devices with auxiliary switch	No
suitability for interaction devices with N conductor	No
suitability for use	for 6 MCBs 2P
Appearance	
color	light grey
Product details	
product feature insulated	Yes
product function	
• suitable for compact devices	No
• can be cut	No
Number	
number of devices suitable for fitting	6
Connections	
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
width	15 mm
length	205 mm
number of modular width units	12
cross-section	16 mm ²
net weight	138 g
Approvals Certificates	
General Product Approval	other



[Miscellaneous](#)



[Confirmation](#)

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3664-1HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3664-1HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3664-1HG


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





last modified:

5/30/2025 

