

WLL80P-22TGY1DEZZZZ1Z1

WLL80

FIBER-OPTIC AMPLIFIER





Ordering information

Туре	Part no.
WLL80P-22TGY1DEZZZZ1Z1	6076719

Included in delivery: BEF-WLL180 (1)

Other models and accessories → www.sick.com/WLL80

Illustration may differ



Detailed technical data

Features

Teatures		
Device type	Fiber-optic amplifier	
Device type detail	Expansion unit	
Functional principle detail	Depending on the optical fiber cable used	
Sensing range max.	Depending on the optical fiber cable used	
Emitted beam		
Light source	LED	
Type of light	Visible red light	
Key LED figures		
Normative reference	EN 62471:2008-09 IEC 62471:2006, modified	
LED risk group marking	Free group	
Wave length	660 nm	
Average service life	100,000 h at $T_a = +25 ^{\circ}\text{C}$	
Adjustment		
Wire/pin	For deactivating the sender and executing the test logic/for setting the sensing range/for resetting the counter	
Display + operating buttons	For configuring the sensor parameters	
Indication		
LED green	Operating indicator Static on: power on	
LED yellow 1	Status of switching output 1 Permanently on: Switching output 1 active Permanently off: Switching output 1 not active Flashing: Executing teach-in/teach-in error	
LED yellow 2	Status of switching output 2 Permanently on: Switching output 2 active Permanently off: Switching output 2 not active Flashing: Executing teach-in/teach-in error	
Display	Display of sensor functions Menu languages: German, English, Chinese, Korean, Japanese	

	OLED display
Items supplied	BEF-WLL180 mounting bracket

Safety-related parameters

MTTF _D	304.4 years
DC _{avg}	0%
T _M (mission time)	20 years

Communication interface

Serial	✓

Electronics

Supply voltage U _B	12 V DC 24 V DC ¹⁾	
Ripple	± 10 %	
Current consumption	≤ 50 mA	
Protection class	III	
Digital output		
Number	2 (individually adjustable)	
Туре	Push-pull: PNP/NPN, PNP, NPN: open collector ²⁾	
Signal voltage PNP HIGH/LOW	Approx. U_{B} -2.5 V / 0 V	
Signal voltage NPN HIGH/LOW	Approx. $U_B / < 2.5 \text{ V}$	
Output current I _{max.}	≤ 100 mA	
Circuit protection outputs	Reverse polarity protected Overcurrent protected Short-circuit protected	
Response time	≤ 16 μ s, ≤ 70 μ s, ≤ 250 μ s, ≤ 500 μ s, ≤ 1,000 μ s, ≤ 2,000 μ s, ≤ 8,000 μ s	
Switching frequency	31.2 kHz, 7.1 kHz, 2 kHz, 1 kHz, 500 Hz, 250 Hz, 62.5 Hz ⁴⁾	
Time functions	Switch-on delay off delay ON and OFF delay Impulse (one shot) Switch-on delay and pulse de- activated	
Delay time	e Adjustment via operating buttons / via gateway, 0 ms 30,000 ms	
Pin/Wire assignment		
Function of pin 4/black (BK)	Switching output, object present \rightarrow Q1 output HIGH	
Function of pin 2/white (WH)	Switching output, object present \rightarrow Q _{L2} output HIGH	
Function of pin 2/white (WH) - detail	The pin 2 function of the sensor can be configured	

¹⁾ Limit values.

Mechanics

Housing	Rectangular
Dimensions (W x H x D)	10.5 mm x 33.2 mm x 79.9 mm
Connection	Male connector M8, 4-pin
Material	
Housing	Plastic, PC
Weight	Approx. 25 g

²⁾ Selectable via menu.

 $^{^{3)}}$ In bus mode, the fastest response time is 22 $\mu s.$

 $^{^{\}rm 4)}$ With a light/dark ratio of 1:1. In bus mode, the highest switching frequency is 22.7 kHz.

Ambient data

Enclosure rating	IP54 (EN 60529)
Ambient operating temperature	-25 °C +55 °C ¹⁾
Ambient temperature, storage	-40 °C +70 °C
Typ. Ambient light immunity	Artificial light: ≤ 3,000 lx Sunlight: ≤ 10,000 lx
Shock resistance	50 g, $11~\rm ms$ (3 positive and 3 negative shocks along X, Y, Z axes, 18 total shocks (EN60068-2-27))
Vibration resistance	10 Hz 55 Hz (Amplitude 1 mm, 3 x 30 min (EN60068-2-6))
Air humidity	$35\ \% \dots 85\ \%,$ relative humidity (no condensation)
Electromagnetic compatibility (EMC)	EN 60947-5-2

 $^{^{1)}}$ In bus mode, the temperature range is restricted (I $_{max.}$ 20 mA): –25 $^{\circ}\text{C}$... +45 $^{\circ}\text{C}.$

Smart Task

Timer function	Deactivated Switch-on delay Off delay ON and OFF delay Impulse (one shot) Switch-on delay and pulse
Inverter	Yes

Diagnosis


Quality of run	Yes
----------------	-----

Classifications

ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

Adjustments


Display and adjustment elements



- ① Fiber optic interlock
- ② LED yellow 1
- 3 LED green
- 4 LED yellow 2
- ⑤ Indicator for correctly inserted fibers
- 6 Display
- ⑦ (+) button
- ® (-) pushbutton
- Menu/OK pushbutton
- 1 Teach-in/escape pushbutton

Connection type

Male connector M8, 4-pin




Connection diagram

Cd-528

*) Only base unit

Dimensional drawing (Dimensions in mm (inch))



- ① Aperture angle
- ② Hinged cover for the pushbuttons
- ③ Connection
- ④ Connection cap
- Side cover
- ⑤ Female connector for bus module
- Male connector for bus module

Recommended accessories

Other models and accessories → www.sick.com/WLL80

	Brief description	Туре	Part no.
Others			
	• Description: EtherCAT coupler for WLL180T, KTL180 and AOD1. Features: Ether-CAT; transmission rates of up to 100 Mbaud; M12 EtherCAT connection; M8 voltage supply connection, 4-pin; full read/write functionality for the process and service data of the connected sensors. See operating instructions for additional information and technical details	WI180C-EC	6068089
	Description: IO-Link Smart Sensor Gateway for WLL180T, KTL180 and AOD1; Features: IO-Link; COM3; M8 connection, 4-pin; full read/write functionality for the process and service data of the connected sensors. See operating instructions for additional information and technical details	WI180C-IOA00	6071650
	Description: PROFINET coupler for WLL180T, KTL180 and AOD1. Features: PROFINET IRT; transmission rates 10 Mbaud – 100 Mbaud; M12 PROFINET connection; M8 voltage supply connection, 4-pin; full read/write functionality for the process and service data of the connected sensors. See operating instructions for additional information and technical details	WI180C-PN	6068088
Fibers			
	LL3-DT01	LL3-DT01	5308076

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

