

# DISCONNECTABLE PEN SYSTEM



## CERTIFICATIONS



## FEATURES

Dedicated product allowing separation from PEN to PE+N

Unique solution for TN-C/TN-S networks

Safe disconnectable system

Clear identification

Prevents measurement errors

Avoid reconnection errors

Screen stickers included in 12 languages

## SPECIFICATIONS

**Complies With:** IEC® 60439.1; IEC® 61439.1



Table 1/2

Catalog Number	Article Number	Max Current Rating, IEC	Thread Size (TS)	Busbar Width	Busbar Thickness	Depth (D)
PEN-D100	568805	250A	M8	0.79"	0.2"	2.69
PEN-D75	568800	125A	M6	0.59"	0.2"	2.69
PEN-D300	568810	630A	M10	1.18"	0.39"	3.08

Table 2/2

Catalog Number	Article Number	Height (H)	Width (W)	A	B
PEN-D100	568805	6.69"	5.04"	3.94"	4.43"
PEN-D75	568800	4.72"	3.78"	3.94"	2.95"
PEN-D300	568810	6.69"	5.04"	3.94"	4.43"

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

### Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**