

Socket, Harmony Electromechanical Relays, Screw clamp socket with maintaining clamp, for RXG1 relays, 10A, mixed contact terminal

RGZE05E

Main

Range of product	Harmony Electromechanical Relays	
Product or component type	Socket	
Product compatibility	Plug-in relay RXG with 1 C/O contact	
[Ui] rated insulation voltage	250 V	

Complementary

oompicinemal y		
[Uimp] rated impulse withstand voltage	4 kV between terminals and DIN rail with basic insulation	
[Ue] rated operational voltage		
Dielectric strength	4 kV between coil and contact with basic insulation 3 kV between terminals and DIN rail with basic insulation	
Shape of pin	Flat	
Connections - terminals	Screw terminals, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) flexible with cable end Screw terminals, 2 x 0.52 x 1 mm² (AWG 20AWG 17) flexible with cable end Screw terminals, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Screw terminals, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end	
Fixing mode	Clip-on (35 mm symmetrical DIN rail)	
Length	69.6 mm	
Contact terminal arrangement	Mixed	
Overvoltage category	III	
pollution degree	3	
Width	16 mm	
Height	50.2 mm	
Net weight	0.024 kg	

Environment

Standards	IEC 61984
Product certifications	CSA UL EAC
Marking	CE
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4070 °C
IP degree of protection	IP20

Relative humidity 10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.700 cm
Package 1 Width	3.400 cm
Package 1 Length	7.400 cm
Package 1 Weight	23.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.100 cm
Package 2 Width	8.200 cm
Package 2 Length	16.700 cm
Package 2 Weight	263.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	360
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	10.007 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better


Materials and Packaging		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
PVC free	Yes	
Silicon free	Yes	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No

Dimensions Drawings


Dimensions



- (1) Side view (2) Top view
- (3) Front view

Connections and Schema

Wiring



Symbols shown in blue correspond to NEMA marking.

Installation




Note: Wiring recommendations for exposed conductor length

RGZE05E

Technical Illustration

Dimensions






Image of product / Alternate images

Alternative





