

Shunt release, up to 40A, 110-415V, 1HP

Part no. **FAZ-XAA-NA110-415VAC**
102036

General specifications		
Product name		Eaton Distribution parts
Part no.		FAZ-XAA-NA110-415VAC
EAN		4015081019274
Product Length/Depth		105 millimetre
Product height		75.5 millimetre
Product width		17.7 millimetre
Product weight		0.11 kilogram
Compliances		RoHS conform
Certifications		CSA (File No. 204453) UL (File No. E257181) UL 489 IEC/EN 60898 CSA-C22.2 No. 5-09 North America (UL listed, CSA certified) UL (Category Control Number DIHS, DIHS7) CSA (Class No. 1437-01) CE marking IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Shunt release
Additional equipment required		Shunt release (for power circuit breaker)
Ambient operating temperature - max		40 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for 110-V systems
Assembly width		1
Degree of protection		IP20 (IEC) IP40 UL/CSA Type: -
Device fitting		Miniature circuit breaker (MCB)
Enclosure width		105 mm
Frame		Standard front dimension: 45 mm
Frequency rating		50 Hz / 60 Hz
Functions		Shunt release (for power circuit breaker)
Mounting width		17.5 mm (1 space unit)
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		415 V
Rated switch current		0 A
Suitable for current of main contact unit - max		0 A
Terminal protection		Busbar tag shroud to BGV A3
Terminal type		Twin-purpose terminals
Type		Accessory Accessory for miniature circuit breaker

Used with			Shunt releases Accessory for miniature circuit breaker Accessory
Voltage range			110 V AC - 415 V AC
Voltage type			AC/DC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Miniature circuit breaker (MCB)
Additional equipment			Shunt release (for power circuit breaker)
Installed at the factory			No
Width in number of modular spacings			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	415
Voltage type for actuating			AC/DC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	0