KERN **OBE 134T241**



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Digital microscope set
Product family	OBE-S

Display		
Display resolution	2048×1536	

Construction	
Dimension (W×D×H)	360×235×540 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	20:80
Contrasting methods	Bright field Darkfield (optional)
Standard objectives	4× 10× 40× 100×
Lens quality	achromatic
Nosepiece screw-in locations	4
Eyepieces fixed	✓
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	6000 K

Functions		
Camera - Applicable software	integrated	
Supported operating systems	Android	
Memory - total size	128 GB	

Interface	
Interfaces	WiFi standard USB 2.0
	HDMI
	MicroSD card slot

Ocular	
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	18 mm
Ocular diameter	23,2 mm

Illumination	
Illuminance	Transmitted light
Illumination type incident light	none
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓

Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Camera	
Cameratype	Tablet camera
Camera - Resolution	5 MP
Camera - Sensor type	Sony CMOS
Camera - Sensor size	1/2,8"
Camera - Colour depth	Colour
Camera - Framerate	30 fps
Camera- Mounting types	C-mount thread
Camera - Exposure method	Rolling Shutter

Power Supply		
Supplied power supply	Power supply unit	
		4

1

KERN **OBE 134T241**



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Plug-in power supply type Power adapter

Plug-in power supply / adapter for countries - included with the delivery

AUS

Plug-in power supply / adapter for countries - optional

Input voltage power supply / power [Max]

Power adapter for CURO

LURO

LU

Input voltage device / power [Max] 5 V, 1 A

Environmental conditions

Storage temperature [Min] -5 °C Storage temperature [Max] 40 °C

Approval

CE mark

D I		0	O.L			
Pac	king	X۷	5°	110		١ø
1 40	B	\sim	٠.	шъ	ייי	ס'

Delivery time 1 d
Dimensions packaging (W×D×H) 560×440×330 mm

Net weight 5,978 kg
Shipping method Parcel service

Net weight approx. 6 kg
Gross weight approx. 8 kg
Shipping weight 16,3 kg

Pictograms

STANDARD











OPTION



