


Eaton 172742

Catalog Number: 172742

Eaton Moeller® series EMS Control cable connector; 3 Devices

General specifications



Product Name	Catalog Number
Eaton Moeller® series EMS control cable 172742 connector	

EAN
4015081693009

Product Length/Depth
220 mm

Product Height
150 mm

Product Width
160 mm

Product Weight
0.03 kg

Compliances
CE

Catalog Notes
Conductor cross-section: 0.75 mm²

Features & Functions

Number Of Poles

Single-pole

General

Accessory/spare part type

Connecting cable

Product category

Accessories

Electronic motor starter

Used with

3 devices can be connected

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Design verification

Equipment heat dissipation, current-dependent P_{vid}

0.007 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.007 W

Rated operational current for specified heat dissipation (I_n)

0.4 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

[eaton-ems2-electronic-motorstarter-brochure-br034001en-en-us.pdf](#)

Catalogs

[Switching and protecting motors - catalog](#)

Drawings

[eaton-contactors-3d-drawing-013.eps](#)

eCAD model

[DA-CE-ETN.EMS-XCW-3](#)

Installation instructions

[IL03407198Z](#)

[IL120002ZU](#)

Installation videos

[Eaton's electronic motor starter EMS2](#)

Sales notes

[eaton-ems2-electronic-motorstarter-flyer-fl034007en-en-us.pdf](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia