






RIG DOG LIGHT NBR

Knitted cut protection gloves with nitrile foam coating and impact protection cover

FEATURES & BENEFITS:

- Seamlessly knitted highly comfortable and flexible liner
- Special design of impact protection pad offers good finger mobility
- Nitrile foam palm coating provides excellent grip
- Knitted cuff provides additional wrist protection
- Glass fibre-free
- With recycled polyester

ATTRIBUTE	DESCRIPTION / VALUES
Article No. Name	<ul style="list-style-type: none"> • 2332524N • Rig Dog Light NBR
Liner Material	<ul style="list-style-type: none"> • HPPE, steel fibre, recycled polyester/Spandex
Coating	<ul style="list-style-type: none"> • Nitrile foam
Impact protection cover	<ul style="list-style-type: none"> • PVC
Length (mm)	<ul style="list-style-type: none"> • 220-266 mm
Total thickness	<ul style="list-style-type: none"> • 0,85 ± 0,1 mm
Gauge	<ul style="list-style-type: none"> • 15
Dexterity	<ul style="list-style-type: none"> • 5
Colour	<ul style="list-style-type: none"> • Green, Black
Size	<ul style="list-style-type: none"> • 6 - 11
Classification	<ul style="list-style-type: none"> • Category II <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <small>EN ISO 21420</small>  </div> <div style="text-align: center;"> <small>EN 388:2016</small>  </div> <div style="text-align: center;"> <small>ANSI 3</small>  </div> <div style="text-align: center;"> <small>ANSI A4</small>  </div> <div style="text-align: center;"> <small>ANSI 3</small>  </div> </div> <p style="font-size: 8px; margin-top: 5px;"> <small>EN ISO 21420 4X42DP ABRASION CUT PUNCTURE</small> </p>



INDUSTRIES:

- Oil & Gas
- Building & Construction
- Civil engineering & steel construction
- Mechanical and plant engineering
- Mining and quarrying
- Marine industry & aviation
- Wood industry
- Manufacturing
- Warehouse & Logistics

APPLICATIONS:

- Handling of heavy parts in oily work environments
- Rigging
- Confined Space
- Material transportation
- Shipbuilding
- Drilling

Care & Maintenance: Not tested for washability
Storage in dry place below 40°C. Shelf life: 3 years

Packaging: 12 pairs in a bag, 10 bags in a case

FOR TECHNICAL QUESTIONS

HONEYWELL PPE TECHNICAL SUPPORT PORTAL:

<https://sps-support.honeywell.com/s/>

UNITED KINGDOM

Honeywell Safety Products UK LTD
Honeywell House, Skimped Hill Lane,
Bracknell, Berkshire RG12 1EB
United Kingdom
Phone: +44 (0) 1256 274938
Email: info-uk.hsp@honeywell.com

sps.honeywell.com

BENELUX

Honeywell Safety Products Benelux BV
Lange Amerikaweg 55
1H – 1831 Diegem
7332 BP Apeldoorn, Nederland
Tel: +31 (0) 20 5656 988
Email: info-benelux.hsp@honeywell.com

NORDICS

Honeywell Safety Products Nordic AB
Box 15 147
SE-167 15 Bromma – Sverige
Phone: +46 (0) 424480433
Email: info-nordic.hsp@honeywell.com

Honeywell