

### Main

Range of product	AccuSine
Product name	AccuSine PFV+
Product or component type	Electronic VAR controller

### Complementary

Network type	3P
Network configuration	3 or 4 wires
Network rated voltage	380...480 V AC
Network frequency	50/60 Hz +/- 3 % auto-sensing
Maximum permissible voltage	1.1 x Un
RMS output current rating	200 A
Reactive power rating	166 kvar 480 V AC 50/60 Hz
Operating mode	Volt-var support Mains current balancing Power factor correction
Installation location	Indoor
Enclosure mounting	Floor-standing
Protection type	Circuit breaker protection
Disconnect type	Door-interlocked with rotary handle
Interrupt capacity	200 kA
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Conducted EMC, class A conforming to EN 61000-6-4
Accessibility for operation	Front
Location of connection	Top or bottom

### Environment

Enclosure degree of protection	UL type 12
Environmental characteristic	Operating: 3C2 conforming to IEC 60721-3-3 Operating: 3S2 conforming to IEC 60721-3-3 Storage: 3C3 conforming to IEC 60721-3-3 Storage: 3S3 conforming to IEC 60721-3-3
Operating altitude	<= 1000 m 1 % per 100 m
Ambient air temperature for operation	0...40 °C 0...50 °C maximum with current derating of 2 % per °C
Relative humidity	0...95 %
PCBA protection	Conformal coated
Standards	UL 60947-1 CSA C22.2 No 14 CSA C22.2 No 60947-1-07 EN 60439-1 UL 508 EN 61000-6-4
Product certifications	cULus[RETURN]ABS[RETURN]CE[RETURN]RCM

Ambient air temperature for storage	-20...60 °C
Height	2100 mm
Width	900 mm
Depth	600 mm
Colour	Light grey (RAL 7035)

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins