

Aquacoat Plus #918-9121

RS Components

Chemwatch: **5301-30** Version No: **2.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: **28/03/2018** Print Date: **04/04/2018** L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Aquacoat Plus #918-9121	
Synonyms	Not Available	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 4,5-dichloro-2-octyl-3(2H)-isothiazolone and 3-iodo-2-propynyl butyl carbamate)	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use according to manufacturer's directions.

Appliance protection.

Details of the supplier of the safety data sheet

Registered company name	RS Components	RS Components
Address	25 Pavesi Street Smithfield NSW 2164 Australia	Level 6, Agility CIS Tower, 56 Cawley Street Ellerslie Auckland 1051 New Zealand
Telephone	+1 300 656 636	+64 27 4747122
Fax	+1 300 656 696	+64 9 579 1700
Website	Not Available	www.nz.rs-online.com
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	1800 039 008 (24 hours),+61 3 9573 3112	Not Available
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

DANGEROUS GOODS. NON-HAZARDOUS CHEMICAL. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1		
Toxicity	0		0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	0		4 = Extreme

Poisons Schedule	Not Applicable	
Classification [1]	Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)



Chemwatch: **5301-30** Page **2** of **10**Version No: **2.1.1.1**

Aquacoat Plus #918-9121

Issue Date: **28/03/2018**Print Date: **04/04/2018**

SIGNAL WORD NOT

NOT APPLICABLE

Hazard statement(s)

H411

Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P273

Avoid release to the environment.

Precautionary statement(s) Response

P391

Collect spillage.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
111-76-2	5-10	ethylene glycol monobutyl ether
34590-94-8	<1	dipropylene glycol monomethyl ether
64359-81-5	<1	4,5-dichloro-2-octyl-3(2H)-isothiazolone
1332-58-7	<1	<u>kaolin</u>
55406-53-6	NotSpec.	3-iodo-2-propynyl butyl carbamate

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

- ► Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- ▶ Seek medical attention in event of irritation.

Inhalation

- ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

Ingestion

- If swallowed do NOT induce vomiting.
 If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
 - ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Alcohol stable foam
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.

Do not use water jets.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.

Chemwatch: 5301-30 Page 3 of 10 Issue Date: 28/03/2018 Version No: 2.1.1.1 Print Date: 04/04/2018

Aquacoat Plus #918-9121

 Combustible. Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). Fire/Explosion Hazard Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. **HAZCHEM**

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Environmental hazard - contain spillage.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Safe handling

Precautions for safe handling

▶ DO NOT allow clothing wet with material to stay in contact with skin

The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe

- ▶ DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential.
 - Any static discharge is also a source of hazard. ▶ Before any distillation process remove trace peroxides by shaking with excess 5% aqueous ferrous sulfate solution or by percolation through a column of
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - ▶ Use in a well-ventilated area.

activated alumina.

- Prevent concentration in hollows and sumps.
- Other information
- ▶ Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- ► Store in a cool, dry, well-ventilated area.

Avoid reaction with oxidising agents

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
	► Check all containers are clearly labelled and free from leaks.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	96.9 mg/m3 / 20 ppm	242 mg/m3 / 50 ppm	Not Available	Not Available
Australia Exposure Standards	dipropylene glycol monomethyl ether	(2-Methoxymethylethoxy) propanol	308 mg/m3 / 50 ppm	Not Available	Not Available	Not Available
Australia Exposure Standards	kaolin	Kaolin	10 mg/m3	Not Available	Not	Not

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethylene glycol monobutyl ether	Butoxyethanol, 2-; (Glycol ether EB)	60 ppm	120 ppm	700 ppm
dipropylene glycol monomethyl ether	Dipropylene glycol methyl ether	150 ppm	1700 ppm	9900 ppm
3-iodo-2-propynyl butyl carbamate	Butyl-3-iodo-2-propynylcarbamate	3.3 mg/m3	36 mg/m3	220 mg/m3

Chemwatch: **5301-30**Page **4** of **10**Issue Date: **28/03/2018**Version No: **2.1.1.1**Print Date: **04/04/2018**

Aquacoat Plus #918-9121

Leves Post	October LIBITE	Partie UPUU
Ingredient	Original IDLH	Revised IDLH
ethylene glycol monobutyl ether	700 ppm	Not Available
dipropylene glycol monomethyl ether	600 ppm	Not Available
4,5-dichloro-2-octyl- 3(2H)-isothiazolone	Not Available	Not Available
kaolin	Not Available	Not Available
3-iodo-2-propynyl butyl carbamate	Not Available	Not Available

MATERIAL DATA

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. Appropriate engineering The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. controls Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Personal protection Safety glasses with side shields. Chemical goggles. Eye and face protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task Skin protection See Hand protection below Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber Personal hygiene is a key element of effective hand care. Hands/feet protection ► Butyl rubber gloves ▶ Nitrile rubber gloves See Other protection below **Body protection** Other protection P.V.C. apron. Barrier cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

Thermal hazards

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Not Available

Aquacoat Plus #918-9121

Material	CPI
BUTYL	С
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NEOPRENE	С
NITRILE	С
PE/EVAL/PE	С
PVA	С
PVC	С
SARANEX-23	С

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

White liquid.

Chemwatch: 5301-30

Page **5** of **10** Version No: 2.1.1.1

Aquacoat Plus #918-9121

Issue Date: 28/03/2018 Print Date: 04/04/2018

Physical state	Liquid	Relative density (Water = 1)	1.03
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	180-220 @23C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7	
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

o			
Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.		
Ingestion	Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Еуе	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.		
	TOXICITY	IRRITATION	
	Dermal (None) LD50: 17187.5 mg/kg* ^[2]	Not Available	
Aquacoat Plus #918-9121	Inhalation (None) LC50: 171.88 mg/l (vapours)* ^[2]		
	Oral (None) LD50: 27281.25 mg/kg* ^[2]		
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 100 mg SEVERE	
ethylene glycol monobutyl ether	Inhalation (rat) LC50: 449.48655 mg/l/4H ^[2]	Eye (rabbit): 100 mg/24h-moderate	
	Oral (rat) LD50: 250 mg/kg ^[2]	Skin (rabbit): 500 mg, open; mild	
dipropulana alucal manamathul	TOXICITY	IRRITATION	
dipropylene glycol monomethyl ether	dermal (rat) LD50: >19020 mg/kg ^[1]	Eye (human): 8 mg - mild	

Issue Date: **28/03/2018**Print Date: **04/04/2018**

Aquacoat Plus #918-9121

	Oral (rat) LD50: 5135 mg/kg ^[2]	Eye (rabbit): 500 r	ng/24hr - mild
		Skin (rabbit): 238	mg - mild
	٤	Skin (rabbit): 500	mg (open)-mild
4,5-dichloro-2-octyl-	TOXICITY	IRRITATION	
3(2H)-isothiazolone	Inhalation (rat) LC50: 0.758 mg/l/4h*[2]	Not Available	
	TOXICITY	IRRITATION	
kaolin	Not Available	Not Available	
	TOXICITY	IRRITATION	
2 iada 2 propunul hutul	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye: Irritating	
3-iodo-2-propynyl butyl carbamate	[0]	Skin: Slight irritan	ıt
	Oral (rat) LD50: 1056 mg/kg ^[2]		
	, , , , ,		
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* data extracted from RTECS - Register of Toxic Effect of chemical Substances	* Value obtained fi	rom manufacturer's SDS. Unless otherwise specified
ETHYLENE GLYCOL MONOBUTYL ETHER	The material may produce severe irritation to the eye causing pronounced inflamic conjunctivitis. For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ether and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catal transient metabolites). Further, rapid conversion of the aldehydes by aldehyde defurinary metabolites of mono substituted glycol ethers. Acute Toxicity: Oral LD50 values in rats for all category members range from 7: decreasing molecular weight. Exposure of pregnant rats to ethylene glycol monobutyl ether (2-butoxyethanol) at toxicity and embryotoxicity including a decreased number of viable implantations skeletal elements was also apparent in rats. Teratogenic effects were not observe At least one researcher has stated that the reproductive effects were less than that For ethylene glycol: Ethylene glycol is quickly and extensively absorbed through the gastrointestinal trespiratory tract; dermal absorption is apparently slow. Following absorption, ethywater. In most mammalian species, including humans, ethylene glycol is initially in NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposses.	hylene glycol buty lyzes the convers hydrogenase proc 39 (EGHE) to 300 at 100 ppm or rabt per litter. Slight for ed in other specie at of other monoal tract. Limited infor lylene glycol is dis metabolised by ald	of ether (EGBE) and ethylene glycol hexyl ether (EGHE) ion of their terminal alcohols to aldehydes (which are luces alkoxyacetic acids, which are the predominant is mg/kg bw (EGPE), with values increasing with boits at 200 ppm during organogenesis resulted in maternal etoxicity in the form of poorly ossified or unossified s. kyl ethers of ethylene glycol. mation suggests that it is also absorbed through the tributed throughout the body according to total body cohol.
DIPROPYLENE GLYCOL MONOMETHYL ETHER	for propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on reproductive organs, the developing embryo and fetus, blood (haemolytic effects), or thymus, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
4,5-DICHLORO-2-OCTYL- 3(2H)-ISOTHIAZOLONE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. Guinea Pig Assay: causes sensitisation * Did not show teratogenic effects in animal experiments. * Not mutagenic * *Rohm and Haas MSDS Rozone 2000 Mildewcide		
3-IODO-2-PROPYNYL BUTYL CARBAMATE	for 3-iodo-2-propynyl butyl carbamate (IPBC): Acute toxicity: Acceptable acute toxicity studies with IPBC indicate low toxicity except eye irritation. In a primary eye irritation study in rabbi. IPBC technical was severely irritating to the eyes of white rabbits, with comeal opacity and comeal vascularization reported in unwashed eyes by day 21 post-treatment. The technical grade of IPBC was slightly irritating to the skin of white rabbits.		
ETHYLENE GLYCOL MONOBUTYL ETHER & DIPROPYLENE GLYCOL MONOMETHYL ETHER	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.		
DIPROPYLENE GLYCOL MONOMETHYL ETHER & 4,5-DICHLORO-2-OCTYL- 3(2H)-ISOTHIAZOLONE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.		
Acute Toxicity	X Ca	arcinogenicity	0
Skin Irritation/Corrosion	○ Re	eproductivity	0
Serious Eye Damage/Irritation	○ STOT - Sing	gle Exposure	0
Respiratory or Skin sensitisation	STOT - Repeated Exposure		

Chemwatch: 5301-30 Page **7** of **10** Version No: 2.1.1.1

Aquacoat Plus #918-9121

Issue Date: 28/03/2018 Print Date: 04/04/2018

Mutagenicity

Aspiration Hazard

Legend:

🗶 – Data available but does not fill the criteria for classification

 Data available to make classification ○ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Aquacoat Plus #918-9121	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
athedrica where I was not be to distant	LC50	96	Fish	1250mg/L	4
thylene glycol monobutyl ether	EC50	48	Crustacea	>1000mg/L	4
	NOEC	96	Crustacea	1000mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1930mg/L	2
dipropylene glycol monomethyl ether	EC50	48	Crustacea	1930mg/L	2
ether	EC50	72	Algae or other aquatic plants	>969mg/L	2
	NOEC	72	Algae or other aquatic plants	969mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.0027mg/L	4
4,5-dichloro-2-octyl- 3(2H)-isothiazolone	EC50	48	Crustacea	0.00522mg/L	4
0(211) 100111102010110	EC50	96	Algae or other aquatic plants	0.018mg/L	4
	NOEC	24	Algae or other aquatic plants	0.02709408mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
kaolin	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
3-iodo-2-propynyl butyl	LC50	96	Fish	0.067mg/L	4
carbamate	EC50	48	Crustacea	0.04mg/L	5
	NOEC	48	Crustacea	<0.01mg/L	4

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol monobutyl ether LOW (Half-life = 56 days)		LOW (Half-life = 1.37 days)
dipropylene glycol monomethyl ether	нівн	нен
4,5-dichloro-2-octyl- 3(2H)-isothiazolone	нівн	нен
3-iodo-2-propynyl butyl carbamate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation	
ethylene glycol monobutyl ether	LOW (BCF = 2.51)	
dipropylene glycol monomethyl ether LOW (BCF = 100)		
4,5-dichloro-2-octyl- 3(2H)-isothiazolone HIGH (LogKOW = 4.7295)		
3-iodo-2-propynyl butyl carbamate LOW (LogKOW = 2.4542)		

Mobility in soil

,	
Ingredient	Mobility

Chemwatch: 5301-30 Page 8 of 10 Issue Date: 28/03/2018 Version No: 2.1.1.1 Print Date: 04/04/2018

Aquacoat Plus #918-9121

ethylene glycol monobutyl ether	HIGH (KOC = 1)
dipropylene glycol monomethyl ether	LOW (KOC = 10)
4,5-dichloro-2-octyl- 3(2H)-isothiazolone	LOW (KOC = 5796)
3-iodo-2-propynyl butyl carbamate	LOW (KOC = 365.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Product / Packaging disposal
- ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant



HAZCHEM

•3Z

Land transport (ADG)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 4,5-dichloro-2-octyl-3(2H)-isothiazolone and 3-iodo-2-propynyl butyl carbamate)		
Transport hazard class(es)	Class 9 Subrisk Not Applicable		
Packing group			
Environmental hazard	Environmentally hazardous		
Special precautions for user	Special provisions 274 331 335 375 AU01 Limited quantity 5 L		

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 $\,$ are not subject to this Code when transported by road or rail in;

(a) packagings; (b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

UN number	3082			
UN proper shipping name	Environmentally hazardo	Environmentally hazardous substance, liquid, n.o.s. * (contains 4,5-dichloro-2-octyl-3(2H)-isothiazolone and 3-iodo-2-propynyl butyl carbamate)		
Transport hazard class(es)	ICAO/IATA Class 9 ICAO / IATA Subrisk Not Applicable ERG Code 9L			
Packing group				
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions		A97 A158 A197 964 450 L 964	

Chemwatch: **5301-30**Page **9** of **10**Issue Date: **28/03/2018**Version No: **2.1.1.1**Print Date: **04/04/2018**

Aquacoat Plus #918-9121

Passenger and Cargo Maximum Qty / Pack 450 L

Passenger and Cargo Limited Quantity Packing Instructions Y964

Passenger and Cargo Limited Maximum Qty / Pack 30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 4,5-dichloro-2-octyl-3(2H)-isothiazolone and 3-iodo-2-propynyl butyl carbamate)
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable
Packing group	III
Environmental hazard	Marine Pollutant
Special precautions for user	EMS Number F-A , S-F Special provisions 274 335 969 Limited Quantities 5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

E (Part 2)

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHYLENE GLYCOL MONOBUTYL ETHER(111-76-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

F

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Part 2, Section Seven - Appendix I

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

DIPROPYLENE GLYCOL MONOMETHYL ETHER(34590-94-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards
Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)

4,5-DICHLORO-2-OCTYL-3(2H)-ISOTHIAZOLONE(64359-81-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

KAOLIN(1332-58-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards
Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)

3-IODO-2-PROPYNYL BUTYL CARBAMATE(55406-53-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule

National Inventory	Status
Australia - AICS	Y
Canada - DSL	N (4,5-dichloro-2-octyl-3(2H)-isothiazolone)
Canada - NDSL	N (3-iodo-2-propynyl butyl carbamate; kaolin; dipropylene glycol monomethyl ether; ethylene glycol monobutyl ether)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (kaolin)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Chemwatch: 5301-30 Page 10 of 10 Issue Date: 28/03/2018 Version No: 2.1.1.1 Print Date: 04/04/2018

Aquacoat Plus #918-9121

Other information

Ingredients with multiple cas numbers

Name	CAS No
dipropylene glycol monomethyl ether	34590-94-8, 12002-25-4, 112388-78-0, 104512-57-4, 83730-60-3, 112-28-7, 13429-07-7, 20324-32-7, 13588-28-8, 55956-21-3
kaolin	1332-58-7, 71888-52-3, 1026990-70-4, 12198-85-5, 12199-11-0, 190086-05-6, 290817-34-4, 384842-32-4, 39406-22-9, 52624-41-6, 849104-81-0, 903527-69-5, 90803-81-9, 944250-63-9, 95077-05-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term Exposure Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.