



**SAFETY DATA SHEET
FLEXANE 80L RESIN.**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FLEXANE 80L RESIN.

Product number X0020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word

Danger

FLEXANE 80L RESIN.

Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
Precautionary statements	P261 Avoid breathing vapour/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
Contains	4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P284 [In case of inadequate ventilation] wear respiratory protection. P312 Call a POISON CENTER/ doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)	1-2%
CAS number: 5124-30-1	EC number: 225-863-2
Classification	
Acute Tox. 3 - H331	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	
STOT SE 3 - H335	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

FLEXANE 80L RESIN.

General information	Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Persons with impaired lung function should not handle this product.. Persons susceptible to allergic reactions should not handle this product.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly. May cause sensitisation by inhalation.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Avoid breathing fire gases or vapours.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to flames with water until well after the fire is out. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.
--------------------------------	--

6.4. Reference to other sections

FLEXANE 80L RESIN.

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Handle and open container with care. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE) (CAS: 5124-30-1)

DNEL

Workers - Inhalation; Short term local effects: 0.6 mg/m³

Workers - Inhalation; Long term local effects: 0.3 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC). To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Wear chemical protective suit.

FLEXANE 80L RESIN.

Hygiene measures	Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Promptly remove any clothing that becomes wet or contaminated.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear liquid.
pH	pH (concentrated solution): 7 @ 25 °C
Melting point	n/d°C
Initial boiling point and range	>149.°C @
Flash point	>234.°C
Vapour pressure	<10 mmHg @ °C
Relative density	1.04 @ 25 °C°C
Viscosity	3.2-8.5 Pa s @ °C

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Alcohols, glycols. Amines. Alkalis.
-------------------	-------------------------------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not available.
---	----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Water, moisture. Alcohols, glycols. Amines. Alkalis.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire or high temperatures create: Nitrous gases (NO _x). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂). Vapours/gases/fumes of: Ammonia or amines.
---	---

FLEXANE 80L RESIN.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (gases ppm) 2,668.5

ATE inhalation (vapours mg/l) 11.44

ATE inhalation (dusts/mists mg/l) 1.91

Inhalation Irritating to respiratory system. May cause sensitisation by inhalation.

Skin contact Irritating to skin. May cause sensitisation or allergic reactions in sensitive individuals.

Acute and chronic health hazards Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Persons with impaired lung function should not handle this product. Persons susceptible to allergic reactions should not handle this product. The product contains small quantities of isocyanate. May cause respiratory allergy. May cause respiratory system irritation.

4,4'-METHYLENEDI(CYCLOHEXYL ISOCYANATE)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 18,200.0

Species Rat

ATE oral (mg/kg) 18,200.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,000.0

Species Rat

ATE dermal (mg/kg) 7,000.0

Acute toxicity - inhalation

ATE inhalation (gases ppm) 700.0

ATE inhalation (vapours mg/l) 3.0

ATE inhalation (dusts/mists mg/l) 0.5

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1.2mg/l mg/l, Algae

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >500mg/l mg/l, Daphnia magna

FLEXANE 80L RESIN.

12.2. Persistence and degradability

Persistence and degradability Assessment of biological degradability (Closed-Bottle Test) 60 %.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

No information required.

14.2. UN proper shipping name

No information required.

14.3. Transport hazard class(es)

No information required.

14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

FLEXANE 80L RESIN.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 03/04/2018

Revision 18

Supersedes date 25/04/2017

Hazard statements in full H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



**SAFETY DATA SHEET
FLEXANE 80/94L HARDENER**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FLEXANE 80/94L HARDENER

Product number X0023

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Eye Irrit. 2 - H319 STOT RE 2 - H373

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

2.2. Label elements

Pictogram



Signal word

Warning

Hazard statements

H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

FLEXANE 80/94L HARDENER

Precautionary statements

P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 Get medical advice/ attention if you feel unwell.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains DIETHYLMETHYLBENZENEDIAMINE

Supplementary precautionary statements

P260 Do not breathe vapour/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P330 Rinse mouth.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P391 Collect spillage.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIETHYLMETHYLBENZENEDIAMINE	30-60%
CAS number: 68479-98-1	EC number: 270-877-4
M factor (Acute) = 1	M factor (Chronic) = 1
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Eye Irrit. 2 - H319 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
CARBON BLACK	<1%
CAS number: 1333-86-4	
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Avoid contact with eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Do not induce vomiting. Give plenty of water to drink. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

FLEXANE 80/94L HARDENER

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Do not breathe vapour. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination. Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Handle and open container with care. Use only in well-ventilated areas. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Store away from incompatible materials (see Section 10).

FLEXANE 80/94L HARDENER

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

CARBON BLACK

Long-term exposure limit (8-hour TWA): 3.5 mg/m³

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate general and local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn. It is recommended that gloves are made of the following material: Neoprene. It is recommended that gloves are made of the following material: Nitrile rubber. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection Wear chemical protective suit.

Hygiene measures Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Promptly remove any clothing that becomes wet or contaminated.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Black.
Odour	Slight.

FLEXANE 80/94L HARDENER

pH	pH (concentrated solution): 8.5 @ 25 °C
Melting point	n/d°C
Initial boiling point and range	>232°C @
Flash point	>177°C
Vapour density	<1
Relative density	1.08 @ 20 °C°C
Viscosity	160-320 mPa s @ 25°C

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Acids. Strong oxidising agents.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire or high temperatures create: Nitrous gases (NOx). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO2). Vapours/gases/fumes of: Ammonia or amines.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,461.43

Acute toxicity - dermal

ATE dermal (mg/kg) 3,215.15

Inhalation Irritating to respiratory system. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Ingestion Harmful if swallowed.

Skin contact Irritating to skin. Harmful in contact with skin.

Eye contact Irritating to eyes.

SECTION 12: Ecological Information

FLEXANE 80/94L HARDENER

Ecotoxicity Avoid releasing into the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Very toxic to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

Road transport notes Refer to the Dangerous Goods List for information on any Special Provisions 375.

Rail transport notes Refer to the Dangerous Goods List for information on any Special Provisions 375.

Sea transport notes Refer to the Dangerous Goods List for information on any Special Provisions IMDG 2.10.2.7.

Air transport notes Refer to the Dangerous Goods List for information on any Special Provisions 375.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

FLEXANE 80/94L HARDENER

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	03/04/2018
Revision	15
Supersedes date	25/04/2017
Hazard statements in full	H302 Harmful if swallowed. H312 Harmful in contact with skin. H319 Causes serious eye irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.