

513.1657

SURFACE MOUNTING SOCKET
16A 3P+N+E 6h 346-415V 60Hz 50Hz
Screw terminals



* Product image may be indicative



EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-BASE Series
Synthetical description	SURFACE MOUNTING SOCKET
Description	
The OPTIMA-BASE Series surface mounting socket is engineered for robust industrial applications. Featuring an angled outlet design, it accommodates a 3P+N+E configuration with a rated current of 16A. It operates efficiently within a working frequency range of 50Hz to 60Hz and supports a rated voltage of 346-415V. The socket is designed with a 6h hour position and offers an IP44 protection degree, ensuring reliable performance in demanding environments. It is equipped with screw terminals for secure connections. The product includes an open threaded cable entry and a rubber threaded cable sleeve, enhancing its versatility and ease of installation.	
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M25X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Rubber threaded cable sleeve included