

Product data sheet

Specifications



trip unit MicroLogic 7.2 E for
ComPact NSX 100/160/250 circuit
breakers, electronic, rating 40A, 4
poles 4d

LV433879

⚠ To be discontinued

⚠ Discontinued on: 30 September 2022

Important message : This product has been switched to new ComPact range and is no longer commercialized. It will continue to be available until Q4 2022 only limited to specific projects.

Main

Range	ComPact
Range of product	ComPact NSX100...250
Product or component type	Trip unit
Trip unit name	Micrologic 7.2 E
Trip unit technology	Electronic
Range compatibility	ComPact NSX100 ComPact NSX160 ComPact NSX250
Device application	Distribution
Number of poles	4P
Protected poles description	4t 3t 3t + N/2 3t + OSN
Neutral position	Left
Trip unit protection functions	LSIR
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection R : for earth-leakage protection
Trip unit rated current	40 A at 40 °C
[Ue] rated operational voltage	440 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	18...40 A
Long-time protection delay adjustment type tr	Adjustable

[Tr] long-time protection delay adjustment range	15...400 s at 1.5 x Ir 0.35...11 s at 7.2 x Ir 0.5...16 s at 6 x Ir
Thermal memory	20 minutes before and after tripping
Short-time protection pick-up adjustment type Isd	Adjustable
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Adjustable
[Tsd] Short-time protection delay adjustment range	0...0.4 s
Instantaneous protection pick-up adjustment type li	Adjustable
[li] instantaneous protection pick-up adjustment range	600 A
Earth-leakage protection	Integrated
Earth-leakage protection class	Class A
Earth-leakage protection sensivity adjustment type IΔn	Adjustable
[IΔn] earth-leakage protection sensitivity adjustment range	100 mA 3 A 500 mA 5 A 30 mA 300 mA 1 A
Earth-leakage protection specific mode	OFF using the IΔn rotary switch
Earth-leakage protection time delay adjestment type Δt	Adjustable
[Δt] Earth-leakage protection time delay adjustment range	500 ms 0 ms 150 ms 60 ms 1 s
Neutral protection settings	0.5 x Ir (3t + N/2) 1 x Ir (4t) 1.6 x Ir (3t + OSN) No protection (3t)
Zone selective interlocking ZSI	Without
Local signalling	Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload
Display type	LCD display
Type of measurement	Energy meter
Communication of data	Maintenance indicators Instantaneous and demand values Time-stamped histories and event tables Maximeters/minimeters Earth leakage current Demand current and power Power quality Test reports Protection and alarm settings Energy metering

Environment

Standards	NEMA AB1 UL 508 EN 60947-2 IEC 60947-2
Product certifications	CB CCC

	EAC
Pollution degree	3 conforming to IEC 60947-1
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	806.0 g
Package 1 Height	9.5 cm
Package 1 width	11.0 cm
Package 1 Length	15.0 cm
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Weight	8.488 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

LV433879 is replaced by:

1x



Trip unit MicroLogic Vigi 7.2E, ComPacT NSX100/160/250, 4 poles, basic and earth leakage protections, energy meter, 40A
C1047E040