

For Automotive 45 V 500 mA Fixed/Adjustable Output QuiCur™ LDO Regulators

BD9xxM5-C Series

General Description

The BD9xxM5-C series are linear regulators using the QuiCur™ topology^(Note 1) designed as low current consumption products for power supplies in various automotive applications requiring a direct connection to the battery. These products are designed for up to 45 V as an absolute maximum voltage and to operate until 500 mA for the output current with low current consumption 9.5 μ A (Typ). These can regulate the output with a very high accuracy ± 2.0 %. The output voltage line-up are 3.3 V, 5.0 V and Adjustable type by an external resistive divider. The output voltage can be adjusted between 1.0 V and 18 V by an external resistive divider connected to the ADJ pin.

Output shutdown function is integrated in the devices^(Note 2). A logical "HIGH" at the EN pin turns on the device, and the devices are controlled to disable by a logical "LOW" input to the EN pin.

The devices feature the integrated Over Current Protection to protect the device from a damage caused by a short-circuiting or an overload. These products also integrate Thermal Shutdown Protection to avoid the damage by overheating and Under Voltage Lock Out to avoid false operation at low input voltage.

Furthermore, low ESR ceramic capacitors are sufficiently applicable for the phase compensation.

^(Note 1) QuiCur™ is a combination of technologies that provides high-speed load response.

^(Note 2) Applicable for product with Output shutdown Function.

Key Specifications

- Wide Temperature Range (Tj): -40 °C to +150 °C
- Wide Operating Input Range: 3 V to 42 V
- Output Voltage: 3.3 V / 5.0 V / Adjustable
- Low Current Consumption^(Note 3): 9.5 μ A (Typ)
- Output Current Capability: 500 mA
- Output Voltage Accuracy^(Note 4): ± 2.0 %

^(Note 3) It does not contain the current of external feedback resistance.

^(Note 4) The effect of external feedback resistor is not included.

Features

- QuiCur™ Topology
- AEC-Q100 Qualified^(Note 5)
- Functional Safety Supportive Automotive Products
- Automotive Grade
- Over Current Protection (OCP)
- Thermal Shutdown Protection (TSD)
- Under Voltage Lock Out (UVLO)

^(Note 5) Grade 1

Applications

- Automotive (Power Train, Body ECU)
- Car Infotainment System, etc.
- Also General Consumer, Industrial Equipment, etc.

Packages

- TO252-3
- TO252-5
- HRP5
- HTSOP-J8

W (Typ) x D (Typ) x H (Max)

- 6.5 mm x 9.5 mm x 2.5 mm
- 6.5 mm x 9.5 mm x 2.5 mm
- 9.395 mm x 10.540 mm x 2.005 mm
- 4.9 mm x 6.0 mm x 1.0 mm



TO252-3



TO252-5



HRP5



HTSOP-J8

QuiCur™ is a trademark or a registered trademark of ROHM Co., Ltd.

○Product structure : Silicon integrated circuit ○This product has no designed protection against radioactive rays.

www.rohm.com

© 2021 ROHM Co., Ltd. All rights reserved.

TSZ22111 • 14 • 001

Typical Application Circuits1 (Output voltage fixed type)


Components Externally Connected

Capacitor: $0.1 \mu\text{F} \leq C_{\text{IN}} (\text{Min})$, $1 \mu\text{F} \leq C_{\text{OUT}} (\text{Min})$ ^(Note 1)


^(Note 1) Electrolytic capacitor, tantalum capacitor and ceramic capacitors can be used.

In case of using electrolytic capacitor or tantalum capacitor with large ESR ($> 100 \text{ m}\Omega$), note that ceramic capacitor with $1 \mu\text{F}$ (Min) and more must be connected near VOUT pin in parallel.

Applicable for product without Output shutdown Function



Applicable for product with Output shutdown Function



Typical Application Circuits2 (Output voltage adjustable type)

Components Externally Connected

Capacitor: $0.1 \mu\text{F} \leq C_{\text{IN}} (\text{Min})$, $1 \mu\text{F} \leq C_{\text{OUT}} (\text{Min})$ ^(Note 2)

Resistor: $5 \text{ k}\Omega \leq R_1 \leq 200 \text{ k}\Omega$ ^(Note 3)

$V_{\text{ADJ}} (\text{Typ}): 0.65 \text{ V}$

$$R_2 = R_1 \left(\frac{V_{\text{OUT}}}{V_{\text{ADJ}}} - 1 \right)$$

^(Note 2) Electrolytic capacitor, tantalum capacitor and ceramic capacitors can be used.


In case of using electrolytic capacitor or tantalum capacitor with large ESR ($> 100 \text{ m}\Omega$), note that ceramic capacitor with $1 \mu\text{F}$ (Min) and more must be connected near VOUT pin in parallel.

^(Note 3) The value of a feedback resistor R_1 must be within this range.


R_2 value is defined by following the formula using the limitation of R_1 .

Error occurs due to the resistance value used and the ADJ pin input current.

Applicable for product without Output shutdown Function




Applicable for product with Output shutdown Function



Contents

General Description	1
Key Specifications	1
Features.....	1
Applications	1
Packages	1
Typical Application Circuits1 (Output voltage fixed type)	2
Typical Application Circuits2 (Output voltage adjustable type)	2
Pin Configurations	4
Pin Descriptions.....	4
Block Diagrams.....	6
Description of Blocks	8
Absolute Maximum Ratings	9
Thermal Resistance.....	10
Operating Conditions	11
Electrical Characteristics.....	12
Typical Performance Curves 5 V Output	15
Typical Performance Curves 3.3 V Output.....	23
Measurement Circuit for Typical Performance Curves	29
Application and Implementation.....	31
Selection of External Components	31
Input Pin Capacitor	31
Output Pin Capacitor	31
Typical Application.....	32
Surge Voltage Protection for Linear Regulators	33
Positive Surge to the Input.....	33
Negative Surge to the Input	33
Reverse Voltage Protection for Linear Regulators	33
Protection against Reverse Input/Output Voltage	33
Protection against Input Reverse Voltage.....	34
Protection against Reverse Output Voltage when Output Connect to an Inductor.....	35
Power Dissipation	36
Thermal Design	38
I/O Equivalence Circuit	40
Operational Notes.....	42
1. Reverse Connection of Power Supply	42
2. Power Supply Lines.....	42
3. Ground Voltage.....	42
4. Ground Wiring Pattern.....	42
5. Operating Conditions.....	42
6. Inrush Current.....	42
7. Thermal Consideration	42
8. Testing on Application Boards	42
9. Inter-pin Short and Mounting Errors	42
10. Unused Input Pins	42
11. Regarding the Input Pin of the IC	43
12. Ceramic Capacitor.....	43
13. Thermal Shutdown Protection Circuit (TSD).....	43
14. Over Current Protection Circuit (OCP)	43
15. Functional Safety.....	43
Ordering Information.....	44
Lineup.....	44
Marking Diagrams.....	45
Physical Dimension and Packing Information	47
Revision History.....	51

Pin Configurations



Pin Descriptions

(TO252-3) BD9xxM5FP-C (xx = 33, 50)

Pin No.	Pin Name	Function	Descriptions
1	VIN	Input Supply Voltage Pin	Set a capacitor with a capacitance of 0.1 μ F (Min) or higher between the VIN pin and the GND pin. The selecting method is described in Selection of External Components . If the impedance or inductance of power supply line is high, adjust input capacitor value.
2	N.C.	-	This pin is not connected (N.C.) to the chip. This pin can be left open.
3	VOUT	Output Voltage Pin	Set a capacitor with a capacitance of 1 μ F (Min) or higher between the VOUT pin and the GND pin. The selecting method is described in Selection of External Components .
FIN	GND	Ground Pin	Ground.

(TO252-5) BD900M5FP-C, BD9xxM5WFP-C (xx = 33, 50, 00)

Pin No.	Pin Name	Function	Descriptions
1	VIN	Input Supply Voltage Pin	Set a capacitor with a capacitance of 0.1 μ F (Min) or higher between the VIN pin and the GND pin. The selecting method is described in Selection of External Components . If the impedance or inductance of power supply line is high, adjust input capacitor value.
2	(EN)	(Control Output ON / OFF Pin)	A logical "HIGH" ($V_{EN} \geq 2.0$ V) at the EN pin enables the device and "LOW" ($V_{EN} \leq 0.8$ V) at the EN pin disables the device. Although the output is turned off when the EN pin is open, it is recommended to connect it to GND with low impedance to prevent incorrect operation. Without Output shutdown Function, this pin is not connected (N.C.) to the chip. <i>(Note 1)</i>
3	N.C.	-	This pin is not connected (N.C.) to the chip. This pin can be left open.
4	(ADJ)	(Adjustment Pin For Output Voltage)	Connect an external resistor between the VOUT pin and the ADJ pin and between the ADJ pin and the GND pin to adjust output voltage. Output voltage fixed type, this pin is not connected (N.C.) to the chip. <i>(Note 1)</i>
5	VOUT	Output Voltage Pin	Set a capacitor with a capacitance of 1 μ F (Min) or higher between the VOUT pin and the GND pin. The selecting method is described in Selection of External Components .
FIN	GND	Ground Pin	Ground.

(Note 1) N.C. pin can be either left floated or for connect to GND.

Pin Descriptions – continued

(HRP5) BD9xxM5HFP-C, BD9xxM5WHFP-C (xx = 33, 50, 00)

Pin No.	Pin Name	Function	Descriptions
1	VIN	Input Supply Voltage Pin	Set a capacitor with a capacitance of 0.1 μ F (Min) or higher between the VIN pin and the GND pin. The selecting method is described in Selection of External Components . If the impedance or inductance of power supply line is high, adjust input capacitor value.
2	(EN)	(Control Output ON / OFF Pin)	A logical "HIGH" ($V_{EN} \geq 2.0$ V) at the EN pin enables the device and "LOW" ($V_{EN} \leq 0.8$ V) at the EN pin disables the device. Although the output is turned off when the EN pin is open, it is recommended to connect it to GND with low impedance to prevent incorrect operation. Without Output shutdown Function, this pin is not connected (N.C.) to the chip. (Note 1)
3	GND	Ground Pin	Ground.
4	(ADJ)	(Adjustment Pin For Output Voltage)	Connect an external resistor between the VOUT pin and the ADJ pin and between the ADJ pin and the GND pin to adjust output voltage. Output voltage fixed type, this pin is not connected (N.C.) to the chip. (Note 1)
5	VOUT	Output Voltage Pin	Set a capacitor with a capacitance of 1 μ F (Min) or higher between the VOUT pin and the GND pin. The selecting method is described in Selection of External Components .
FIN	GND	Ground Pin	Ground. It is recommended to connect FIN to external Ground pattern in order to make heat dissipation better.

(Note 1) N.C. pin can be either left floated or for connect to GND.

(HTSOP-J8) BD9xxM5EFJ-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)


Pin No.	Pin Name	Function	Descriptions
1	VOUT	Output Voltage Pin	Set a capacitor with a capacitance of 1 μ F (Min) or higher between the VOUT pin and the GND pin. The selecting method is described in Selection of External Components .
2	(ADJ)	(Adjustment Pin For Output Voltage)	Connect an external resistor between the VOUT pin and the ADJ pin and between the ADJ pin and the GND pin to adjust output voltage. Output voltage fixed type, this pin is not connected (N.C.) to the chip. (Note 1)
3	N.C.	-	This pin is not connected (N.C.) to the chip. (Note 1)
4	N.C.	-	This pin is not connected (N.C.) to the chip. (Note 1)
5	GND	Ground Pin	Ground.
6	N.C.	-	This pin is not connected (N.C.) to the chip. (Note 1)
7	(EN)	(Control Output ON / OFF Pin)	A logical "HIGH" ($V_{EN} \geq 2.0$ V) at the EN pin enables the device and "LOW" ($V_{EN} \leq 0.8$ V) at the EN pin disables the device. Although the output is turned off when the EN pin is open, it is recommended to connect it to GND with low impedance to prevent incorrect operation. Without Output shutdown Function, this pin is not connected (N.C.) to the chip. (Note 1)
8	VIN	Input Supply Voltage Pin	Set a capacitor with a capacitance of 0.1 μ F (Min) or higher between the VIN pin and the GND pin. The selecting method is described in Selection of External Components . If the impedance or inductance of power supply line is high, adjust input capacitor value.
-	EXP-PAD	Heat Dissipation	It is recommended to connect EXP-PAD on the back side to external ground pattern in order to make heat dissipation better.

(Note 1) N.C. pin can be either left floated or for connect to GND.

Block Diagrams


Applicable for product output voltage fixed type without Output shutdown Function

• BD9xxM5FP-C, BD9xxM5HFP-C, BD9xxM5EFJ-C (xx = 33, 50)



Applicable for product output voltage fixed type with Output shutdown Function


·BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50)



Block Diagrams – continued


Applicable for product output voltage adjustable type without Output shutdown Function

·BD900M5FP-C, BD900M5HFP-C, BD900M5EFJ-C



Applicable for product output voltage adjustable type with Output shutdown Function

·BD900M5WFP-C, BD900M5WHFP-C, BD900M5WEFJ-C



Description of Blocks

BD9xxM5FP-C, BD9xxM5HFP-C, BD9xxM5EFJ-C (xx = 33, 50, 00)

Block Name	Function	Description of Blocks
PREREG	Internal Power Supply	Power supply for internal circuit.
TSD	Thermal Shutdown Protection	In case maximum power dissipation exceeds or when the junction temperature rises and the chip temperature (T _j) exceeds the heating protection set temperature. The TSD protection circuit detects this and forces the gate of output MOSFET to turn off in order to protect the device from overheating. (Typ: 175 °C) When the junction temperature decreases to low, the thermal Shutdown protection is released and the output turns on automatically.
VREF	Internal Reference Voltage	Generate the reference voltage.
AMP	Error Amplifier	The fixed output voltage product compares the voltage obtained by dividing the output voltage with the reference voltage, and the variable output voltage product compares the ADJ voltage with the reference voltage, and controls the output power transistor via the DRIVER.
DRIVER	Output MOSFET Driver	Drive the output MOSFET.
OCP	Over Current Protection	If the output current increases higher than the maximum output current, it is limited by Over Current Protection in order to protect the device from a damage caused by an over current. (Typ: 900 mA) While this block is operating, the output voltage may decrease because the output current is limited. If an abnormal state is removed and the output current value returns to normal, the output voltage also returns to normal state.
DISCHARGE	Output Discharge Function	Output pin is discharged when TSD is detected.
UVLO	Under Voltage Lock Out	The Under Voltage Lock Out protection detects when V _{IN} voltage becomes less than 2.4 V (Typ), it forces AMP to turn off in order to avoid any false operation at low input voltage.

BD9xxM5WFP-C, BD9xxM5WHFP-C BD9xxM5WEFJ-C (xx = 33, 50, 00)

Block Name	Function	Description of Blocks
EN	Enable Input	A logical "HIGH" (V _{EN} ≥ 2.0 V) at the EN pin enables the device and "LOW" (V _{EN} ≤ 0.8 V) at the EN pin disables the device.
PREREG	Internal Power Supply	Power supply for internal circuit.
TSD	Thermal Shutdown Protection	In case maximum power dissipation exceeds or when the junction temperature rises and the chip temperature (T _j) exceeds the heating protection set temperature. The TSD protection circuit detects this and forces the gate of output MOSFET to turn off in order to protect the device from overheating. (Typ: 175 °C) When the junction temperature decreases to low, the thermal Shutdown protection is released and the output turns on automatically.
VREF	Internal Reference Voltage	Generate the reference voltage.
AMP	Error Amplifier	The fixed output voltage product compares the voltage obtained by dividing the output voltage with the reference voltage, and the variable output voltage product compares the ADJ voltage with the reference voltage, and controls the output power transistor via the DRIVER.
DRIVER	Output MOSFET Driver	Drive the output MOSFET.
OCP	Over Current Protection	If the output current increases higher than the maximum output current, it is limited by Over Current Protection in order to protect the device from a damage caused by an over current. (Typ: 900 mA) While this block is operating, the output voltage may decrease because the output current is limited. If an abnormal state is removed and the output current value returns to normal, the output voltage also returns to normal state.
DISCHARGE	Output Discharge Function	Output pin is discharged when EN = "LOW" input or TSD is detected.
UVLO	Under Voltage Lock Out	The Under Voltage Lock Out protection detects when V _{IN} voltage becomes less than 2.4 V (Typ), it forces AMP to turn off in order to avoid any false operation at low input voltage.

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Input Voltage ^(Note 1)	V _{IN}	-0.3 to +45	V
EN Pin Voltage ^(Note 2)	V _{EN}	-0.3 to +45	V
VOUT Pin Voltage	V _{OUT}	-0.3 to +20 ($\leq V_{IN} + 0.3$)	V
ADJ Pin Voltage ^(Note 3)	V _{ADJ}	-0.3 to +7	V
Junction Temperature Range	T _J	-40 to +150	°C
Storage Temperature Range	T _{stg}	-55 to +150	°C
Maximum Junction Temperature	T _{jmax}	150	°C
ESD Withstand Voltage (HBM) ^(Note 4)	V _{ESD_HBM}	±2000	V
ESD Withstand Voltage (CDM) ^(Note 5)	V _{ESD_CDM}	±750	V

Caution 1: Operating the IC over the absolute maximum ratings may damage the IC. The damage can either be a short circuit between pins or an open circuit between pins and the internal circuitry. Therefore, it is important to consider circuit protection measures, such as adding a fuse, in case the IC is operated over the absolute maximum ratings.

Caution 2: Should by any chance the maximum junction temperature rating be exceeded the rise in temperature of the chip may result in deterioration of the properties of the chip. In case of exceeding this absolute maximum rating, design a PCB with thermal resistance and power dissipation taken into consideration by increasing board size and copper area so as not to exceed the maximum junction temperature rating.

(Note 1) Do not exceed T_{jmax}.

(Note 2) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)

The start-up orders of Input Voltage (V_{IN}) and the V_{EN} do not influence if the voltage is within the operation power supply voltage range.

(Note 3) Applicable for product with BD900M5FP-C, BD900M5WFP-C, BD900M5HFP-C, BD900M5WHFP-C, BD900M5EFJ-C, BD900M5WEFJ-C.

(Note 4) ESD susceptibility Human Body Model "HBM"; base on ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF).

(Note 5) ESD susceptibility Charged Device Model "CDM"; base on AEC-Q100-011.

Thermal Resistance^(Note 1)

Parameter	Symbol	Thermal Resistance (Typ)		Unit
		1s ^(Note 3)	2s2p ^(Note 4)	
TO252-3				
Junction to Ambient	θ_{JA}	122.3	23.0	°C/W
Junction to Top Characterization Parameter ^(Note 2)	Ψ_{JT}	14	3	°C/W
TO252-5				
Junction to Ambient	θ_{JA}	122.3	23.0	°C/W
Junction to Top Characterization Parameter ^(Note 2)	Ψ_{JT}	14	3	°C/W
HRP5				
Junction to Ambient	θ_{JA}	91.0	21.9	°C/W
Junction to Top Characterization Parameter ^(Note 2)	Ψ_{JT}	7	3	°C/W
HTSOP-J8				
Junction to Ambient	θ_{JA}	129.0	26.0	°C/W
Junction to Top Characterization Parameter ^(Note 2)	Ψ_{JT}	10	3	°C/W

(Note 1) Based on JESD51-2A (Still-Air), using a BD950M5FP-C, BD950M5WFP-C, BD950M5WHFP-C, BD950M5WEFJ-C Chip.

(Note 2) The thermal characterization parameter to report the difference between junction temperature and the temperature at the top center of the outside surface of the component package.

(Note 3) Using a PCB board based on JESD51-3.

(Note 4) Using a PCB board based on JESD51-5, 7.

Layer Number of Measurement Board	Material	Board Size
Single	FR-4	114.3 mm x 76.2 mm x 1.57 mmt

Top	
Copper Pattern	Thickness
Footprints and Traces	70 μ m

Layer Number of Measurement Board	Material	Board Size	Thermal Via ^(Note 5)	
			Pitch	Diameter
4 Layers	FR-4	114.3 mm x 76.2 mm x 1.6 mmt	1.20 mm	Φ 0.30 mm

Top		2 Internal Layers		Bottom	
Copper Pattern	Thickness	Copper Pattern	Thickness	Copper Pattern	Thickness
Footprints and Traces	70 μ m	74.2 mm x 74.2 mm	35 μ m	74.2 mm x 74.2 mm	70 μ m

(Note 5) This thermal via connect with the copper pattern of layers 1, 2, and 4. The placement and dimensions obey a land pattern.

Operating Conditions ($-40\text{ }^{\circ}\text{C} \leq T_j \leq +150\text{ }^{\circ}\text{C}$)

Parameter	Symbol	Min	Max	Unit
Input Voltage ^{(Note 1)(Note 2)}	V_{IN}	4.5	42.0	V
		$V_{OUT}(\text{Max}) + \Delta V_D(\text{Max})$	42.0	V
Start-up Voltage	$V_{IN \text{ Start-Up}}$	3	-	V
Output Voltage ^(Note 3)	V_{OUT}	1	18	V
Feedback Resistor ADJ vs GND ^(Note 3)	R_1	5	200	k Ω
EN Input Voltage ^(Note 4)	V_{EN}	0	42	V
Output Current	I_{OUT}	0	500	mA
Input Capacitor ^{(Note 5)(Note 6)}	C_{IN}	0.1	-	μF
Output Capacitor ^(Note 6)	C_{OUT}	1	500	μF
Output Capacitor Equivalent Series Resistance ^(Note 7)	ESR (C_{OUT})	-	100	m Ω
Operating Temperature	T_a	-40	+125	$^{\circ}\text{C}$

(Note 1) Consider that the output voltage would be dropped (Dropout voltage ΔV_D) by the output current.

(Note 2) Apply 4.5V or $V_{OUT}(\text{Max}) + \Delta V_D(\text{Max})$, whichever is higher.

(Note 3) Applicable for product with BD900M5FP-C, BD900M5WFP-C, BD900M5HFP-C, BD900M5WHFP-C, BD900M5EFJ-C, BD900M5WEFJ-C.

(Note 4) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)

(Note 5) If the inductance of power supply line is high, adjust input capacitor value in order to lower the input impedance.

A lower input impedance can bring out the ideal characteristic of IC as much as possible.

It also has the effect of preventing the voltage-drop at the input line.

(Note 6) Set capacitor value which do not fall below the minimum value. This value needs to consider the temperature characteristics and DC bias characteristics.

(Note 7) It is recommended to use ceramic capacitors that have low ESR characteristics for the output phase compensation.

In case of using electrolytic capacitor or tantalum capacitor with large ESR ($> 100\text{ m}\Omega$), note that ceramic capacitor with 1 μF (Min) and more must be connected near the V_{OUT} pin in parallel.

Electrical Characteristics

BD9xxM5FP-C, BD9xxM5WFP-C, BD9xxM5HFP-C, BD9xxM5WHFP-C (xx = 33, 50, 00)

Unless otherwise specified, T_j = -40 °C to +150 °C, V_{IN} = 13.5 V, V_{EN} = 5 V^(Note 1), I_{OUT} = 0 mA, C_{OUT} = 2.2 μF

Output voltage adjustable type V_{OUT} setting = 5 V, R₁ = 200 kΩ, R₂ = 1338 kΩ

Typical values are defined at T_j = 25 °C, V_{IN} = 13.5 V

Parameter	Symbol	Limits			Unit	Conditions
		Min	Typ	Max		
Circuit Current ^(Note 2)	I _{CC}	-	9.5	19.5	μA	I _{OUT} = 0 mA, T _j ≤ 125 °C
		-	9.5	24.5	μA	I _{OUT} = 0 mA, T _j ≤ 150 °C
Output Voltage ^(Note 3)	V _{OUT}	3.234	3.300	3.366	V	4.6 V ≤ V _{IN} ≤ 42 V 0 mA ≤ I _{OUT} ≤ 500 mA
Output Voltage ^(Note 4)	V _{OUT}	4.900	5.000	5.100	V	5.85 V ≤ V _{IN} ≤ 42 V 0 mA ≤ I _{OUT} ≤ 300 mA or 6.35 V ≤ V _{IN} ≤ 42 V 0 mA ≤ I _{OUT} ≤ 500 mA
Reference Voltage ^(Note 5)	V _{ADJ}	0.637	0.650	0.663	V	At V _{OUT} setting ≥ 3.25 V, V _{OUT} setting + 1.25 V ≤ V _{IN} ≤ 42 V 0 mA ≤ I _{OUT} ≤ 500 mA or At V _{OUT} setting < 3.25 V, 4.5 V ≤ V _{IN} ≤ 42 V 0 mA ≤ I _{OUT} ≤ 500 mA
Dropout Voltage	ΔV _{D1}	-	440	840	mV	V _{IN} = 3.135 V, I _{OUT} = 300 mA
	ΔV _{D2}	-	740	1400	mV	V _{IN} = 3.135 V, I _{OUT} = 500 mA
	ΔV _{D3}	-	390	750	mV	V _{IN} = 4.75 V, I _{OUT} = 300 mA
	ΔV _{D4}	-	660	1250	mV	V _{IN} = 4.75 V, I _{OUT} = 500 mA
Ripple Rejection ^(Note 6)	R.R.	-	70	-	dB	f = 1 kHz V _{Ripple} = 1 V _{rms} I _{OUT} = 100 mA
Line Regulation	Reg.I1	-	0.1	0.3	%	V _{OUT} setting + 1.5 V ≤ V _{IN} ≤ 42 V (V _{OUT} setting ≥ 3.0 V)
	Reg.I2	-	3	9	mV	4.5 V ≤ V _{IN} ≤ 42 V (V _{OUT} setting < 3.0 V)
Load Regulation	Reg.L1	-	0.1	0.5	%	0 mA ≤ I _{OUT} ≤ 500 mA (V _{OUT} setting ≥ 3.0 V)
	Reg.L2	-	3	15	mV	0 mA ≤ I _{OUT} ≤ 500 mA (V _{OUT} setting < 3.0 V)
ADJ Input Current ^{(Note 5)(Note 6)}	I _{ADJ}	-	0	15	nA	V _{ADJ} = 1 V

(Note 1) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C (xx = 33, 50, 00)

(Note 2) Adjustable output voltage type does not contain the current of R₁ and R₂.

(Note 3) Applicable for product with BD933M5FP-C, BD933M5WFP-C, BD933M5HFP-C, BD933M5WHFP-C

(Note 4) Applicable for product with BD950M5FP-C, BD950M5WFP-C, BD950M5HFP-C, BD950M5WHFP-C

(Note 5) Applicable for product with BD900M5FP-C, BD900M5WFP-C, BD900M5HFP-C, BD900M5WHFP-C

(Note 6) Not all devices are measured for shipment.

Electrical Characteristics – continued

BD9xxM5EFJ-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

Output voltage adjustable type V_{OUT} setting = 5 V , $R_1 = 200\text{ k}\Omega$, $R_2 = 1338\text{ k}\Omega$

Typical values are defined at $T_j = 25\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$

Parameter	Symbol	Limits			Unit	Conditions
		Min	Typ	Max		
Circuit Current (Note 2)	I_{CC}	-	9.5	19.5	μA	$I_{OUT} = 0\text{ mA}$, $T_j \leq 125\text{ }^{\circ}\text{C}$
		-	9.5	24.5	μA	$I_{OUT} = 0\text{ mA}$, $T_j \leq 150\text{ }^{\circ}\text{C}$
Output Voltage (Note 3)	V_{OUT}	3.234	3.300	3.366	V	$4.5\text{ V} \leq V_{IN} \leq 42\text{ V}$ $0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$
Output Voltage (Note 4)	V_{OUT}	4.900	5.000	5.100	V	$5.76\text{ V} \leq V_{IN} \leq 42\text{ V}$ $0\text{ mA} \leq I_{OUT} \leq 300\text{ mA}$ or $6.2\text{ V} \leq V_{IN} \leq 42\text{ V}$ $0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$
Reference Voltage (Note 5)	V_{ADJ}	0.637	0.650	0.663	V	At V_{OUT} setting $\geq 3.4\text{ V}$, V_{OUT} setting $+ 1.1\text{ V} \leq V_{IN} \leq 42\text{ V}$ $0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$ or At V_{OUT} setting $< 3.4\text{ V}$, $4.5\text{ V} \leq V_{IN} \leq 42\text{ V}$ $0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$
Dropout Voltage	ΔV_{D1}	-	410	760	mV	$V_{IN} = 3.135\text{ V}$, $I_{OUT} = 300\text{ mA}$
	ΔV_{D2}	-	680	1300	mV	$V_{IN} = 3.135\text{ V}$, $I_{OUT} = 500\text{ mA}$
	ΔV_{D3}	-	360	660	mV	$V_{IN} = 4.75\text{ V}$, $I_{OUT} = 300\text{ mA}$
	ΔV_{D4}	-	600	1100	mV	$V_{IN} = 4.75\text{ V}$, $I_{OUT} = 500\text{ mA}$
Ripple Rejection (Note 6)	R.R.	-	70	-	dB	$f = 1\text{ kHz}$ $V_{Ripple} = 1\text{ V}_{rms}$ $I_{OUT} = 100\text{ mA}$
Line Regulation	Reg.I1	-	0.1	0.3	%	V_{OUT} setting $+ 1.5\text{ V} \leq V_{IN} \leq 42\text{ V}$ (V_{OUT} setting $\geq 3.0\text{ V}$)
	Reg.I2	-	3	9	mV	$4.5\text{ V} \leq V_{IN} \leq 42\text{ V}$ (V_{OUT} setting $< 3.0\text{ V}$)
Load Regulation	Reg.L1	-	0.1	0.5	%	$0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$ (V_{OUT} setting $\geq 3.0\text{ V}$)
	Reg.L2	-	3	15	mV	$0\text{ mA} \leq I_{OUT} \leq 500\text{ mA}$ (V_{OUT} setting $< 3.0\text{ V}$)
ADJ Input Current (Note 5)(Note 6)	I_{ADJ}	-	0	15	nA	$V_{ADJ} = 1\text{ V}$

(Note 1) Applicable for product with BD9xxM5WEFJ-C (xx = 33, 50, 00)

(Note 2) Adjustable output voltage type does not contain the current of R_1 and R_2 .

(Note 3) Applicable for product with BD933M5EFJ-C, BD933M5WEFJ-C

(Note 4) Applicable for product with BD950M5EFJ-C, BD950M5WEFJ-C

(Note 5) Applicable for product with BD900M5EFJ-C, BD900M5WEFJ-C

(Note 6) Not all devices are measured for shipment.

Electrical Characteristics – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

Output voltage adjustable type V_{OUT} setting = 5 V , $R_1 = 200\text{ k}\Omega$, $R_2 = 1338\text{ k}\Omega$

Typical values are defined at $T_j = 25\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$

Parameter	Symbol	Limits			Unit	Conditions
		Min	Typ	Max		
UVLO Fall Threshold	V_{UVLOF}	1.8	2.4	2.8	V	V_{IN} falling
UVLO Rise Threshold	V_{UVLOR}	2.0	2.6	3.0	V	V_{IN} rising
UVLO Hysteresis	$V_{UVLOHYS}$	-	0.2	-	V	-
Over Current Protection	I_{OCP}	501	900	1300	mA	-
Thermal Shutdown Temperature	T_{TSD}	151	175	-	$^{\circ}\text{C}$	-
Thermal Shutdown Hysteresis	T_{TSDHYS}	-	15	-	$^{\circ}\text{C}$	-

(Note 1) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)

Electrical Characteristics (Applicable for product with Output shutdown Function) (Note 2)

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

Output voltage adjustable type V_{OUT} setting = 5 V , $R_1 = 200\text{ k}\Omega$, $R_2 = 1338\text{ k}\Omega$

Typical values are defined at $T_j = 25\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$

Parameter	Symbol	Limits			Unit	Conditions
		Min	Typ	Max		
Shutdown Current	I_{SHUT}	-	1	5	μA	$V_{EN} = 0\text{ V}$ $T_j \leq 125\text{ }^{\circ}\text{C}$
EN ON Threshold Voltage	V_{ENTH}	1.05	1.45	2.00	V	V_{EN} rising
EN OFF Threshold Voltage	V_{ENTL}	0.80	1.27	1.70	V	V_{EN} falling
EN Hysteresis Voltage	V_{ENHYS}	-	0.18	-	V	-
EN Bias Current	I_{EN}	-	4	8	μA	$V_{EN} = 5\text{ V}$
VOUT Discharge Resistance	R_{DSC}	2.6	6.5	11.0	$\text{k}\Omega$	$V_{EN} = 0\text{ V}$

(Note 2) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50, 00)

Typical Performance Curves 5 V Output

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 1. Circuit Current vs Input Voltage
(5 V Output)




Figure 2. Circuit Current vs Input Voltage;
Enlarged view of Figure 1 at narrow Circuit Current range
(5 V Output)




Figure 3. Ground Current vs Output Current
(5 V Output)




Figure 4. Ground Current vs Output Current;
Enlarged view of Figure 3 at low Output Current
(5 V Output)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 5. Circuit Current vs Junction Temperature (5 V Output)




Figure 6. Output Voltage vs Junction Temperature (5 V Output)




Figure 7. Dropout Voltage vs Output Current (5 V Output, $V_{IN} = 4.75\text{ V}$)




Figure 8. Ripple Rejection vs Frequency (5 V Output, $V_{Ripple} = 1\text{ Vrms}$, $I_{OUT} = 100\text{ mA}$)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 9. Output Voltage vs Input Voltage
(5 V Output)




Figure 10. Output Voltage vs Input Voltage;
Enlarged view of Figure 9 at narrow Output Voltage range
(5 V Output, Line Regulation)




Figure 11. Output Voltage vs Input Voltage;
Enlarged view of Figure 9 at low Input Voltage
(5 V Output)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 12. Output Voltage vs Output Current
(5 V Output, Load Regulation)




Figure 13. Output Voltage vs Output Current
(5 V Output, Over Current Protection)




Figure 14. Output Voltage vs Junction Temperature
(5 V Output, Thermal Shutdown)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_J = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 15. Reference Voltage vs Junction Temperature
(Output voltage adjustable type; $V_{OUT} = 5\text{ V}$ setting)




Figure 16. Shutdown Current vs Input Voltage
($V_{EN} = 0\text{ V}$)




Figure 17. EN Bias Current vs EN Input Voltage




Figure 18. Output Voltage vs EN Input Voltage
(5 V Output)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_a = 25\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 19. Load Transient 1 mA to 500 mA
(5 V Output, $T_r = 1\text{ }\mu\text{s}$)




Figure 20. Load Transient 500 mA to 1 mA
(5 V Output, $T_f = 1\text{ }\mu\text{s}$)




Figure 21. Load Transient 150 mA to 350 mA
(5 V Output, $T_r = 1\text{ }\mu\text{s}$)




Figure 22. Load Transient 350 mA to 150 mA
(5 V Output, $T_f = 1\text{ }\mu\text{s}$)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_a = 25^\circ\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 23. Line Transient 8 V to 16 V
(5 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 24. Line Transient 16 V to 8 V
(5 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 25. Line Transient 8 V to 16 V
(5 V Output, $I_{OUT} = 500\text{ mA}$)




Figure 26. Line Transient 16 V to 8 V
(5 V Output, $I_{OUT} = 500\text{ mA}$)

Typical Performance Curves 5 V Output – continued

Unless otherwise specified, $T_a = 25\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 27. VIN Startup Waveform
 V_{IN} : 0 V to 16 V
 (5 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 28. VIN Startup Waveform
 V_{IN} : 0 V to 16 V
 (5 V Output, $I_{OUT} = 500\text{ mA}$)




Figure 29. EN Startup Waveform
 (5 V Output, $I_{OUT} = 1\text{ mA}$)




Figure 30. EN Shutdown Waveform
 (5 V Output, $I_{OUT} = 1\text{ mA}$)

Typical Performance Curves 3.3 V Output

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 31. Circuit Current vs Input Voltage
(3.3 V Output)




Figure 32. Circuit Current vs Input Voltage;
Enlarged view of Figure 31 at narrow Circuit Current range
(3.3 V Output)




Figure 33. Ground Current vs Output Current
(3.3 V Output)




Figure 34. Ground Current vs Output Current;
Enlarged view of Figure 33 at low Output Current
(3.3 V Output)

Typical Performance Curves 3.3 V Output – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 35. Circuit Current vs Junction Temperature
(3.3 V Output)




Figure 36. Output Voltage vs Junction Temperature
(3.3 V Output)




Figure 37. Dropout Voltage vs Output Current
(3.3 V Output, $V_{IN} = 3.135\text{ V}$)




Figure 38. Ripple Rejection vs Frequency
(3.3 V Output, $V_{Ripple} = 1\text{ Vrms}$, $I_{OUT} = 100\text{ mA}$)

Typical Performance Curves 3.3 V Output – continued

Unless otherwise specified, $T_j = -40\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 39. Output Voltage vs Input Voltage
(3.3 V Output)




Figure 40. Output Voltage vs Input Voltage;
Enlarged view of Figure 39 at narrow output voltage range
(3.3 V Output)




Figure 41. Output Voltage vs Output Current
(3.3 V Output, Load Regulation)




Figure 42. Output Voltage vs Output Current
(3.3 V Output, Over Current Protection)

Typical Performance Curves 3.3 V Output – continued

Unless otherwise specified, $T_a = 25^\circ\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 43. Load Transient 1 mA to 500 mA
(3.3 V Output, $Tr = 1\text{ }\mu\text{s}$)




Figure 44. Load Transient 500 mA to 1 mA
(3.3 V Output, $Tf = 1\text{ }\mu\text{s}$)




Figure 45. Load Transient 150 mA to 350 mA
(3.3 V Output, $Tr = 1\text{ }\mu\text{s}$)




Figure 46. Load Transient 350 mA to 150 mA
(3.3 V Output, $Tf = 1\text{ }\mu\text{s}$)

Typical Performance Curves 3.3 V Output – continued

Unless otherwise specified, $T_a = 25^\circ\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 47. Line Transient 8 V to 16 V
(3.3 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 48. Line Transient 16 V to 8 V
(3.3 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 49. Line Transient 8 V to 16 V
(3.3 V Output, $I_{OUT} = 500\text{ mA}$)




Figure 50. Line Transient 16 V to 8 V
(3.3 V Output, $I_{OUT} = 500\text{ mA}$)

Typical Performance Curves 3.3 V Output – continued

Unless otherwise specified, $T_a = 25^\circ\text{C}$, $V_{IN} = 13.5\text{ V}$, $V_{EN} = 5\text{ V}$ (Note 1), $I_{OUT} = 0\text{ mA}$, $C_{OUT} = 2.2\text{ }\mu\text{F}$

(Note 1) Applicable for product with Output shutdown Function.




Figure 51. VIN Startup Waveform
 V_{IN} : 0 V to 16 V
(3.3 V Output, $I_{OUT} = 0\text{ mA}$)




Figure 52. VIN Startup Waveform
 V_{IN} : 0 V to 16 V
(3.3 V Output, $I_{OUT} = 500\text{ mA}$)




Figure 53. EN Startup Waveform
(3.3 V Output, $I_{OUT} = 1\text{ mA}$)






Figure 54. EN Shutdown Waveform
(3.3 V Output, $I_{OUT} = 1\text{ mA}$)


Measurement Circuit for Typical Performance Curves




Measurement Setup for
Figure 1 to 5, 16, 31 to 35




Measurement Setup for
Figure 6, 9 to 12, 14, 36, 39 to 41




Measurement Setup for
Figure 7, 37




Measurement Setup for
Figure 8, 38




Measurement Setup for
Figure 13, 42



Measurement Setup for
Figure 17, 18




Measurement Setup for
Figure 29, 30, 53, 54



Measurement Setup for
Figure 19 to 28, 43 to 52

Measurement Circuit for Typical Performance Curves – continued



Measurement Setup for
Figure 15

Application and Implementation

Notice: The following information is given as a reference or hint for the application and the implementation. Therefore, it does not guarantee its operation on the specific function, accuracy or external components in the application. In the application, it shall be designed with sufficient margin by enough understanding about characteristics of the external components, e.g. capacitor, and also by appropriate verification in the actual operating conditions.

Selection of External Components

Input Pin Capacitor

In order to fully demonstrate the performance of this IC, it is recommended that the input capacitor be placed as close as possible to the input pin and the GND pin without being affected by mounting impedance, etc., and that it be laid out on the same mounting surface. In this case, a capacitor with a capacitance value of 0.1 μF (Min) or higher is recommended.

Depending on the layout of the peripheral components, including this IC, from the input power supply, if the distance from the input power supply is too far or the impedance of the input side is too high, for example, the current supply due to the load response of the IC cannot be withstood, and the output voltage may become unstable due to fluctuations in the input voltage. In such a case, it is necessary to use a large capacitor to prevent the input voltage from dropping. Select the capacitance of the input pin capacitor according to the line impedance between the power smoothing circuit and the input pin, and the load response required by the application.

In addition, the consideration should be taken as the input pin capacitor, to prevent an influence to the regulator's characteristic from the deviation or the variation of the input capacitor's characteristic. All input capacitors mentioned above are recommended to have a good DC bias characteristic and a temperature characteristic (approximately $\pm 15\%$, e.g. X7R, X8R) with being satisfied high absolute maximum voltage rating based on EIA standard.

Output Pin Capacitor

The output capacitor is mandatory for the regulator in order to realize stable operation. The output capacitor with capacitance value of 1 μF (Min) or higher and ESR up to 100 m Ω (Max) must be required between the output pin and the GND pin.

A proper selection of appropriate both the capacitance value and ESR for the output capacitor can improve the transient behavior of the regulator and can also keep the stability with better regulation loop. The correlation of the output capacitance value and ESR is shown in the graph on the next page as the **output capacitor's capacitance value and the stability region for ESR**. As described in this graph, this regulator is designed to be stable with ceramic capacitors as of MLCC, with the capacitance value from 1 μF to 500 μF and with ESR value within almost 0 Ω to 100 m Ω . The frequency range of ESR can be generally considered at around 1 MHz.

Note that the provided the stable area of the capacitance value and ESR in the graph is obtained under a specific set of conditions which is based on the measurement result in single IC on our board with a resistive load. In the actual environment, the stability is affected by wire impedance on the board, input power supply impedance and also loads impedance. Therefore, note that a careful evaluation of the actual application, the actual usage environment and the actual conditions should be done to confirm the actual stability of the system.

Generally, in the transient event which is caused by the input voltage fluctuation or the load fluctuation beyond the gain bandwidth of the regulation loop, the transient response ability of the regulator depends on the capacitance value of the output capacitor. Basically the capacitance value of 1 μF (Min) or higher for the output capacitor is recommended as shown in the table on **Output Capacitance C_{OUT} , ESR Available Area**. Using bigger capacitance value can be expected to improve better the transient response ability in a high frequency. Various types of capacitors can be used for the output capacitor with high capacity which includes electrolytic capacitor, electro-conductive polymer capacitor and tantalum capacitor. Noted that, depending on the type of capacitors, its characteristics such as ESR (≤ 100 m Ω) absolute value range, a temperature dependency of capacitance value and increased ESR at cold temperature needs to be taken into consideration. When using capacitor with large ESR (> 100 m Ω), note that ceramic capacitor with 1 μF (Min) or higher must be connected in parallel to keep stability. In this case, the total capacitance should be less than 500 μF .

In addition, the same consideration should be taken as the input pin capacitor, to prevent an influence to the regulator's characteristic from the deviation or the variation of the external capacitor's characteristic. All output capacitors mentioned above are recommended to have a good DC bias characteristic and a temperature characteristic (approximately $\pm 15\%$, e.g. X7R, X8R) with being satisfied high absolute maximum voltage rating based on EIA standard. These capacitors should be placed close to the output pin and mounted on the same board side of the regulator not to be influenced by implement impedance.

Application and Implementation – continued




Figure 55. Output Capacitance C_{OUT} , ESR Available Area
($V_{IN} = 4.5\text{ V}$ to 42 V , $V_{OUT} = 1\text{ V}$ ^(Note 1), $-40\text{ }^{\circ}\text{C} \leq T_j \leq +150\text{ }^{\circ}\text{C}$, $I_{OUT} = 0\text{ mA}$ to 500 mA)
(Note 1) The most strict condition from the stability theory for the control loop of regulator.

Typical Application

Parameter	Symbol	Reference Value for Application
Output Current Range	I_{OUT}	$I_{OUT} \leq 500\text{ mA}$
Output Capacitor	C_{OUT}	$2.2\text{ }\mu\text{F}$
Input Voltage	V_{IN}	13.5 V
Input Capacitor ^(Note 2)	C_{IN}	$1\text{ }\mu\text{F}$
Feedback Resistor ADJ vs GND ^(Note 3)	R_1	$200\text{ k}\Omega$
Feedback Resistor ADJ vs VOUT ^(Note 3)	R_2	$1338\text{ k}\Omega$

(Note 2) If the impedance, inductance of power supply line is high, please adjust input capacitor value.
To avoid any malfunctions by input voltage drop of power supply line, please consider to adjust the impedance of power supply line to small as much as possible.

(Note 3) Applicable for product with BD900M5FP-C, BD900M5WFP-C, BD900M5HFP-C, BD900M5WHFP-C, BD900M5EFJ-C, BD900M5WEFJ-C.
Place the feedback resistor close to the terminals as much as possible to avoid the effect by parasitic capacitance on the board, etc.

Application and Implementation – continued

Surge Voltage Protection for Linear Regulators

The following shows some helpful tips to protect ICs from possible inputting surge voltage which exceeds absolute maximum ratings.

Positive Surge to the Input

If there is any potential risk that positive surges higher than absolute maximum ratings, it is applied to the input, a Zener Diode should be inserted between the VIN pin and the GND to protect the device as shown in Figure 56.




Figure 56. Surges Higher than Absolute Maximum Ratings is Applied to the Input

Negative Surge to the Input

If there is any potential risk that negative surges below the absolute maximum ratings, (e.g.) -0.3 V, is applied to the input, a Schottky Diode should be inserted between the VIN and the GND to protect the device as shown in Figure 57.




Figure 57. Surges Lower than -0.3 V is Applied to the Input

Reverse Voltage Protection for Linear Regulators

A linear regulator which is one of the integrated circuit (IC) operates normally in the condition that the input voltage is higher than the output voltage. However, it is possible to happen the abnormal situation in specific conditions which is the output voltage becomes higher than the input voltage. A reverse polarity connection between the input and the output might be occurred or a certain inductor component can also cause a polarity reverse conditions. If the countermeasure is not implemented, it may cause damage to the IC. The following shows some helpful tips to protect ICs from the reverse voltage occasion.

Protection against Reverse Input/Output Voltage

In the case that MOSFET is used for the pass transistor, a parasitic body diode between the drain-source generally exists. If the output voltage becomes higher than the input voltage and if its voltage difference exceeds V_F of the body diode, a reverse current flows from the output to the input through the body diode as shown in Figure 58. The current flows in the parasitic body diode is not limited in the protection circuit because it is the parasitic element, therefore too much reverse current may cause damage to degrade or destroy the semiconductor elements of the regulator.




Figure 58. Reverse Current Path in a MOS Linear Regulator

Protection against Reverse Input/Output Voltage – continued

An effective solution for this problem is to implement an external bypass diode in order to prevent the reverse current flow inside the IC as shown in Figure 59. Especially in applications where the output voltage setting is high and a large output capacitor is connected, be sure to consider countermeasures for large reverse current values. Note that the bypass diode must be turned on prior to the internal body diode of the IC. This external bypass diode should be chosen as being lower forward voltage V_F than the internal body diode. It should be selected a diode which has a rated reverse voltage greater than the IC's input maximum voltage and also which has a rated forward current greater than the anticipated reverse current in the actual application.




Figure 59. Bypass Diode for Reverse Current Diversion

A Schottky Barrier Diode which has a characteristic of low forward voltage (V_F) can meet to the requirement for the external diode to protect the IC from the reverse current. However, it also has a characteristic that the leakage (I_R) caused by the reverse voltage is bigger than other diodes. Therefore, it should be taken into the consideration to choose it because if I_R is large, it may cause increase of the current consumption, or raise of the output voltage in the light-load current condition. I_R characteristic of Schottky Diode has positive temperature characteristic, which the details shall be checked with the datasheet of the products, and the careful confirmation of behavior in the actual application is mandatory.

Even in the condition when the input/output voltage is inverted, if the VIN pin is open as shown in Figure 60, or if the VIN pin becomes high-impedance condition as designed in the system, it cannot damage or degrade the parasitic element. It's because a reverse current via the pass transistor becomes extremely low. In this case, therefore, the protection external diode is not necessary.




Figure 60. Open VIN

Protection against Input Reverse Voltage

When the input of the IC is connected to the power supply, accidentally if plus and minus are routed in reverse, or if there is a possibility that the input may become lower than the GND pin, it may cause to destroy the IC because a large current passes via the internal electrostatic breakdown prevention diode between the VIN pin and the GND pin inside the IC as shown in Figure 61.

The simplest solution to avoid this problem is to connect a Schottky Barrier Diode or a rectifier diode in series to the power supply line as shown in Figure 62. However, it increases a power loss calculated as $V_F \times I_{CC}$, and it also causes the voltage drop by a forward voltage V_F at the supply voltage while normal operation.

Generally, since the Schottky Barrier Diode has lower V_F , so it contributes to rather smaller power loss than rectifier diodes. If IC has load currents, the required input current to the IC is also bigger. In this case, this external diode generates heat more, therefore select a diode with enough margin in power dissipation. On the other hand, a reverse current passes this diode in the reverse connection condition, however, it is negligible because its small amount.




Figure 61. Current Path in Reverse Input Connection




Figure 62. Protection against Reverse Polarity 1

Protection against Input Reverse Voltage – continued

Figure 63 shows a circuit in which a P-channel MOSFET is connected in series to the power. The body diode (parasitic element) is located in the drain-source junction area of the MOSFET. The drop voltage in a forward connection is calculated from the on state resistance of the MOSFET and the output current I_{OUT} . It is smaller than the drop voltage by the diode as shown in Figure 62 and results in less of a power loss. No current flows in a reverse connection where the MOSFET remains off in Figure 63.

If the gate-source voltage exceeds maximum rating of MOSFET gate-source junction with derating curve in consideration, reduce the gate-source junction voltage by connecting resistor voltage divider as shown in Figure 64.




Figure 63. Protection against Reverse Polarity 2




Figure 64. Protection against Reverse Polarity 3

Protection against Reverse Output Voltage when Output Connect to an Inductor

If the output load is inductive, electrical energy accumulated in the inductive load is released to the ground at the moment that the output voltage is turned off. IC integrates ESD protection diodes between the IC output and ground pins. A large current may flow in such condition finally resulting on destruction of the IC. To prevent this situation, connect a Schottky Barrier Diode in parallel to the integrated diodes as shown in Figure 65.

Further, if a long wire is in use for the connection between the output pin of the IC and the load, confirm that the negative voltage is not generated at the VOUT pin when the output voltage is turned off by observation of the waveform on an oscilloscope, since it is possible that the load becomes inductive. An additional diode is required for a motor load that is affected by its counter electromotive force, as it produces an electrical current in a similar way.





Figure 65. Current Path in Inductive Load (Output: Off)

Power Dissipation

■ TO252-3 / TO252-5



(1): 1-layer PCB

(Copper foil area on the reverse side of PCB: 0 mm x 0 mm)

Board material: FR-4

Board size: 114.3 mm x 76.2 mm x 1.57 mm

Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.

(2): 4-layer PCB

(Copper foil area on the reverse side of PCB: 74.2 mm x 74.2 mm)

Board material: FR-4

Board size: 114.3 mm x 76.2 mm x 1.60 mm

Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.

2 inner layers copper foil area of PCB:


74.2 mm x 74.2 mm, 35 μ m. copper.

Copper foil area on the reverse side of PCB:

74.2 mm x 74.2 mm, 70 μ m. copper.Condition (1) : $\theta_{JA} = 122.3$ °C/W, Ψ_{JT} (top center) = 14 °C/WCondition (2) : $\theta_{JA} = 23.0$ °C/W, Ψ_{JT} (top center) = 3 °C/W

Figure 66. Power Dissipation Graph (TO252-3 / TO252-5)

■ HRP5



(1): 1-layer PCB

(Copper foil area on the reverse side of PCB: 0 mm x 0 mm)

Board material: FR-4

Board size: 114.3 mm x 76.2 mm x 1.57 mm

Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.

(2): 4-layer PCB

(Copper foil area on the reverse side of PCB: 74.2 mm x 74.2 mm)

Board material: FR-4

Board size: 114.3 mm x 76.2 mm x 1.60 mm

Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.

2 inner layers copper foil area of PCB:


74.2 mm x 74.2 mm, 35 μ m. copper.

Copper foil area on the reverse side of PCB:

74.2 mm x 74.2 mm, 70 μ m. copper.Condition (1) : $\theta_{JA} = 91.0$ °C/W, Ψ_{JT} (top center) = 7 °C/WCondition (2) : $\theta_{JA} = 21.9$ °C/W, Ψ_{JT} (top center) = 3 °C/W

Figure 67. Power Dissipation Graph (HRP5)

Power Dissipation – continued



(1): 1-layer PCB
(Copper foil area on the reverse side of PCB: 0 mm x 0 mm)
Board material: FR-4
Board size: 114.3 mm x 76.2 mm x 1.57 mm
Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.

(2): 4-layer PCB
(Copper foil area on the reverse side of PCB: 74.2 mm x 74.2 mm)
Board material: FR-4
Board size: 114.3 mm x 76.2 mm x 1.60 mm
Top copper foil: Mounted land pattern + wiring to measure, 70 μ m. copper.
2 inner layers copper foil area of PCB:
74.2 mm x 74.2 mm, 35 μ m. copper.
Copper foil area on the reverse side of PCB:
74.2 mm x 74.2 mm, 70 μ m. copper.

Condition (1) : $\theta_{JA} = 129.0\text{ }^{\circ}\text{C/W}$, Ψ_{JT} (top center) = 10 $^{\circ}\text{C/W}$
Condition (2) : $\theta_{JA} = 26.0\text{ }^{\circ}\text{C/W}$, Ψ_{JT} (top center) = 3 $^{\circ}\text{C/W}$

Figure 68. Power Dissipation Graph (HTSOP-J8)

Thermal Design

This product exposes a frame on the back side of the package for thermal efficiency improvement. The power consumption of the IC is decided by the dropout voltage condition, the load current and the current consumption. Refer to power dissipation curves illustrated in Figure 66 to 68 when using the IC in an environment of $T_a \geq 25^\circ\text{C}$. Even if the ambient temperature T_a is at 25°C , chip junction temperature (T_j) can be very high depending on the input voltage and the load current. Consider the design to be $T_j \leq T_{j\max} = 150^\circ\text{C}$ in whole operating temperature range.

Should by any condition the maximum junction temperature $T_{j\max} = 150^\circ\text{C}$ rating be exceeded by the temperature increase of the chip, it may result in deterioration of the properties of the chip. The thermal impedance in this specification is based on recommended PCB and measurement condition by JEDEC standard. Therefore, need to be careful because it might be different from the actual use condition. Verify the application and allow sufficient margins in the thermal design by the following method to calculate the junction temperature T_j . T_j can be calculated by either of the two following methods.

1. The following method is used to calculate the junction temperature T_j with ambient temperature T_a .

$$T_j = T_a + P_C \times \theta_{JA} [^\circ\text{C}]$$

Where:

T_j is the Junction Temperature
 T_a is the Ambient Temperature
 P_C is the Power Consumption
 θ_{JA} is the Thermal Resistance (Junction to Ambient)

2. The following method is also used to calculate the junction temperature T_j with top center of case's (mold) temperature T_T .

$$T_j = T_T + P_C \times \Psi_{JT} [^\circ\text{C}]$$

Where:

T_j is the Junction Temperature
 T_T is the Top Center of Case's (mold) Temperature
 P_C is the Power Consumption
 Ψ_{JT} is the Thermal Resistance (Junction to Top Center of Case)

3. The following method is used to calculate the power consumption P_C (W).

$$P_C = (V_{IN} - V_{OUT}) \times I_{OUT} + V_{IN} \times I_{CC} [\text{W}]$$

Where:

P_C is the Power Consumption
 V_{IN} is the Input Voltage
 V_{OUT} is the Output Voltage
 I_{OUT} is the Load Current
 I_{CC} is the Current Consumption

Thermal Design – continued

Calculation Example (HTSOP-J8)

If $V_{IN} = 13.5\text{ V}$, $V_{OUT} = 5.0\text{ V}$, $I_{OUT} = 200\text{ mA}$, $I_{CC} = 170\text{ }\mu\text{A}$, the power consumption P_C can be calculated as follows:

$$\begin{aligned} P_C &= (V_{IN} - V_{OUT}) \times I_{OUT} + V_{IN} \times I_{CC} \\ &= (13.5\text{ V} - 5.0\text{ V}) \times 200\text{ mA} + 13.5\text{ V} \times 170\text{ }\mu\text{A} \\ &= 1.7\text{ W} \end{aligned}$$

At the ambient temperature $T_a = 85\text{ }^\circ\text{C}$,
the thermal impedance (Junction to Ambient) $\theta_{JA} = 26.0\text{ }^\circ\text{C/W}$ (4-layer PCB)


$$\begin{aligned} T_J &= T_a + P_C \times \theta_{JA} \\ &= 85\text{ }^\circ\text{C} + 1.7\text{ W} \times 26.0\text{ }^\circ\text{C/W} \\ &= 129.2\text{ }^\circ\text{C} \end{aligned}$$

When operating the IC, the top center of case's (mold) temperature $T_T = 100\text{ }^\circ\text{C}$,
the Thermal Resistance (Junction to Top Center of Case) $\Psi_{JT} = 10\text{ }^\circ\text{C/W}$ (1-layer PCB)

$$\begin{aligned} T_J &= T_T + P_C \times \Psi_{JT} \\ &= 100\text{ }^\circ\text{C} + 1.7\text{ W} \times 10\text{ }^\circ\text{C/W} \\ &= 117.0\text{ }^\circ\text{C} \end{aligned}$$


If it is difficult to ensure the margin by the calculations above, it is recommended to expand the copper foil area of the board, increasing the layer and thermal via between thermal land pad for optimum thermal performance.

I/O Equivalence Circuit



(Note 1) Applicable for product with BD9xxM5FP-C, BD9xxM5WFP-C, BD9xxM5HFP-C, BD9xxM5WHFP-C, BD9xxM5EFJ-C, BD9xxM5WEFJ-C (xx = 33, 50).
(Note 2) Applicable for product with BD900M5FP-C, BD900M5WFP-C, BD900M5HFP-C, BD900M5WHFP-C, BD900M5EFJ-C, BD900M5WEFJ-C.

I/O Equivalence Circuit – continued



(Note 3) Applicable for product with BD9xxM5WFP-C, BD9xxM5WHFP-C, BD9xxM5WEFJ-C (xx = 33, 50, 00).

Operational Notes

1. Reverse Connection of Power Supply

Connecting the power supply in reverse polarity can damage the IC. Take precautions against reverse polarity when connecting the power supply, such as mounting an external diode between the power supply and the IC's power supply pins.

2. Power Supply Lines

Design the PCB layout pattern to provide low impedance supply lines. Furthermore, connect a capacitor to ground at all power supply pins. Consider the effect of temperature and aging on the capacitance value when using electrolytic capacitors.

3. Ground Voltage

Ensure that no pins are at a voltage below that of the ground pin at any time, even during transient condition.

4. Ground Wiring Pattern

When using both small-signal and large-current ground traces, the two ground traces should be routed separately but connected to a single ground at the reference point of the application board to avoid fluctuations in the small-signal ground caused by large currents. Also ensure that the ground traces of external components do not cause variations on the ground voltage. The ground lines must be as short and thick as possible to reduce line impedance.

5. Operating Conditions

The function and operation of the IC are guaranteed within the range specified by the recommended operating conditions. The characteristic values are guaranteed only under the conditions of each item specified by the electrical characteristics.

6. Inrush Current

When power is first supplied to the IC, it is possible that the internal logic may be unstable and inrush current may flow instantaneously due to the internal powering sequence and delays, especially if the IC has more than one power supply. Therefore, give special consideration to power coupling capacitance, power wiring, width of ground wiring, and routing of connections.

7. Thermal Consideration

The power dissipation under actual operating conditions should be taken into consideration and a sufficient margin should be allowed in the thermal design. On the reverse side of the package this product has an exposed heat pad for improving the heat dissipation. The amount of heat generation depends on the voltage difference between the input and output, load current, and bias current. Therefore, when actually using the chip, ensure that the generated heat does not exceed the Pd rating. If Junction temperature is over Tjmax (= 150 °C), IC characteristics may be worse due to rising chip temperature. Heat resistance in specification is measurement under PCB condition and environment recommended in JEDEC. Ensure that heat resistance in specification is different from actual environment.

8. Testing on Application Boards

When testing the IC on an application board, connecting a capacitor directly to a low-impedance output pin may subject the IC to stress. Always discharge capacitors completely after each process or step. The IC's power supply should always be turned off completely before connecting or removing it from the test setup during the inspection process. To prevent damage from static discharge, ground the IC during assembly and use similar precautions during transport and storage.

9. Inter-pin Short and Mounting Errors

Ensure that the direction and position are correct when mounting the IC on the PCB. Incorrect mounting may result in damaging the IC. Avoid nearby pins being shorted to each other especially to ground, power supply and output pin. Inter-pin shorts could be due to many reasons such as metal particles, water droplets (in very humid environment) and unintentional solder bridge deposited in between pins during assembly to name a few.

10. Unused Input Pins

Input pins of an IC are often connected to the gate of a MOS transistor. The gate has extremely high impedance and extremely low capacitance. If left unconnected, the electric field from the outside can easily charge it. The small charge acquired in this way is enough to produce a significant effect on the conduction through the transistor and cause unexpected operation of the IC. So unless otherwise specified, unused input pins should be connected to the power supply or ground line.

Operational Notes – continued

11. Regarding the Input Pin of the IC

This monolithic IC contains P+ isolation and P substrate layers between adjacent elements in order to keep them isolated. P-N junctions are formed at the intersection of the P layers with the N layers of other elements, creating a parasitic diode or transistor. For example, (refer to figure below):

When $GND > Pin\ A$ and $GND > Pin\ B$, the P-N junction operates as a parasitic diode.

When $GND > Pin\ B$, the P-N junction operates as a parasitic transistor.

Parasitic diodes inevitably occur in the structure of the IC. The operation of parasitic diodes can result in mutual interference among circuits, operational faults, or physical damage. Therefore, conditions that cause these diodes to operate, such as applying a voltage lower than the GND voltage to an input pin (and thus to the P substrate) should be avoided.




Figure 69. Example of Monolithic IC Structure

12. Ceramic Capacitor

When using a ceramic capacitor, determine a capacitance value considering the change of capacitance with temperature and the decrease in nominal capacitance due to DC bias and others.

13. Thermal Shutdown Protection Circuit (TSD)

This IC has a built-in thermal shutdown circuit that prevents heat damage to the IC. Normal operation should always be within the IC's maximum junction temperature rating. If however the rating is exceeded for a continued period, the junction temperature (T_j) will rise which will activate the TSD circuit that will turn OFF power output pins. When the T_j falls below the TSD threshold, the circuits are automatically restored to normal operation.

Note that the TSD circuit operates in a situation that exceeds the absolute maximum ratings and therefore, under no circumstances, should the TSD circuit be used in a set design or for any purpose other than protecting the IC from heat damage.

14. Over Current Protection Circuit (OCP)

This IC incorporates an integrated overcurrent protection circuit that is activated when the load is shorted. This protection circuit is effective in preventing damage due to sudden and unexpected incidents. However, the IC should not be used in applications characterized by continuous operation or transitioning of the protection circuit.

15. Functional Safety

"ISO 26262 Process Compliant to Support ASIL-*)"

A product that has been developed based on an ISO 26262 design process compliant to the ASIL level described in the datasheet.

"Safety Mechanism is Implemented to Support Functional Safety (ASIL-*)"

A product that has implemented safety mechanism to meet ASIL level requirements described in the datasheet.

"Functional Safety Supportive Automotive Products"

A product that has been developed for automotive use and is capable of supporting safety analysis with regard to the functional safety.

Note: "ASIL-*)" is stands for the ratings of "ASIL-A", "-B", "-C" or "-D" specified by each product's datasheet.

Ordering Information


B D 9 x x M 5 W x x x - C x x											
Output Voltage 33: 3.3 V 50: 5.0 V 00: Adjustable			Output Current Capability 5: 500 mA		Output shutdown Function None: Without Output shutdown Function W : Output shutdown Function			Package FP: TO252-3 : TO252-5 HFP: HRP5 EFJ: HTSOP-J8		Product Rank C: for Automotive Packaging and Forming Specification E2: Embossed Tape and Reel TR: Embossed Tape and Reel	

Lineup

Output Current Capability	Output Voltage	Output shut-down Function	Package	Ordering
500 mA	3.3 V	not available	TO252-3	BD933M5FP-CE2
			HRP5	BD933M5HFP-CTR
			HTSOP-J8	BD933M5EFJ-CE2
		available	TO252-5	BD933M5WFP-CE2
			HRP5	BD933M5WHFP-CTR
			HTSOP-J8	BD933M5WEFJ-CE2
	5.0 V	not available	TO252-3	BD950M5FP-CE2
			HRP5	BD950M5HFP-CTR
			HTSOP-J8	BD950M5EFJ-CE2
		available	TO252-5	BD950M5WFP-CE2
			HRP5	BD950M5WHFP-CTR
			HTSOP-J8	BD950M5WEFJ-CE2
	Adjustable	not available	TO252-5	BD900M5FP-CE2
			HRP5	BD900M5HFP-CTR
			HTSOP-J8	BD900M5EFJ-CE2
		available	TO252-5	BD900M5WFP-CE2
			HRP5	BD900M5WHFP-CTR
			HTSOP-J8	BD900M5WEFJ-CE2


Marking Diagrams

TO252-3(TOP VIEW)




Part Number	Part Number Marking	Output Voltage [V]	Output shutdown Function ^(Note 1)
BD933M5FP-CE2	D933M5	3.3	not available
BD950M5FP-CE2	D950M5	5.0	not available

TO252-5(TOP VIEW)



Part Number	Part Number Marking	Output Voltage [V]	Output shutdown Function ^(Note 1)
BD933M5WFP-CE2	D933M5W	3.3	available
BD950M5WFP-CE2	D950M5W	5.0	available
BD900M5FP-CE2	D900M5	Adjustable	not available
BD900M5WFP-CE2	D900M5W	Adjustable	available


HRP5 (TOP VIEW)



Part Number	Part Number Marking	Output Voltage [V]	Output shutdown Function ^(Note 1)
BD933M5HFP-CTR	BD933M5	3.3	not available
BD950M5HFP-CTR	BD950M5	5.0	not available
BD900M5HFP-CTR	BD900M5	Adjustable	not available
BD933M5WHFP-CTR	BD933M5W	3.3	available
BD950M5WHFP-CTR	BD950M5W	5.0	available
BD900M5WHFP-CTR	BD900M5W	Adjustable	available

Marking Diagrams – continued

HTSOP-J8(TOP VIEW)




Part Number	Part Number Marking	Output Voltage [V]	Output shutdown Function ^(Note 1)
BD933M5EFJ-CE2	933M5	3.3	not available
BD950M5EFJ-CE2	950M5	5.0	not available
BD900M5EFJ-CE2	900M5	Adjustable	not available
BD933M5WEFJ-CE2	933M5W	3.3	available
BD950M5WEFJ-CE2	950M5W	5.0	available
BD900M5WEFJ-CE2	900M5W	Adjustable	available

(Note 1) available: With Enable Input
not available: Without Enable Input

Physical Dimension and Packing Information


Package Name	TO252-3
--------------	---------



(UNITS ; mm)
PKG : TO252-3
Drawing No. EX535-5001-1


< Tape and Reel Information >

Tape	Embossed carrier tape
Quantity	2000pcs
Direction of feed	E2



Physical Dimension and Packing Information – continued


Package Name	TO252-5
--------------	---------



(UNIT : mm)
PKG : TO252-5
Drawing No. EX536-5001-1

< Tape and Reel Information >




Tape	Embossed carrier tape
Quantity	2000pcs
Direction of feed	E2



Physical Dimension and Packing Information – continued

Package Name

HRP5




(UNIT ; mm)

PKG : HRP5

Drawing No. EX541-5002-2

< Tape and Reel Information >

Tape	Embossed carrier tape
Quantity	2000pcs
Direction of feed	TR The direction is the pin 1 of product is at the upper right when you hold reel on the left hand and you pull out the tape on the right hand



Package Name

HTSOP-J8

Top View Dimensions:

- Overall Width: 4.9 ± 0.1 (Max 5.25 include BURR)
- Pin Pitch: 0.545
- Pin 1 Mark: Indicated by a circle and dashed line.
- Pin Numbers: 1, 2, 3, 4 (bottom); 5, 6, 7, 8 (top)
- Internal Dimensions: 3.9 ± 0.1 , 2.4

Side View Dimensions:

- Overall Height: 6.0 ± 0.2
- Pin Height: 0.65 ± 0.15
- Pin Thickness: $0.17^{+0.05}_{-0.03}$
- Lead Angle: $4^{\circ} + 6^{\circ} / - 4^{\circ}$

Detail View Dimensions:

- Pin Thickness: 0.08 ± 0.05
- Pin Spacing: 1.27
- Pin Width: $0.42^{+0.05}_{-0.04}$
- Pin Position: 0.08 ± 0.04
- Pin Mark: 0.08 ± 0.04

(UNIT : mm)

PKG : HTSOP-J8

Drawing No. EX169-5002-2

<Tape and Reel information>	
Tape	Embossed carrier tape
Quantity	2500pcs
Direction of feed	E2 (The direction is the 1pin of product is at the upper left when you hold reel on the left hand and you pull out the tape on the right hand)

Diagram illustrating the carrier tape layout and direction of feed. The tape is shown with multiple pockets, each containing two components (E2 and TR). The direction of feed is indicated by an arrow pointing right. The layout shows the sequence of components (E2, TR) and the direction of feed (TL, E1).

Reel

Pocket Quadrants

Direction of feed

Revision History

Date	Revision	Changes
20.Jan.2023	001	New Release
24.Dec.2023	002	Add Package of TO252-3, TO252-5 and HRP5.

Notice

Precaution on using ROHM Products

1. If you intend to use our Products in devices requiring extremely high reliability (such as medical equipment ^(Note 1), aircraft/spacecraft, nuclear power controllers, etc.) and whose malfunction or failure may cause loss of human life, bodily injury or serious damage to property ("Specific Applications"), please consult with the ROHM sales representative in advance. Unless otherwise agreed in writing by ROHM in advance, ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of any ROHM's Products for Specific Applications.

(Note1) Medical Equipment Classification of the Specific Applications

JAPAN	USA	EU	CHINA
CLASS III	CLASS III	CLASS II b	CLASS III
CLASS IV		CLASS III	

2. ROHM designs and manufactures its Products subject to strict quality control system. However, semiconductor products can fail or malfunction at a certain rate. Please be sure to implement, at your own responsibilities, adequate safety measures including but not limited to fail-safe design against the physical injury, damage to any property, which a failure or malfunction of our Products may cause. The following are examples of safety measures:
 - [a] Installation of protection circuits or other protective devices to improve system safety
 - [b] Installation of redundant circuits to reduce the impact of single or multiple circuit failure
3. Our Products are not designed under any special or extraordinary environments or conditions, as exemplified below. Accordingly, ROHM shall not be in any way responsible or liable for any damages, expenses or losses arising from the use of any ROHM's Products under any special or extraordinary environments or conditions. If you intend to use our Products under any special or extraordinary environments or conditions (as exemplified below), your independent verification and confirmation of product performance, reliability, etc, prior to use, must be necessary:
 - [a] Use of our Products in any types of liquid, including water, oils, chemicals, and organic solvents
 - [b] Use of our Products outdoors or in places where the Products are exposed to direct sunlight or dust
 - [c] Use of our Products in places where the Products are exposed to sea wind or corrosive gases, including Cl₂, H₂S, NH₃, SO₂, and NO₂
 - [d] Use of our Products in places where the Products are exposed to static electricity or electromagnetic waves
 - [e] Use of our Products in proximity to heat-producing components, plastic cords, or other flammable items
 - [f] Sealing or coating our Products with resin or other coating materials
 - [g] Use of our Products without cleaning residue of flux (Exclude cases where no-clean type fluxes is used. However, recommend sufficiently about the residue.); or Washing our Products by using water or water-soluble cleaning agents for cleaning residue after soldering
 - [h] Use of the Products in places subject to dew condensation
4. The Products are not subject to radiation-proof design.
5. Please verify and confirm characteristics of the final or mounted products in using the Products.
6. In particular, if a transient load (a large amount of load applied in a short period of time, such as pulse, is applied, confirmation of performance characteristics after on-board mounting is strongly recommended. Avoid applying power exceeding normal rated power; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.
7. De-rate Power Dissipation depending on ambient temperature. When used in sealed area, confirm that it is the use in the range that does not exceed the maximum junction temperature.
8. Confirm that operation temperature is within the specified range described in the product specification.
9. ROHM shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.

Precaution for Mounting / Circuit board design

1. When a highly active halogenous (chlorine, bromine, etc.) flux is used, the residue of flux may negatively affect product performance and reliability.
2. In principle, the reflow soldering method must be used on a surface-mount products, the flow soldering method must be used on a through hole mount products. If the flow soldering method is preferred on a surface-mount products, please consult with the ROHM representative in advance.

For details, please refer to ROHM Mounting specification

Precautions Regarding Application Examples and External Circuits

1. If change is made to the constant of an external circuit, please allow a sufficient margin considering variations of the characteristics of the Products and external components, including transient characteristics, as well as static characteristics.
2. You agree that application notes, reference designs, and associated data and information contained in this document are presented only as guidance for Products use. Therefore, in case you use such information, you are solely responsible for it and you must exercise your own independent verification and judgment in the use of such information contained in this document. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of such information.

Precaution for Electrostatic

This Product is electrostatic sensitive product, which may be damaged due to electrostatic discharge. Please take proper caution in your manufacturing process and storage so that voltage exceeding the Products maximum rating will not be applied to Products. Please take special care under dry condition (e.g. Grounding of human body / equipment / solder iron, isolation from charged objects, setting of ionizer, friction prevention and temperature / humidity control).

Precaution for Storage / Transportation

1. Product performance and soldered connections may deteriorate if the Products are stored in the places where:
 - [a] the Products are exposed to sea winds or corrosive gases, including Cl₂, H₂S, NH₃, SO₂, and NO₂
 - [b] the temperature or humidity exceeds those recommended by ROHM
 - [c] the Products are exposed to direct sunshine or condensation
 - [d] the Products are exposed to high Electrostatic
2. Even under ROHM recommended storage condition, solderability of products out of recommended storage time period may be degraded. It is strongly recommended to confirm solderability before using Products of which storage time is exceeding the recommended storage time period.
3. Store / transport cartons in the correct direction, which is indicated on a carton with a symbol. Otherwise bent leads may occur due to excessive stress applied when dropping of a carton.
4. Use Products within the specified time after opening a humidity barrier bag. Baking is required before using Products of which storage time is exceeding the recommended storage time period.

Precaution for Product Label

A two-dimensional barcode printed on ROHM Products label is for ROHM's internal use only.

Precaution for Disposition

When disposing Products please dispose them properly using an authorized industry waste company.

Precaution for Foreign Exchange and Foreign Trade act

Since concerned goods might be fallen under listed items of export control prescribed by Foreign exchange and Foreign trade act, please consult with ROHM in case of export.

Precaution Regarding Intellectual Property Rights

1. All information and data including but not limited to application example contained in this document is for reference only. ROHM does not warrant that foregoing information or data will not infringe any intellectual property rights or any other rights of any third party regarding such information or data.
2. ROHM shall not have any obligations where the claims, actions or demands arising from the combination of the Products with other articles such as components, circuits, systems or external equipment (including software).
3. No license, expressly or implied, is granted hereby under any intellectual property rights or other rights of ROHM or any third parties with respect to the Products or the information contained in this document. Provided, however, that ROHM will not assert its intellectual property rights or other rights against you or your customers to the extent necessary to manufacture or sell products containing the Products, subject to the terms and conditions herein.

Other Precaution

1. This document may not be reprinted or reproduced, in whole or in part, without prior written consent of ROHM.
2. The Products may not be disassembled, converted, modified, reproduced or otherwise changed without prior written consent of ROHM.
3. In no event shall you use in any way whatsoever the Products and the related technical information contained in the Products or this document for any military purposes, including but not limited to, the development of mass-destruction weapons.
4. The proper names of companies or products described in this document are trademarks or registered trademarks of ROHM, its affiliated companies or third parties.

General Precaution

1. Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.
2. All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.
3. The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.