



WLD4FP-31312130ZZZ  
W4

MINIATURE PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



Ordering information

| Type               | Part no. |
|--------------------|----------|
| WLD4FP-31312130ZZZ | 1113195  |

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

Detailed technical data

Features

|                                    |                                                                                                 |                                                       |
|------------------------------------|-------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| <b>Functional principle</b>        |                                                                                                 | Photoelectric retro-reflective sensor                 |
| <b>Functional principle detail</b> |                                                                                                 | With minimum distance to reflector (dual lens system) |
| <b>Sensing range</b>               |                                                                                                 |                                                       |
|                                    | Sensing range min.                                                                              | 0 m                                                   |
|                                    | Sensing range max.                                                                              | 4.5 m                                                 |
|                                    | Maximum distance range from reflector to sensor (operating reserve 1)                           | 0.015 m ... 4.5 m                                     |
|                                    | Recommended distance range from reflector to sensor (operating reserve 3,75)                    | 0.035 m ... 3.9 m                                     |
|                                    | Reference reflector                                                                             | Reflector P250                                        |
|                                    | Recommended sensing range for the best performance                                              | 0.035 m ... 3.9 m                                     |
| <b>Polarisation filters</b>        |                                                                                                 | Yes                                                   |
| <b>Emitted beam</b>                |                                                                                                 |                                                       |
|                                    | Light source                                                                                    | PinPoint LED                                          |
|                                    | Type of light                                                                                   | Visible red light                                     |
|                                    | Shape of light spot                                                                             | Point-shaped                                          |
|                                    | Light spot size (distance)                                                                      | Ø 38 mm (1,000 mm)                                    |
|                                    | Maximum dispersion of the emitted beam around the standardized transmission axis (squint angle) | < +/- 1.5° (at Ta = +23 °C)                           |
| <b>Key LED figures</b>             |                                                                                                 |                                                       |

|                        |                                                                                                                                          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Normative reference    | EN 62471:2008-09   IEC 62471:2006, modified                                                                                              |
| LED risk group marking | Free group                                                                                                                               |
| Wave length            | 635 nm                                                                                                                                   |
| Average service life   | 100,000 h at $T_a = +25\text{ °C}$                                                                                                       |
| <b>Adjustment</b>      |                                                                                                                                          |
| Teach-in button        | BluePilot: for sensitivity adjustment                                                                                                    |
| <b>Display</b>         |                                                                                                                                          |
| LED blue               | BluePilot: Alignment aid                                                                                                                 |
| LED green              | Operating indicator<br>Static on: power on                                                                                               |
| LED yellow             | Status of received light beam<br>Static on: object not present<br>Static off: object present<br>Flashing: Below the 1.5 function reserve |

### Safety-related parameters

|                                     |                                              |
|-------------------------------------|----------------------------------------------|
| <b>MTTF<sub>D</sub></b>             | 747 years                                    |
| <b>DC<sub>avg</sub></b>             | 0 %                                          |
| <b>T<sub>M</sub> (mission time)</b> | 20 years (EN ISO 13849)<br>Rate of use: 60 % |

### Electronics

|                                     |                                                                                |
|-------------------------------------|--------------------------------------------------------------------------------|
| <b>Supply voltage U<sub>B</sub></b> | 10 V DC ... 30 V DC <sup>1)</sup>                                              |
| <b>Ripple</b>                       | ≤ 5 V <sub>pp</sub>                                                            |
| <b>Usage category</b>               | DC-12 (According to EN 60947-5-2)<br>DC-13 (According to EN 60947-5-2)         |
| <b>Current consumption</b>          | ≤ 20 mA, without load. At U <sub>B</sub> = 24 V                                |
| <b>Protection class</b>             | III                                                                            |
| <b>Digital output</b>               |                                                                                |
| Number                              | 1                                                                              |
| Type                                | Push-pull: PNP/NPN                                                             |
| Switching mode                      | Light switching                                                                |
| Signal voltage PNP HIGH/LOW         | Approx. U <sub>B</sub> -2.5 V / 0 V                                            |
| Signal voltage NPN HIGH/LOW         | Approx. U <sub>B</sub> / < 2.5 V                                               |
| Output current I <sub>max.</sub>    | ≤ 100 mA                                                                       |
| Circuit protection outputs          | Reverse polarity protected<br>Overcurrent protected<br>Short-circuit protected |
| Response time                       | ≤ 500 μs                                                                       |
| Repeatability (response time)       | 150 μs <sup>2)</sup>                                                           |
| Switching frequency                 | 1,000 Hz <sup>3)</sup>                                                         |
| <b>Pin/Wire assignment</b>          |                                                                                |
| Function of pin 4/black (BK)        | Digital output, light switching, object present → output Q LOW <sup>4)</sup>   |

<sup>1)</sup> Limit values.

<sup>2)</sup> Signal transit time with resistive load in switching mode.

<sup>3)</sup> With light/dark ratio 1:1.

<sup>4)</sup> This switching output must not be connected to another output.

Mechanics

|                                                       |                                        |
|-------------------------------------------------------|----------------------------------------|
| <b>Housing</b>                                        | Rectangular                            |
| <b>Design detail</b>                                  | Flat                                   |
| <b>Dimensions (W x H x D)</b>                         | 16 mm x 40.1 mm x 12.1 mm              |
| <b>Connection</b>                                     | Cable with connector M8, 3-pin, 110 mm |
| <b>Connection detail</b>                              |                                        |
| Deep-freeze property                                  | Do not bend below 0 °C                 |
| Conductor size                                        | 0.14 mm <sup>2</sup>                   |
| Cable diameter                                        | Ø 3.4 mm                               |
| Length of cable (L)                                   | 77 mm                                  |
| <b>Material</b>                                       |                                        |
| Housing                                               | Plastic, VISTAL®                       |
| Front screen                                          | Plastic, PMMA                          |
| Cable                                                 | Plastic, PVC                           |
| Male connector                                        | Plastic, VISTAL®                       |
| <b>Weight</b>                                         | Approx. 30 g                           |
| <b>Maximum tightening torque of the fixing screws</b> | 0.4 Nm                                 |

Ambient data


|                                            |                                                                                                   |
|--------------------------------------------|---------------------------------------------------------------------------------------------------|
| <b>Enclosure rating</b>                    | IP66 (EN 60529)<br>IP67 (EN 60529)                                                                |
| <b>Ambient operating temperature</b>       | -40 °C ... +60 °C                                                                                 |
| <b>Ambient temperature, storage</b>        | -40 °C ... +75 °C                                                                                 |
| <b>Typ. Ambient light immunity</b>         | Artificial light: ≤ 50,000 lx<br>Sunlight: ≤ 50,000 lx                                            |
| <b>Shock resistance</b>                    | 30 g, 11 ms (3 positive and 3 negative shocks along X, Y, Z axes, 18 total shocks (EN60068-2-27)) |
| <b>Vibration resistance</b>                | 10 Hz ... 1,000 Hz (Amplitude 1 mm, 3 x 30 min (EN60068-2-6))                                     |
| <b>Air humidity</b>                        | 35 % ... 95 %, relative humidity (no condensation)                                                |
| <b>Electromagnetic compatibility (EMC)</b> | EN 60947-5-2                                                                                      |
| <b>Resistance to cleaning agent</b>        | ECOLAB                                                                                            |
| <b>UL File No.</b>                         | NRKH.E181493 & NRKH7.E181493                                                                      |

Classifications


|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270902 |
| <b>ECLASS 5.1.4</b> | 27270902 |
| <b>ECLASS 6.0</b>   | 27270902 |
| <b>ECLASS 6.2</b>   | 27270902 |
| <b>ECLASS 7.0</b>   | 27270902 |
| <b>ECLASS 8.0</b>   | 27270902 |
| <b>ECLASS 8.1</b>   | 27270902 |
| <b>ECLASS 9.0</b>   | 27270902 |
| <b>ECLASS 10.0</b>  | 27270902 |
| <b>ECLASS 11.0</b>  | 27270902 |

|                |          |
|----------------|----------|
| ECLASS 12.0    | 27270904 |
| ETIM 5.0       | EC002717 |
| ETIM 6.0       | EC002717 |
| ETIM 7.0       | EC002717 |
| ETIM 8.0       | EC002717 |
| UNSPSC 16.0901 | 39121528 |


Adjustments





Connection type





Connection diagram




Truth table


|                         | Light switching $Q$ (normally closed (upper switch), normally open (lower switch)) |                                                                                     |
|-------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                         | Object not present → Output HIGH                                                   | Object present → Output LOW                                                         |
| Light receive           | ✓                                                                                  | ✗                                                                                   |
| Light receive indicator | ☀                                                                                  | ✗                                                                                   |
| Load resistance to L+   | ✗                                                                                  | ⚡                                                                                   |
| Load resistance to M    | ⚡                                                                                  | ✗                                                                                   |
|                         |  |  |

|                         | Dark switching $\bar{Q}$ (normally open (upper switch), normally closed (lower switch)) |                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                         | Object not present → Output LOW                                                         | Object present → Output HIGH                                                          |
| Light receive           | ✓                                                                                       | ✗                                                                                     |
| Light receive indicator | ☀                                                                                       | ✗                                                                                     |
| Load resistance to L+   | ⚡                                                                                       | ✗                                                                                     |
| Load resistance to M    | ✗                                                                                       | ⚡                                                                                     |
|                         |     |  |



Characteristic curve




Recommended sensing range for the best performance



Recommended sensing range for the best performance




Light spot size




Recommended sensing range for the best performance

Sensing range diagram




A = Sensing range min. in m  
B = Sensing range max. in m  
C = Maximum distance range from reflector to sensor (operating reserve 1)  
D = Recommended distance range from reflector to sensor (operating reserve 3.75)

Recommended sensing range for the best performance




A = Sensing range min. in m  
 B = Sensing range max. in m  
 C = Maximum distance range from reflector to sensor (operating reserve 1)  
 D = Recommended distance range from reflector to sensor (operating reserve 3.75)

Recommended sensing range for the best performance



A = Sensing range min. in m  
 B = Sensing range max. in m  
 C = Maximum distance range from reflector to sensor (operating reserve 1)  
 D = Recommended distance range from reflector to sensor (operating reserve 3.75)


Recommended sensing range for the best performance



A = Sensing range min. in m  
 B = Sensing range max. in m  
 C = Maximum distance range from reflector to sensor (operating reserve 1)  
 D = Recommended distance range from reflector to sensor (operating reserve 3.75)

Recommended sensing range for the best performance

### Dimensional drawing (Dimensions in mm (inch))



## Recommended accessories

Other models and accessories → [www.sick.com/W4](http://www.sick.com/W4)

|                                                                                     | Brief description                                                                                                                                                                                                                                                                                                   | Type     | Part no. |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------|
| Mounting brackets and plates                                                        |                                                                                                                                                                                                                                                                                                                     |          |          |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Mounting bracket for wall mounting</li> <li>• <b>Material:</b> Stainless steel</li> <li>• <b>Details:</b> Stainless steel 1.4571</li> <li>• <b>Items supplied:</b> Mounting hardware included</li> <li>• <b>Suitable for:</b> W4S, W4F, W4S</li> </ul> | BEF-W4-A | 2051628  |
| Others                                                                              |                                                                                                                                                                                                                                                                                                                     |          |          |
|  | <ul style="list-style-type: none"> <li>• <b>Description:</b> Fine triple reflector, screw connection, suitable for laser sensors</li> <li>• <b>Dimensions:</b> 20 mm 32 mm</li> <li>• <b>Ambient operating temperature:</b> -30 °C ... +65 °C</li> </ul>                                                            | PL10F    | 5311210  |

|                                                                                   | Brief description                                                                                                                                                                                                                                                                                                                                                                                                           | Type               | Part no. |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Female connector, M8, 3-pin, straight, A-coded</li><li>• <b>Connection type head B:</b> Flying leads</li><li>• <b>Signal type:</b> Sensor/actuator cable</li><li>• <b>Cable:</b> 5 m, 3-wire, PVC</li><li>• <b>Description:</b> Sensor/actuator cable, unshielded</li><li>• <b>Application:</b> Zones with chemicals, Uncontaminated zones</li></ul> | YF8U13-050VA1XLEAX | 2095884  |
|  | <ul style="list-style-type: none"><li>• <b>Connection type head A:</b> Male connector, M8, 3-pin, straight, A-coded</li><li>• <b>Description:</b> Unshielded</li><li>• <b>Connection systems:</b> Screw-type terminals</li><li>• <b>Permitted cross-section:</b> 0.14 mm² ... 0.5 mm²</li></ul>                                                                                                                             | STE-0803-G         | 6037322  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)