


magnetic coil 230 V AC, 50/60 Hz, for contactors 3RT2.4...A



product brand name	SIRIUS
product category	Solenoid coils
product designation	Magnet coil
product type designation	3RT29

General technical data

Substance Prohibition (Date)	10/01/2014
Weight	0.166 kg
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC - at 50 Hz rated value - at 60 Hz rated value	230 V 230 V
control supply voltage frequency 1 rated value 2 rated value	50 Hz 60 Hz
operating range factor control supply voltage rated value of magnet coil at AC - at 50 Hz - at 60 Hz	0.8 ... 1.1 0.85 ... 1.1
apparent pick-up power of magnet coil at AC - at 50 Hz - at 60 Hz	348 VA 296 VA
inductive power factor with closing power of the coil - at 50 Hz - at 60 Hz	0.62 0.55
apparent holding power of magnet coil at AC - at 50 Hz - at 60 Hz	25 VA 18 VA
inductive power factor with the holding power of the coil - at 50 Hz - at 60 Hz	0.35 0.41

Approvals Certificates

General Product Approval	EMV	Maritime application
--------------------------	-----	----------------------



other	Environment
-------	-------------



[Confirmation](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2944-5AL21>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2944-5AL21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2944-5AL21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2944-5AL21&lang=en

last modified:

4/2/2025 