

TeSys LE - enclosed DOL starter - 40 A - 230 V AC coil

Local distributor code:

398264477 LE1D40AP7

EAN Code: 3606480452611

Main

Range	TeSys	
product name	TeSys LE	
Device short name	LE1D	
Product or component type	Enclosed DOL starter	
Device application	Standard	
Utilisation category	AC-3	
Device composition	Thermal overload relay ordered separately Contactor	
Control type	Push-button start green I	

Complementary

Motor power kW	11 kW at 220/230 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 22 kW at 440 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 30 kW at 660/690 V AC 50/60 Hz 18.5 kW at 380/400 V AC 50/60 Hz	
[Ith] Conventional free air thermal current	40 A	
[Uc] control circuit voltage	230 V AC 50/60 Hz	
Cable entry number	1 ISO32 top 3 1 ISO20 + 2 ISO32 bottom	
Width	200 mm	
Height	300 mm	
Depth	158.4 mm	
Net weight	4.82 kg	

Environment

Material	Sheet steel	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK09 conforming to IEC 60529	
Standards	IEC 60947-4-1	
Ambient air temperature for operation	-540 °C	
Product certifications	UKCA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	32.000 cm
Package 1 Length	41.000 cm
Package 1 Weight	5.018 kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	33.072 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	107
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins