



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER

Product code : CREM SIR1 SNPBAG.

Solder paste type : SIRIUS 1

Alloy type : Sn62Pb36Ag2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Soft soldering

Use descriptor system (REACH) :

SU 3 Industrial uses : uses of substances as such or in preparations at industrial sites

PC 38 Welding and soldering products (with flux coatings or flux cores), flux products

1.3. Details of the supplier of the safety data sheet

Registered company name : MBO.

Address : Rue de la Fonderie.21800.Chevigny-Saint-Sauveur.FRANCE.

Telephone : 00 33 3 80 46 12 58. Fax : 00 33 3 80 46 66 59.

admin@mbosolder.com

www.mbosolder.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Reproductive toxicity, Category 1A (Repr. 1A, H360).

Specific target organ toxicity (repeated exposure), Category 1 (STOT RE 1, H372).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS08

Signal Word :

DANGER

Product identifiers :

EC 231-100-4 LEAD

Additional labeling :

For professional use only.

Hazard statements :

H360FD

May damage fertility. May damage the unborn child.

H372

Causes damage to organs through prolonged or repeated exposure (if inhaled, if swallowed).

**SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG**

Precautionary statements - Prevention :

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

It is recommended to wear safety glasses, protective gloves, to wash hands after use and to work with a good ventilation of area, and suitable fumes extraction system locally installed.

Its use during soldering may produce or release fumes which can be sensitizing for the respiratory system to asthmatics.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 7440-31-5 EC: 231-141-8 REACH: 01-2119486474-28-0033 TIN		[1]	55.00 - 58.00 %
CAS: 7439-92-1 EC: 231-100-4 REACH: 01-2119513221-59-XXXX LEAD	GHS08 Dgr Repr. 1A, H360FD STOT RE 1, H372	[1] [2] [6]	32.00 - 34.00 %
CAS: 65997-06-0 EC: 266-041-3 REACH: 01-2119487113-41-0000 MODIFIED ROSIN			1.50 - 11.00 %
CAS: 7440-22-4 EC: 231-131-3 REACH: 01-2119555669-21-0025 SILVER		[1]	1.00 - 2.00 %

(Full text of H-phrases: see section 16)

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.
[6] Substances of very high concern (SVHC).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

Take affected persons into fresh air. If irritation persists, get medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
If it appears pain, redness or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Immediately wash with water and soap and rinse thoroughly.
If skin irritation persists, get medical attention.



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

If burns should occur from molten metal, treat for burn and get medical assistance if necessary.

Beware of products that may remain between the skin and clothes , the watch , the shoes...

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- dry chemical agents
- sprayed water or water mist
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- toxic and irritating fumes

Molten metal reacts violently with oxidising agents.

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Wear full body protective clothing and appropriate self-contained breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Keep away from heat and sun. Keep away from flames and sources of ignition.

For non first aid worker

Keep persons without protective equipment away from danger area.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

After cooling, contain and collect spillage with absorbent materials.

6.4. Reference to other sections

No data available.

**SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG****SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.
Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.
Remove and wash contaminated clothing before re-using.
The workplace must be ventilated and fumes must be captured at the emission source.
Wear protective shoes and gloves.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Do not store with food products.
Keep container closed when the product is not used.
Store in the original packaging, sealed, in the refrigerator (between 5 and 10°C), protected from the weather and away from sources of heat, for a period of 12 months.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
7440-22-4	0.1	-	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7440-31-5	2 mg/m3				
7439-92-1	0.05 mg/m3	-	-	-	-
7440-22-4	0.1 mg/m3	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
7440-22-4		0,1 E mg/m ³		8(II)

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
7439-92-1	-	0.15	-	-	-	1
7440-22-4	-	0.1	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

**SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG**

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7440-22-4	- ppm 0,1 mg/m ³	- ppm - mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

SILVER (CAS: 7440-22-4)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Inhalation.
Long term systemic effects.
0.1 mg of substance/m³**Final use:**Exposure method:
Potential health effects:
DNEL :**Consumers.**Ingestion.
Long term systemic effects.
1.2 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
0.04 mg of substance/m³

MODIFIED ROSIN (CAS: 65997-06-0)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Long term systemic effects.
17 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
117 mg of substance/m³**Final use:**Exposure method:
Potential health effects:
DNEL :**Man exposed via the environment.**Ingestion.
Long term systemic effects.
10 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Dermal contact.
Long term systemic effects.
10 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
35 mg of substance/m³

TIN (CAS: 7440-31-5)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Short term systemic effects.
133.3 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Dermal contact.
Long term systemic effects.
133.3 mg/kg body weight/dayExposure method:
Potential health effects:Inhalation.
Short term systemic effects.



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

DNEL : 11.75 mg of substance/m³

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 11.75 mg of substance/m³

Final use:

Consumers.

Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 80 mg/kg body weight/day

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 80 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 80 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 80 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 3.476 mg of substance/m³

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 3.476 mg of substance/m³

Predicted no effect concentration (PNEC):

SILVER (CAS: 7440-22-4)

Environmental compartment: Soil.
PNEC : 0.794 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.04 µg/l

Environmental compartment: Sea water.
PNEC : 0.86 µg/l

Environmental compartment: Fresh water sediment.
PNEC : 438.13 mg/kg

Environmental compartment: Marine sediment.
PNEC : 438.13 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 25 µg/l

MODIFIED ROSIN (CAS: 65997-06-0)

Environmental compartment: Soil.

SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

PNEC :	0.00045 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.0016 mg/l
Environmental compartment: PNEC :	Sea water. 0.00016 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.016 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.007 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.0007 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 1000 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Suitable type of protective clothing :

- protective work clothing
- protective shoes

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Independent breathing apparatus for respiratory protection :

It is recommended to set up a fumes exhaust system closer to their emission. In case of insufficient ventilation, wear suitable respiratory equipment. In case of formation of vapors, wear suitable respiratory equipment with filter.

- Thermal risks

The product could cause burns during soldering.



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Paste.
Color : gray

Important health, safety and environmental information

pH : Not relevant.
Boiling point/boiling range : Not specified.
Flash point interval : Not relevant.
Vapour pressure (50°C) : Not relevant.
Density : > 1
Water solubility : Insoluble.
Melting point/melting range : Not specified.
Self-ignition temperature : Not specified.
Decomposition point/decomposition range : Not specified.

9.2. Other information

Solidus / Liquidus temperature (Sn62Pb36Ag2) : 178°C / 180°C

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

The product is stable under normal conditions of use and storage, but reacts with strong oxidisers.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

Reaction with strong oxidizers.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No hazardous decomposition under normal conditions of use.

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Known human reproductive toxicant.
May damage fertility and the unborn child.
Causes severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances

Acute toxicity :

SILVER (CAS: 7440-22-4)

Oral route : 2000 < LD50 <= 5000 mg/kg
Species : Rat

Dermal route : 2,000 < LD50 <= 5000 mg/kg
Species : Rat

Inhalation route (n/a) : LC50 = 5.16 mg/l
Species : Rat



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

Duration of exposure : 4 h

MODIFIED ROSIN (CAS: 65997-06-0)

Oral route :

LD50 > 5000 mg/kg
Species : Rat

Dermal route :

2,000 < LD50 <= 5000 mg/kg
Species : Rat

TIN (CAS: 7440-31-5)

Oral route :

2000 < LD50 <= 5000 mg/kg
Species : Rat

Dermal route :

2,000 < LD50 <= 5000 mg/kg
Species : Rat

Inhalation route (n/a) :

LC50 > 4.75 mg/l
Species : Rat
Duration of exposure : 4 h

Skin corrosion/skin irritation :

SILVER (CAS: 7440-22-4)

Corrosivity :

No observed effect.

Germ cell mutagenicity :

MODIFIED ROSIN (CAS: 65997-06-0)

Mutagenesis (in vitro) :

Negative.
Species : Bacteria

With or without metabolic activation.

SILVER (CAS: 7440-22-4)

No mutagenic effect.

Carcinogenicity :

SILVER (CAS: 7440-22-4)

Carcinogenicity Test :

Negative.
No carcinogenic effect.

Reproductive toxicant :

SILVER (CAS: 7440-22-4)

No toxic effect for reproduction

LEAD (CAS: 7439-92-1)

OECD Guideline 414 (Prenatal Developmental Toxicity Study)
OECD Guideline 415 (One-Generation Reproduction Toxicity Study)

Specific target organ systemic toxicity - repeated exposure :

MODIFIED ROSIN (CAS: 65997-06-0)

Species : Rat
Duration of exposure : 90 days

11.1.2. Mixture



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

Acute toxicity :

No adverse health effect is expected under normal conditions of use.

Skin corrosion/skin irritation :

The product may cause sensitization of the skin with prolonged contact.

Serious damage to eyes/eye irritation :

May cause eye irritation due to the fumes during soldering.

Other information

The product massive ingestion can lead to digestive disorders, réneaux, nervous and blood.

The product releases smoke during soldering from the heated rosin, which irritate the respiratory system and may cause an asthmatic type reaction.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 7439-92-1 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

TIN (CAS: 7440-31-5)

Crustacean toxicity :

EC50 = 1.303 mg/l

Species : Ceriodaphnia dubia

MODIFIED ROSIN (CAS: 65997-06-0)

Crustacean toxicity :

EC50 = 726 mg/l

Species : Daphnia sp.

Duration of exposure : 48 h

SILVER (CAS: 7440-22-4)

Fish toxicity :

NOEC = 0.13 mg/l

Species : Menidia beryllina

Duration of exposure : 28 days

Crustacean toxicity :

NOEC = 0.001 mg/l

Duration of exposure : 7 days

Algae toxicity :

NOEC = 0.0012 mg/l

Duration of exposure : 14 days

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

MODIFIED ROSIN (CAS: 65997-06-0)

Biodegradability :

Rapidly degradable.

LEAD (CAS: 7439-92-1)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

SILVER (CAS: 7440-22-4)

Bioaccumulation :

BCF = 70



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.

For professional users only.



SOLDER PASTES SIRIUS 1 : TIN - LEAD - SILVER - CREM SIR1 SNPBAG

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

We cannot anticipate any and all conditions and situations under which the information and our products or the combination of both with others will be used. We do not assume any liability in the safety and suitability of our products alone or in combination with others. Users must make their own tests to determine the safety and suitability of each product used alone or with other products for their own use.

Except any previous written agreement, our products are sold without guarantee and customers must assume all liability for any loss or damage suffered by themselves or by third parties, either from handling or use of our products alone or with others. In case of any difference or variation seen during the use of the products we request that you contact our technical department.

Wording of the phrases mentioned in section 3 :

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure .

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.