

# BUMPER

## Rectangular Buffer 405L x 50W x 50H

SKU.: 0734069




### Features

- **Durable Construction** – Premium NR + SBR blend for superior strength and resilience.
- **Easy Installation:** Pre-drilled countersunk holes for quick, secure fixing
- **Impact Absorption:** Cushions shocks to protect vehicles, equipment, and property.



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# BUMPER



## Bumper Dimensions

Length (mm)	405
Width (mm)	50
Height (mm)	50

# BUMPER

## Product Description

**Rectangular Buffers** are a versatile solution designed for a wide range of applications, including use on boats, lorries, trailers, and docking bays. Manufactured from a durable blend of NR and SBR rubber, these heavy-duty buffers deliver exceptional abrasion resistance, tear strength, and impact resilience, making them ideal for safeguarding vehicles, equipment, and property against damage. Their robust design ensures reliable performance in demanding environments, whether protecting fleets of vans and lorries during loading and unloading, cushioning forklift trucks in warehouses and loading bays, preventing impact damage to fragile glass rack carriers in transit, or serving as effective door and furniture buffers to reduce wear and scratches. Built to endure harsh outdoor conditions and easy to install with pre-drilled countersunk holes, Rectangular Buffers provide long-lasting protection and enhanced safety across industrial, commercial, and residential settings.

## General Specifications

<b>Material</b>	NR/SBR
<b>Colour</b>	Black

## Mechanical Specifications

<b>Weight</b>	0.09KG
<b>Tensile Strength</b>	4Mpa
<b>Elongation</b>	200%
<b>Hardness</b>	75ShA

## Operation Environment Specifications

<b>Maximum Temperature</b>	70°C
<b>Minimum Temperature</b>	-15°C