



# SmartConnect Wi-Fi Solutions: SAM W23

Embedded ultra-low-power Wi-Fi solutions connecting embedded systems to the 'Internet of Things'



The Internet of Things. Made easy.

Atmel® SmartConnect Wi-Fi is a family of self-contained, low-power and certified modules bringing wireless Internet connectivity to any embedded design. These integrated modules offer the ideal solutions for designers seeking to add to integrate Wi-Fi connectivity with no previous experience with 802.11, RTOS, IP Stack or RF experience. SmartConnect Wi-Fi from Atmel opens the door of the Internet of Things to the vast array of battery-powered devices and applications requiring the integration of WLAN connectivity without compromising on cost and power consumption.


The Wi-Fi SAM W23 modules are based on Atmel's industry-leading ultra-low-power Wi-Fi SoC (System on Chip) combined with Atmel's latest ARM® Cortex®-M0+ based microcontroller technology. This turnkey system provides an integrated software solution with application and security protocols such as TLS, integrated network services (TCP/IP stack), and a standard Real Time Operating System (RTOS) which are all available through Atmel's Studio 6 integrated development platform (IDP).

### SAM W23 Target Applications:

- Battery powered devices
- Smart appliances
- Healthcare
- Home automation
- Consumer electronics
- Industrial automation


### SmartConnect SAM W23 key features:

- Atmel's Wi-Fi SoC and SAM D21 ARM Cortex-M0+ MCU
- WPA/WPA2, WEP, TKIP
- Wi-Fi SoftAP/STA modes
- Out Of the Box Network Services (TCP/IP, UDP, HTTP, HTTPS, DHCP, DNS, SSL/TLS)
- Ultra-low <20uA SUSPEND current for years of battery life
- Can operate completely host-less in most applications
- Direct-connect to battery 1.8V to 3.6V range
- Options from 0dbm to +17dbm output power



## Modules Specification

Parameters	Value
Transmit Power	0dBm, +10dBm, +17dBm
Receive Sensitivity	-81 dBm, 10% PER, 11Mbps
Size	20.0 x 34.3 mm
Connector Pins Pitch	1.0 mm
Operating temperatures	0°C to +70°C
Certifications	Wi-Fi, FCC, CE
OTA flash	SAM W23-MD2
Power Amplifier Front-End Module	SAM W23-MD5




## Ultra-Low Power

Atmel's Wi-Fi SoC and MCUs are optimized for battery-powered applications with a wide 1.8V to 3.6V voltage range and a <20uA deep sleep current with an instant on/off radio architecture. This results in an ultra low power profile when implemented in an IoT Edge Node sending data to an SSL server several times per day. With the SAM W23, Wi-Fi can now penetrate markets and products requiring years of battery life.

## Getting Started

Mounted on an XPRO Wing, SAM W23 is compatible with any existing Atmel Xplained Pro evaluation board. The Smart-Connect library is a turnkey Software Framework available in Atmel Studio that removes the need to understand the Wi-Fi stack. This allows developers to focus on adding functions.



Part Number	Features	Sampling
ATSAMW23G18-MD110PA	Entry level	June 2014
ATSAMW23G18-MD210PA	Onboard OTA Flash	June 2014
ATSAMW23E18-CHPST1A	Chipset	June 2014
ATSAMW23-NC-STK	Starter Kit	June 2014
ATSAMW23G18- MD510	Onboard PA FEM	Sept 2014



**Atmel** | Enabling Unlimited Possibilities®



**Atmel Corporation** 1600 Technology Drive, San Jose, CA 95110 USA **T**: (+1)(408) 441.0311 **F**: (+1)(408) 436.4200 | **www.atmel.com**

© 2014 Atmel Corporation. / Rev.: Atmel-45079A-SmartConnect-Wi-Fi-Solutions\_E\_US\_060214

Atmel®, Atmel logo and combinations thereof, Enabling Unlimited Possibilities®, and others are registered trademarks or trademarks of Atmel Corporation in U.S. and other countries. ARM®, ARM Connected® logo and others are the registered trademarks or trademarks of ARM Ltd. Other terms and product names may be trademarks of others.

Disclaimer: The information in this document is provided in connection with Atmel products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Atmel products. EXCEPT AS SET FORTH IN THE ATMEL TERMS AND CONDITIONS OF SALES LOCATED ON THE ATMEL WEBSITE, ATMEL ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL ATMEL BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS AND PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF ATMEL HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Atmel makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and products descriptions at any time without notice. Atmel does not make any commitment to update the information contained herein. Unless specifically provided otherwise, Atmel products are not suitable for, and shall not be used in, automotive applications. Atmel products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.