# 1-1644055-3 ACTIVE

TE Internal #: 1-1644055-3

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 6 Position, 6.35 mm [.25 in] Centerline, Wire & Cable, UL 94V-0, GWT 750°C (Without Flame)

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug Connector System: Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 6.35 mm [ .25 in ]

## **Features**

## Product Type Features

| Rectangular Power Connector Type  | Housing      |
|-----------------------------------|--------------|
| Connector & Housing Type          | Plug         |
| Connector System                  | Wire-to-Wire |
| Sealable                          | No           |
| Connector & Contact Terminates To | Wire & Cable |

## **Configuration Features**

| Number of Positions | 6 |
|---------------------|---|
| Number of Rows      | 2 |

## **Electrical Characteristics**

| Operating Voltage | 600 VAC |
|-------------------|---------|
|-------------------|---------|

## **Contact Features**

| Contact Retention Within Housing | Without |
|----------------------------------|---------|
| Contact Type                     | Socket  |

## **Termination Features**



| Termination Method to Wire & Cable | Crimp                      |
|------------------------------------|----------------------------|
| Mechanical Attachment              | Сппр                       |
|                                    |                            |
| Mating Alignment Type              | Polarization               |
| Mating Alignment                   | With                       |
| Connector Mounting Type            | Cable Mount (Free-Hanging) |
| Housing Features                   |                            |
| Centerline (Pitch)                 | 6.35 mm[.25 in]            |
| Housing Color                      | Natural                    |
| Housing Material                   | PA 66                      |
| Dimensions                         |                            |
| Row-to-Row Spacing                 | 6.35 mm[.25 in]            |
| Height                             | 13.97 mm[.55 in]           |
| Length                             | 20.32 mm[.8 in]            |
| Width                              | 27.43 mm[1.079 in]         |
| Usage Conditions                   |                            |
| Operating Temperature Range        | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application              |                            |
| Circuit Application                | Power                      |
| Industry Standards                 |                            |
| UL Flammability Rating             | UL 94V-0                   |
| Glow Wire Rating                   | GWT 750°C (Without Flame)  |
| UL Rating                          | Recognized                 |
| Agency/Standard Number             | E28476                     |
| CSA File Number                    | LR7189                     |
| VDE Tested                         | Yes                        |
| Agency/Standard                    | CSA                        |
| Packaging Features                 |                            |
| Packaging Method                   | Bag                        |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



| EU ELV Directive 2000/53/EC                   | Compliant   |
|---|---|
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Not reviewed for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**

























## **Documents**

## **Product Drawings**

06P UMNL PLUG HSG GWEPT-V0 WINDOW LATCH

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1644055-3\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1644055-3\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1644055-3\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Product Specification** 

English

## **Agency Approvals**

**CSA Certificate** 

English