

1-2834331-1 ✓ ACTIVE

Buchanan WireMate | Insulation Displacement Connectors Closed End


TE Internal #: 1-2834331-1

1 Position Ballast Connector, Connector, Wire-to-Board, 6.5 mm Centerline, Printed Circuit Board, Insulation Displacement Connectors Closed End

[View on TE.com >](#)



Connectors > Lighting Connectors > Ballast Connectors



Number of Positions: 1

Lighting Product Type: **Connector**

Connector System: **Wire-to-Board**

Centerline (Pitch): **6.5 mm**

Sealable: **No**

Features

Product Type Features

Lighting Product Type	Connector
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Rows	1
Number of Positions	1

Electrical Characteristics

Operating Voltage (Max)	320 VAC
-------------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Current Rating (Max)	6 A
------------------------------	-----



Mechanical Attachment

Mating Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.5 mm
--------------------	--------

Dimensions

Wire Size	18 – 22 AWG
-----------	-------------

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL 1977

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




Also in the Series | Insulation Displacement Connectors Closed End



Customers Also Bought





Documents

Product Drawings

[6.5PITCH ITB CONN_1P_W CAP_NATURAL](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_1-2834331-1_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-2834331-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-2834331-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[BUCHANAN WIREMATE ITB RELEASABLE POKE-IN CONNECTORS](#)

English

[BUCHANAN WIREMATE ITB RELEASABLE POKE-IN CONNECTORS](#)

Product Specifications

[Application Specification](#)

English

Agency Approvals

1-2834331-1

1 Position Ballast Connector, Connector, Wire-to-Board, 6.5 mm Centerline, Printed Circuit Board, Insulation Displacement Connectors Closed End



[UL](#)

English