

381166348	DATA SHEET	
Valid from: 05.11.2024	EPIC® POWER M12E SCREW 4+FE	

Description:

- Circular connectors for power transmission
- Straight version with cable aperture 8 mm - 12 mm
- High-quality gold-plated screw contacts



Product variants:

Article number	Type	Pole image	Cable diameter
381166348	Cable plug with male contacts (F6)	E-Coded; 4+FE	8 mm - 12 mm
381166349	Cable socket with female contacts (D6)	E-Coded; 4+FE	8 mm - 12 mm

General characteristics:

Series	Power M12
Coding	E-coded
Type	Cable plug/cable socket, straight
Pole image	4+FE
Rated voltage	63 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Rated current	16 A
Contact resistance	≤ 10 mΩ
Connection cross-section	Screw contacts 0.5 - 2.5 mm²
Cable connection	8 mm - 12 mm
Protection class	IP 67 according to IEC 60529
Mating cycles	> 100
Temperature range	-25°C up to +85°C
Tightening torque Contact	0.3 Nm
Tightening torque cable clamp	0.6 Nm
Tightening torque for connector locking	0.3 Nm

Materials/surface:

Contacts	Copper alloy
Contact surface	Au (gold)
Contact body material	PA

Standards:

Product standard	DIN EN 61076-2-111
------------------	--------------------

Approvals:


In preparation

Creator: VACH1/BU EPIC Released: JUKL2/BU EPIC	Document: DB381166348EN Version: 00	Page 1 from 2
---------------------------------------------------	----------------------------------------	---------------

381166348	DATA SHEET	
Valid from: 05.11.2024	EPIC® POWER M12E SCREW 4+FE	


Technical drawings

Technical drawing




Cable plug F6

Pole image




Technical drawing



Cable socket D6

Pole image



Assembly:

Sheath length:	25 - 30 mm
Stripping length:	4 - 5 mm
Tightening torque Contact:	0.3 Nm
Cable clamp tightening torque:	0.6 Nm

Areas of application:

Power transmission for mechanical and plant engineering and servomotors

Note:

The photographs are not to scale and are not detailed images of the respective products.
Further information can be found in the product standard.