

SKINDICHT® BL-M

SKINDICHT® BL-M, brass blind plugs for closing pre-threaded holes, assembling with screwdriver



Temperature-resistant



Reliability



Robust



Corrosion-resistant

Benefits

For closing pre-threaded holes
Assembling with screwdriver

Application range

Machine and equipment manufacturing
Electric motor manufacturing

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000032

ETIM 5.0 Class-Description: Plug for cable screw gland

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000032

ETIM 6.0 Class-Description: Plug for cable screw gland

On request:

Fitted with FKM O-ring

Last Update (10.11.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® BL-M

Material:	Body: nickel-plated brass
Protection rating:	IP 54 IP 68 (with O-Ring)
Temperature range:	With O-ring: -30°C to +100°C Without O-ring: -60°C to +200°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINDICHT® BL-M

Article number	Article designation / size	PL_DURCHMESSERAUSSEN	Outer Ø (mm)
SKINDICHT® BL-M			
52103100	M 12 x 1,5	14	14.0
52103110	M 16 x 1,5	18	18.0
52103120	M 20 x 1,5	22	22.0
52103130	M 25 x 1,5	28	28.0
52103140	M 32 x 1,5	35	35.0
52103150	M 40 x 1,5	44	44.0
52103160	M 50 x 1,5	54	54.0
52103170	M 63 x 1,5	70	70.0
52103190	M 75 x 1,5	80	80.0
SKINDICHT® BL-M with O-ring			
52103105	M 12 x 1,5	14	14.0
52103115	M 16 x 1,5	18	18.0
52103125	M 20 x 1,5	22	22.0
52103135	M 25 x 1,5	28	28.0
52103145	M 32 x 1,5	35	35.0
52103155	M 40 x 1,5	44	44.0
52103165	M 50 x 1,5	54	54.0
52103175	M 63 x 1,5	70	70.0

Last Update (10.11.2018)

©2018 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16