

Image may differ from product. See technical specification for details.

3309 DNRCBM

Double row angular contact ball bearing with snap ring and split inner ring

Double row angular contact ball bearings, with snap ring and split inner ring, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement. The snap ring, fitted in an annular groove in the outer ring, facilitates axial location of the bearings within their housings. The split inner ring enables incorporation of more balls, resulting in higher load carrying capacity.

- Snap ring facilitates axial location within housing
- Accommodate very high axial loads in both directions, radial loads, and tilting moments
- Suitable where a stiff bearing arrangement is required
- Require less axial space than equivalent pair of single row angular contact ball bearings

Overview

Dimensions

Bore diameter	45 mm
Outside diameter	100 mm
Width	39.7 mm
Contact angle	40 °

Performance

Basic dynamic load rating	61.8 kN
Basic static load rating	52 kN
Reference speed	7 500 r/min
Limiting speed	6 300 r/min


Properties

Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Snap ring (fitted)
Ring type	Two-piece inner ring and one-piece outer ring
Cage	Machined brass
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CB
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	5.6 kg CO_2e

Logistics


Product net weight	1.51 kg
eClass code	23-05-08-03
UNSPSC code	31171531

Technical specification



Dimensions

d	45 mm	Bore diameter
D	100 mm	Outside diameter
B	39.7 mm	Width
d_1	≈ 67.95 mm	Shoulder diameter inner ring for two-piece inner ring
D_1	≈ 86.53 mm	Shoulder diameter outer ring
D_3	96.8 mm	Snap ring groove diameter at outer ring
D_4	106.5 mm	Outside diameter snap ring
C	3.28 mm	Distance outer ring side face - snap ring groove
b	2.7 mm	Width snap ring groove outer ring
f	2.46 mm	Width snap ring
r_0	max. 0.6 mm	Snap ring groove bottom radius
$r_{1,2}$	min. 1.5 mm	Chamfer dimension inner ring for two-piece inner ring
a	79 mm	Distance pressure point(s)



Abutment dimensions

d_a	min. 54 mm	Abutment diameter shaft
r_a	max. 1.5 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	61.8 kN
Basic static load rating	C_0	52 kN
Fatigue load limit	P_u	2.2 kN
Reference speed		7 500 r/min
Limiting speed		6 300 r/min
Calculation factor	k_r	0.095
Limiting value	e	1.1
Calculation factor	X	0.57
Calculation factor	Y_0	0.52
Calculation factor	Y_1	0.55
Calculation factor	Y_2	0.93

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5
- Internal clearance: table, drawing no

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) (“SKF”), you agree to the following terms and conditions:

Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using YouTube API Services), you agree to be bound by the YouTube Terms of Service.

Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

Changes

SKF reserves the right to make changes or additions to this website / app at any time.