

standard motor mechanism module MT250, ComPact NSX250, 380/415 VAC 50/60 Hz, 440/480 VAC 60 Hz

Local distributor code: 391355574

LV431542

EAN Code: 3606480020094

Main

Device short name	MT250	
Product or component type	Motor mechanism	
Device application	Automatic spring charging	
Range compatibility	ComPacT NSX250 ComPacT NSX250 DC	
control type	Standard	
[Uc] control circuit voltage	380415 V AC 50/60 Hz 440480 V AC 60 Hz	
circuit breaker mounting mode	Fixed	
circuit breaker frame rated current	250 A	

Complementary

Control signal type	Maintained Impulse
circuit breaker response time	< 700 ms open < 80 ms closed
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.100 cm
Package 1 Width	10.500 cm
Package 1 Length	17.300 cm
Package 1 Weight	1.385 kg
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm

Package 2 Length	60.000 cm
Package 2 Weight	21.475 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	14
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	A3dc0f23-906d-490a-acce-c58e25990143
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins