

Flat indicator lights

Rotation-proof
Waterproof IP64 / IP67 / IP68

Flach-Leuchten

Verdrehsicher
Wasserdicht IP64 / IP67 / IP68

Voyants lumineux plats

Anti-rotation
Étanche IP64 / IP67 / IP68



3D Step-file
available on request



Series 343 / 344 / 348



344S1G1G71NB

348S11R1R50UB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps			Accessories Zubehör Accessoires	Lens with.. Linse mit.. Lentille avec..	Light source Lichtquelle Source lum.	Voltage Spannung Tension								
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface			Fresnel	LED Ø 5mm	Code	V	mA						
343 LED terminals LED-Anschlüsse Fils des LED's	4 IP64	B Brass, blackened Messing, geschwärzt Laiton, noircie	1 	A1 Amber Orange Orange		Y54U 7'000 mcd		0	without ohne sans						
	7 IP67	S Brass, nickel plated Messing, vernickelt Laiton, nickelée				Y50U 3'000 mcd		A	5	20					
	8 IP68	5 Stainless steel Edelstahl Acier inoxydable				5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305		Y501 80 mcd	B	12	20				
		6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie						G1 Green Grün Vert	B91G 9'000 mcd		D	24	20		
344 Faston 2.8 x 0.5	8 IP68	9 Brass, olive darb** Messing, olivebraun** Laiton, olivebrun**		R1 Red Rot Rouge		B21G 2'120 mcd		E	24		20				
						W3 White Weiss Blanc			B61G 1'160 mcd		CL	9-48	20		
									G81N 32'500 mcd			constant current driver only for Series 344, 348 and only for single colour			
										G71N 5'620 mcd					
348 Stranded wire Litze Fil multi-brins Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	4 IP64	1 Brass, blackened Messing, geschwärzt Laiton, noircie	1 	A1 Amber Orange Orange		R54U 7'000 mcd		Z	230	5					
	7 IP67	2 Brass, nickel plated Messing, vernickelt Laiton, nickelée				R50U 3'000 mcd									
	8 IP68	5 Stainless steel Edelstahl Acier inoxydable				5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305		C1 Clear Klar Claire	R521 80 mcd	only for Series 348*					
		6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie						G1 Green Grün Vert	W55N 22'000 mcd						
		9 Brass, olive darb** Messing, olivebraun** Laiton, olivebrun**							R1 Red Rot Rouge		W50N 2'320 mcd		Red-Green Rot-Grün Rouge-Vert		
									W3 White Weiss Blanc					RGWW common cathode	
			RGVW common anode only series 343, 348												

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G“

Réserve de modifications de toutes les données techniques

34..

