



**Part Number :** [732511150](#)  
**Product Description :** SMA Jack, Straight, PCB  
Receptacle, Edge Mount, Brass Body, .25µm Gold (Au)  
Plating, 80 Pieces Per Tray, 50 Ohms  
**Series Number :** 73251  
**Status :** Active  
**Product Category :** RF / Coaxial Connectors



## Documents & Resources

### Drawings


[732511150 sd.pdf](#)  
[895420040-000.pdf](#)

### 3D Models and Design Files

[732511150 stp.zip](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### Substances of Interest

- PFAS

#### EU RoHS Certificate of Compliance

#### Additional Product Compliance Information

---

## Part Details

### General

Status	Active
Category	RF / Coaxial Connectors
Series	73251
Description	SMA Jack, Straight, PCB Receptacle, Edge Mount, Brass Body, .25µm Gold (Au) Plating, 80 Pieces Per Tray, 50 Ohms
Product Name	SMA
Style	PCB
Type	Subminiature
UPC	756054901984

### Electrical

Frequency	18 GHz
Impedance	50Ω
Power / Voltage	VOLTAGE: 500 Vrms@Sea Level

### Physical

Cable Attachment	N/A
Gender	Jack
Keying to Mating Part	N/A
Net Weight	1.889/g
Orientation	Straight
Packaging Type	Tray
Panel Mount	No
Panel Mount Method	N/A

PCB Mounting	Edge Mount
PCB Thickness - Recommended	1.60mm
Reverse Polar	No
Wire/Cable Type	N/A

**Solder Process Data**

Max-Duration	10
Lead-Free Process Capability	REFLOW
Max-Cycle	2
Max-Temp	260